



COMMISSION OF THE EUROPEAN COMMUNITIES

Brussels, 20.11.1996
COM(96) 578 final

Proposal for a

COUNCIL REGULATION (EC)

amending the Annex to Council Regulation (EC) No 1255/96 temporarily suspending
the autonomous Common Customs Tariff duties on certain
industrial and agricultural products

(presented by the Commission)

EXPLANATORY MEMORANDUM

1. During the third quarter of this year, the Commission, assisted by the Economic Tariff Problems Group, has reviewed requests for temporary suspension of autonomous Common Customs Tariff duties presented to it by the Member States, including certain requests amending existing suspensions.
2. The attached proposal concerns certain industrial and agricultural products.
3. The requests for suspension relating to the above products were examined in the light of the criteria set out in the communication from the Commission to the Council and the Member States concerning autonomous tariff suspensions (see OJ C 235, 13.9.1989, p. 2).

Following this review, the Commission considers that the suspension or reduction of duties is justified for the products listed in Annex I to the attached proposal of Regulation.

It also considers that for products listed in Annex II to this proposal of Regulation, maintenance of suspension is no longer justified in the light of the Community's economic interests.

This Regulation has two Annexes corresponding, respectively, to the list of products for which suspension is proposed, or for which the wording (including the nomenclature code) has to be changed, and the list of products removed from the Annex to Regulation (EC) No 1255/96.

Amendments to the description of certain products listed in the Annex to Regulation (EC) No 1255/96, where they have become necessary, have been taken into account as follows:

- addition to the nomenclature code for the product (listed in the Annex to Regulation (EC) No 1255/96) in Annex II,
- addition of the new amended product description in Annex I.

4. The period of validity of the proposed measure is unspecified, since its purpose is to amend the Annex to Council Regulation (EC) No 1255/96, the period of validity of which is itself unspecified.

Proposal for a
COUNCIL REGULATION (EC) No /96

amending the Annex to Council Regulation (EC) No 1255/96 temporarily suspending the autonomous Common Customs Tariff duties on certain industrial and agricultural products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 28 thereof,

Having regard to the proposal from the Commission,

Having regard to Council Regulation (EC) No 1255/96 temporarily suspending the autonomous Common Customs Tariff duties on certain industrial and agricultural products,¹

Whereas it is in the interest of the Community to suspend partially or totally the autonomous Common Customs Tariff duties for a number of new products not listed in the Annex to Regulation (EC) No 1255/96,

Whereas the products referred to in that Regulation, for which it is no longer in the Community's interest to maintain suspension of autonomous Common Customs Tariff duties or for which it is necessary to amend the description in the light of technical developments, must be withdrawn from the list in the Annex thereto,

Whereas, for the sake of clarity, it is therefore advisable to regard the products for which amendments to the description are required as new products,

HAS ADOPTED THIS REGULATION:

Article 1

The products set out in Annex I to this Regulation are hereby added to the Annex to Regulation (EC) No 1255/96. The autonomous Common Customs Tariff duties on these products are hereby suspended at the rate indicated for each product.

Article 2

The products for which the codes are set out in Annex II to this Regulation are hereby removed from the Annex to Regulation (EC) No 1255/96.

Article 3

This Regulation shall enter into force on 1 January 1997.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at,

*For the Council
The President*

¹ OJ No L 158, 29.6.1996, p.1.

ANNEX I

CN code & TARIC	Description	Rate of autonomous duty (%)
0007 ex2819 90 90 10	Dichromium trioxide: - of a specific surface of 37 m ² /g or more (as determined by the BET method), - of a purity by weight of 99,5 % or more calculated on the dry substance, - of a specific gravity of 1,2 g/cm ³ or less, for the manufacture of magnetic tapes (a)	0
0009 ex2825 10 00 10	Aqueous solution containing by weight 49 % or more of stabilized free hydroxylamine	0
0014 ex2830 20 00 10	Zinc sulphide containing: - 20,0 mg/kg or less of chloride, - 0,2 mg/kg or less of copper, - 0,5 mg/kg or less of iron and - 1,0 mg/kg or less of lead	0
0021 ex2902 90 80 10	<i>p</i> -Cymene	0
0022 ex2902 90 80 15	2-Methylnaphthalene	0
0020 ex2902 90 80 25	1,2-Di(3,4-xylyl)ethane	0
0023 ex2902 90 80 30	1,2,4,5-Tetramethylbenzene (durene)	0
0028 ex2903 69 90 40	2,6-Dichlorotoluene, of a purity by weight of 99 % or more and containing: - 0,001 mg/kg or less of tetrachlorodibenzodioxines, - 0,001 mg/kg or less of tetrachlorodibenzofurans, - 0,2 mg/kg or less of tetrachlorobiphenyls	0
0201 ex2904 90 80 20	Quintozene (ISO)	0
0039 ex2905 39 80 10	2-Methylpropane-1,3-diol	0
0062 ex2915 60 19 10	2,2,4-Trimethylpentane-1,3-diol monoisobutyrate	0
0073 ex2917 39 80 10	Dimethyl naphthalene-2,6-dicarboxylate	0
0074 ex2917 39 80 20	Benzene-1,2,4,5-tetracarboxylic acid (pyromellitic acid)	0
0090 ex2921 19 80 10	Triallylamine	0
0089 ex2921 19 80 20	Ethyl(2-methylallyl)amine	0
0094 ex2921 30 99 10	Dicyclohexyl(methyl)amine	0
0095 ex2921 42 10 40	2-Bromo-6-chloro-4-nitroaniline	0
0100 ex2921 43 90 20	4-Amino-6-chlorotoluene-3-sulphonic acid	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0104	ex2921 49 90 10	8-Anilinonaphthalene-1-sulphonic acid	0
0105	ex2921 59 90 10	Mixture of isomers of 3,5-diethyltoluenediamine	0
0123	ex2924 29 90 10	Alachlor (ISO)	0
0122	ex2924 29 90 20	3'-Amino-4'-methoxyacetanilide	0
0120	ex2924 29 90 30	5-Amino-N,N'-bis(2,3-dihydroxypropyl)-2,4,6-triiodoisophthalamide	0
0121	ex2924 29 90 70	4'-Amino-N-methylacetanilide	0
0130	ex2926 90 80 10	Methacrylonitrile	0
0131	ex2926 90 80 20	Ethyl 1-cyanocyclohexylacetate	0
0132	ex2926 90 80 30	2-Amino-5-nitrobenzonitrile	0
0133	ex2926 90 80 40	Chlorothalonil (ISO)	0
0134	ex2926 90 80 45	2-Cyanoacetamide	0
0135	ex2926 90 80 50	Alkyl or alkoxyalkyl esters of cyanoacetic acid	0
0139	ex2928 00 90 10	3,3'-Bis(3,5-di-tert-butyl-4-hydroxyphenyl)-N,N'-bipropionamide	0
0140	ex2928 00 90 20	2,4,6-Trichlorophenylhydrazine	0
0145	ex2930 90 70 10	Thiophenol	0
0146	ex2930 90 70 15	Ethoprophos (ISO)	0
0147	ex2930 90 70 20	3,3-Dimethyl-1-methylthiobutanone oxime	0
0148	ex2930 90 70 25	Thiophanate-methyl (ISO)	0
0149	ex2930 90 70 30	4-(4-Isopropoxyphenylsulphonyl)phenol	0
0150	ex2930 90 70 40	3,3'-Thiodi(propionic acid)	0
0110	ex2930 90 70 45	2-[(p-Aminophenyl)sulphonyl]ethyl hydrogen sulphate	0
0163	ex2932 29 80 10	2'-Anilino-6'-[ethyl(isopentyl)amino]-3'-methylspiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0
0164	ex2932 29 80 15	13,14,15,16-Tetranorlabdano-12,8a-lactone	0
0165	ex2932 29 80 25	2'-(2-Chloroanilino)-6'-dibutylaminospiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0
0166	ex2932 29 80 30	2'-Anilino-3'-methyl-6'-methyl(propyl)aminospiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0
0167	ex2932 29 80 35	6'-Diethylamino-3'-methyl-2'-(2,4-xylidino)spiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0168	ex2932 29 80 40	2'-Anilino-6'-(N-ethyl-p-toluidino)-3'-methylspiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0
0169	ex2932 29 80 45	2'-Anilino-6'-ethyl(isobutyl)amino-3'-methylspiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0
0170	ex2932 29 80 50	2'-Anilino-6'-cyclohexyl(methyl)amino-3'-methylspiro[isobenzofuran-1(3H),9'-xanthen]-3-one	0
0171	ex2932 29 80 55	6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide	0
0178	ex2933 39 95 10	Cloperastine fendizoate (INN)	0
0179	ex2933 39 95 15	Pyridine-2,3-dicarboxylic acid	0
0180	ex2933 39 95 20	5-Methyl-2-pyridylamine	0
0181	ex2933 39 95 25	Imazethapyr (ISO)	0
0182	ex2933 39 95 30	4,4'-Trimethylenedipiperidine	0
0185	ex2933 59 70 10	1-Ethyl-6-fluoro-1,4-dihydro-4-oxo-7-piperazin-1-yl-1,8-naphthyridine-3-carboxylic acid and its salts and esters	0
0186	ex2933 69 80 10	1,3,5-Tris(4-tert-butyl-3-hydroxy-2,6-dimethylbenzyl)-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	0
0187	ex2933 69 80 20	1,3,5-Tris[(3,5-di-tert-butyl-4-hydroxyphenyl)methyl]-1,3,5-triazine-2,4,6(1H,3H,5H)-trione	0
0188	ex2933 69 80 30	Tris(2,3-epoxypropyl)-1,3,5-triazinetrione	0
0189	ex2933 69 80 40	Cyanazine (ISO)	0
0191	ex2933 90 95 10	2-(2H-Benzotriazol-2-yl)-4,6-di-tert-butylphenol	0
0192	ex2933 90 95 15	2-(2H-Benzotriazol-2-yl)-4,6-di-tert-pentylphenol	0
0193	ex2933 90 95 20	2-(2H-Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol	0
0194	ex2933 90 95 25	6,6'-Di-2H-benzotriazol-2-yl-4,4'-bis(1,1,3,3-tetramethylbutyl)-2,2'-methylenediphenol	0
0195	ex2933 90 95 30	Quizalofop-P-ethyl (ISO)	0
0196	ex2933 90 95 35	Indoline	0
0184	ex2933 90 95 45	Maleic hydrazide (ISO)	0
0202	ex2934 90 98 10	7-Chloro-5-methyl-2H-1,4-benzothiazin-3-(4H)-one	0
0203	ex2934 90 98 20	Carboxin (ISO)	0
0204	ex2934 90 98 30	4-[4-(Tridecyl[branched]oxy)phenyl]-1,4-thiazinane 1,1-dioxide	0
0200	ex2934 90 98 40	Oxycarboxin (ISO)	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0199 ex2934 90 98 50	Etridiazole (ISO)	0
0205 ex2935 00 90 10	Salts of sulfathiazole (INN)	0
0206 ex2935 00 90 20	Toluenesulphonamides	0
0207 ex2935 00 90 30	Mixture of isomers consisting of N-ethyltoluene-2-sulphonamide and N-ethyltoluene-4-sulphonamide	0
0366 ex3208 90 19 10 ex3911 90 99 35	Copolymer of maleic acid and methyl vinyl ether, monoesterified with ethyl and/or isopropyl and/or butyl groups, in the form of a solution in ethanol, ethanol and butanol, isopropanol or isopropanol and butanol	0
0223 ex3405 90 90 10	Abrasive powder consisting of particles containing by weight 50 % or more but not more than 55 % of dialuminium trioxide and 26 % or more but not more than 30 % of zirconium dioxide, for working semiconductor wafers (a)	0
0228 ex3507 90 90 10	Asparaginase	0
0229 ex3507 90 90 20	Enzymatic preparation based on thermolysine	0
0230 ex3701 30 00 10	Letterpress printing plates, consisting of a metal substrate covered with a photopolymer layer, of a total thickness of 0,5 mm or more but not exceeding 0,8 mm	0
0232 ex3707 10 00 10	Photosensitive emulsion for the sensitization of silicon discs (a)	0
0245 ex3815 19 90 10	Catalyst, consisting of chromium trioxide or dichromium trioxide fixed on a silicon-dioxide support, of a pore-volume, as determined by the nitrogen-absorption method, of 2 cm ³ /g or more	0
0246 ex3815 19 90 20	Catalyst consisting of chromium oxides and titanium dioxide fixed on a support of silicon dioxide, aluminium oxide or aluminium phosphate	0
0247 ex3815 19 90 30	Catalyst consisting of titanium tetrachloride supported on magnesium dichloride, in the form of a suspension in mineral oil or in hexane, for use in the manufacture of polypropylene (a)	0
0248 ex3815 19 90 40	Catalyst, in the form of spheres of a diameter of 4,2 mm or more but not exceeding 9 mm, consisting of a mixture of oxides of molybdenum, tungsten, vanadium, copper and strontium, on a support of silicon dioxide and/or aluminium oxide, for use in the manufacture of acrylic acid (a)	0
0249 ex3815 19 90 50	Catalyst consisting of organo-metallic compounds of titanium, magnesium and aluminium on a support of silicon dioxide, in the form of a suspension in tetrahydrofuran	0
0250 ex3815 19 90 60	Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide	0
0244 ex3815 19 90 70	Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide	0
0252 ex3815 90 90 15	Catalyst, in the form of rodlets of a diameter of 4 mm or more but not exceeding 6 mm, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, vanadium, nickel and antimony, for use in the manufacture of acrylic acid (a)	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0253 ex3815 90 90 20	Catalyst, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing by weight: - 20 % or more but not more than 30 % of titanium and - 55 % or more but not more than 72 % of chlorine	0
0254 ex3815 90 90 25	Catalyst, in the form of rodlets of a diameter of 4 mm or more but not exceeding 6 mm, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, bismuth, nickel, iron and silicon, for use in the manufacture of acrylaldehyde (a)	0
0255 ex3815 90 90 35	Catalyst, in the form of a suspension in oil, consisting of titanium trichloride and aluminium trichloride, containing by weight (on an oil-free basis): - 15 % or more but not more than 30 % of titanium and - 40 % or more but not more than 72 % of chlorine	0
0256 ex3815 90 90 40	Catalyst, in the form of rodlets of a length of 5 mm or more but not exceeding 8 mm, consisting of a mixture of oxides of iron, molybdenum and bismuth, for use in the manufacture of acrylic acid (a)	0
0257 ex3815 90 90 50	Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium	0
0258 ex3815 90 90 55	Reaction initiator, consisting of a mixture of <i>N,N,N',N'</i> -tetramethyl-2,2'-oxybis(ethylamine) and dipropylene glycols	0
0259 ex3815 90 90 60	Catalyst, in the form of rodlets, consisting of an acid aluminosilicate (zeolite): - with a mole-ratio of silicon dioxide : dialuminium trioxide of not less than 500 : 1 and - containing by weight 0,2 % or more but not more than 0,8 % of platinum	0
0260 ex3815 90 90 65	Catalyst based on a mordenite zeolite, in the form of granules, for use in the manufacture of mixtures of methylamines containing by weight 50 % or more of dimethylamine (a)	0
0261 ex3815 90 90 70	Catalyst, consisting of a mixture of (2-hydroxypropyl)trimethylammonium formate and dipropylene glycols	0
0251 ex3815 90 90 80	Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol	0
0265 ex3818 00 90 10	Wafers of gallium phosphide, with epitaxial layers of gallium arsenide phosphide, doped, for the manufacture of goods of subheading 8541 40 19 (a)	0
0270 ex3824 90 64 01	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Micromonospora purpurea</i> , whether or not dried	0
0271 ex3824 90 64 02	Cholic acid and 3 α ,12 α -dihydroxy-5 β -cholan-24-oic acid (deoxycholic acid), crude	0
0272 ex3824 90 64 03	Products obtained by the <i>N</i> -ethylation of sisomycin (INN)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0273	ex3824 90 64 04	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Micromonospora inyoensis</i> , whether or not dried	0
0274	ex3824 90 64 05	Residues of manufacture containing by weight 40 % or more of 11 β ,17,20,21-tetrahydroxy-6-methylpregna-1,4-dien-3-one-21-acetate	0
0278	ex3824 90 95 01	Colloidal diantimony pentaoxide	0
0279	ex3824 90 95 02	Mixture of nitromethane and 1,2-epoxybutane	0
0280	ex3824 90 95 03	Grains or granules, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight: - 70 % or more but not more than 78 % of dialuminium trioxide and - 19 % or more but not more than 26 % of zirconium dioxide	5.2
0281	ex3824 90 95 04	Crude lithium hypochlorite	0
0282	ex3824 90 95 05	Mixed oxides of barium, titanium and other metals, in the form of powder, containing by weight: - 5 % or more of barium and - 15 % or more of titanium, for use as dielectric materials in the manufacture of multilayer ceramic capacitors (a)	0
0283	ex3824 90 95 06	Preparation, in the form of powder, containing by weight 75 % or more of zinc bis(3,5-bis(1-phenylethyl)salicylate)	0
0284	ex3824 90 95 07	Film consisting of the oxides of barium, calcium and either titanium or zirconium, mixed with binding materials	0
0285	ex3824 90 95 08	Preparation consisting essentially of alkaline asphalt sulphonate, of: - a specific gravity of 0,9 or more but not exceeding 1,5 and - a solubility in water of 70 % by weight or more	0
0286	ex3824 90 95 09	Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulphonic acid, either: - on a support of mineral wax, whether or not modified chemically, or - in the form of a solution in an organic solvent	0
0287	ex3824 90 95 10	Calcined bauxite (refractory grade)	0
0288	ex3824 90 95 11	Magnetisable iron oxide, in the form of powder, containing by weight: - 30 % or more but not more than 38 % of bivalent iron in relation to the total iron and - 1 % or more but not more than 4 % of cobalt	0
0289	ex3824 90 95 12	Spent catalyst, in the form of rodlets of diameter of 1 mm or more but not exceeding 3 mm, containing a mixture of sulphides of tungsten and of nickel on a support of zeolite, containing by weight not more than 10 % of tungsten and not more than 10 % of nickel, for regeneration as a catalyst for hydrocarbon-cracking (a)	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0290 ex3824 90 95 13	Mixture containing by weight: <ul style="list-style-type: none"> - 7 % or more but not more than 9 % of 2-methyl-1,3-phenylene diisocyanate, - 31 % or more but not more than 34 % of 4-methyl-1,3-phenylene diisocyanate, - 10 % or more but not more than 13 % of 2,4'-methylenediphenyl diisocyanate, - 46 % or more but not more than 49 % of 4,4'-methylenediphenyl diisocyanate 	0
0291 ex3824 90 95 14	Mixture of magnesium bromide 2-oxoperhydroazepin-1-ide and ϵ -caprolactam	0
0292 ex3824 90 95 15	Mixture of disodium <i>N</i> -benzyloxycarbonyl-L-aspartate and sodium chloride, in the form of a solution in water	0
0293 ex3824 90 95 16	Disodium 9,10-dihydro-9,10-dioxoanthracene-2,7-disulphonate, containing by weight 10 % or more but not more than 20 % of sodium sulphate	0
0294 ex3824 90 95 17	Eutectic alloy wholly of potassium and sodium, containing by weight 77 % or more but not more than 79 % of potassium	0
0295 ex3824 90 95 18	Blend of terephthaloyl dichloride and isophthaloyl dichloride	0
0296 ex3824 90 95 20	Preparation consisting by weight of 90 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber and <ul style="list-style-type: none"> - either an aluminium-alkyl compound - or an organic complex of tungsten 	0
0297 ex3824 90 95 21	Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of methylphosphonic acid and phosphoric acid with ethane-1,2-diol	0
0298 ex3824 90 95 22	Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of 2-chloroethyl phosphate with ethane-1,2-diol	0
0299 ex3824 90 95 23	Mixture of sucrose esters, derived from the esterification of sucrose with industrial stearic acid	0
0300 ex3824 90 95 24	Preparations consisting predominantly of phosphabicyclononanes and <i>P</i> -alkyl derivatives thereof, in the form of a solution in 4-tert-butyltoluene	0
0301 ex3824 90 95 25	Lithium tantalate wafers, undoped	0
0302 ex3824 90 95 28	Preparation consisting predominantly of ethylene glycol and <i>N,N</i> -dimethylformamide or ethylene glycol and γ -butyrolactone, for the manufacture of electrolytic capacitors (a)	0
0303 ex3824 90 95 29	Preparation consisting predominantly of γ -butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors (a)	0
0304 ex3824 90 95 30	2,4,7,9-Tetramethyldec-5-yn-4,7-diol, hydroxyethylated	0
0305 ex3824 90 95 31	Copper zinc ferrite, in the form of granules of a size not exceeding 120 micrometres, coated with a silicone resin	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0306	ex3824 90 95 32	Styrene oligomer	0
0307	ex3824 90 95 33	Preparation consisting of α -(4-allyloxy-carbonylbenzoyl)- ω -allyloxypoly(oxy(2-methylethylene)oxyterephthaloyl) and either diallyl-2,2'-oxydiethyl dicarbonate or diallyl isophthalate	0
0308	ex3824 90 95 39	Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid	0
0309	ex3824 90 95 40	Azelaic acid of a purity by weight of 75 % or more but not exceeding 85 %	0
0136	ex3824 90 95 41	7-Nitronaphth[1,2-d][1,2,3]oxadiazole-5-sulphonic acid of a purity by weight of 60 % or more but not exceeding 85 %	0
0282a	ex3824 90 95 42	Mixed metals oxides, in the form of powder, containing by weight: <ul style="list-style-type: none"> - either 5 % or more of barium, neodymium or magnesium and 15 % or more of titanium, - or 30 % or more of lead and 5 % or more of niobium, for use in the manufacture of dielectric films (a) 	0
0277	ex3824 90 95 43	7-Aminonaphthalene-1,3,6-trisulphonic acid and its salts, of a purity by weight of 65 % or more	0
0276	ex3824 90 95 44	Mixture containing by weight: <ul style="list-style-type: none"> - 60 % or more of 2-[N-(2-cyanoethyl)anilino]ethyl acetate and - 20 % or more of acetic acid 	0
0275	ex3824 90 95 45	Preparations consisting predominantly of ethylene glycol and <ul style="list-style-type: none"> - either diethylene glycol, dodecandioic acid and ammonia water - or silicon oxide - or ammonium hydrogen azelate - or ammonium hydrogen azelate and silicon oxide - or dodecandioic acid, ammonia water and silicon oxide, for the manufacture of electrolytic capacitors (a) 	0
0354	ex3824 90 95 46	Carboxylic acid anhydride based hardener for epoxyde resin, in liquid form, of a specific weight at 25 °C of 1,15 g/cm ³ or more but not exceeding 1,18 g/cm ³	0
0310	ex3901 10 90 10	Polyethylene for the manufacture of photo-resist film for semiconductors or printed circuits (a)	0
0311	ex3901 20 90 10	Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, of a specific gravity of 0,945 or more but not exceeding 0,985, for the manufacture of films for typewriter ribbon or similar ribbon (a)	0
0312	ex3901 20 90 20	Polyethylene, containing by weight 35 % or more but not more than 45 % of mica	0
0316	ex3901 90 90 91	Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid	4
0317	ex3901 90 90 93	Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticizer in the manufacture of roof sheets (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0320	ex3902 30 00 91 ex3903 90 90 25	A-B Block copolymer of polystyrene and an ethylene-propylene copolymer, containing by weight 40 % or less of styrene, in one of the forms mentioned in note 6 (b) to Chapter 39	0
0319	ex3902 90 90 92	Polymers of 4-methylpent-1-ene	0
0325	ex3903 90 90 10	Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, whether or not containing a styrene-butadiene block copolymer, in one of the forms mentioned in note 6 (b) to Chapter 39, for the manufacture of sheetings for head-liners for cars (a)	0
0326	ex3903 90 90 15	Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, also partially esterified, of an average molecular weight not exceeding 3 000, in one of the forms mentioned in note 6 (b) to Chapter 39	0
0327	ex3903 90 90 20	Copolymer of styrene with 2-ethylhexyl acrylate or with n-butyl acrylate, containing: - 10 mole % or more but not more than 16 mole % of acrylate, - 0,2 mg/kg or less of sodium and - 0,1 mg/kg or less of calcium	0
0328	ex3903 90 90 30	Copolymer of styrene, butyl acrylate and acrylic acid, containing by weight 92 (± 1) % of styrene, 7 (± 1) % of butyl acrylate and 1 (± 0,5) % of acrylic acid	0
0329	ex3903 90 90 35 ex3911 90 99 30	Copolymer of α-methylstyrene and styrene, having a softening point exceeding 113 °C	0
0324	ex3903 90 90 40 ex3906 90 90 40 ex3911 90 99 50	Copolymer of styrene with α-methylstyrene and acrylic acid, of a molecular weight of 500 or more but not exceeding 6 000	0
0322	ex3903 90 90 45	Bimodal copolymer of styrene and butyl acrylate	0
0332	ex3904 50 90 91	Copolymer of vinylidene chloride with vinyl chloride, containing by weight 79,5 % or more of vinylidene chloride, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of fibres, monofilament or strip (a)	0
0335	ex3904 69 90 92	Copolymer of tetrafluoroethylene and trifluoro(trifluoromethoxy)ethylene	0
0336	ex3904 69 90 93	Copolymer of ethylene with chlorotrifluoroethylene, in one of the forms mentioned in note 6 (b) to Chapter 39	0
0337	ex3904 69 90 94	Copolymer of ethylene and tetrafluoroethylene	0
0340	ex3905 99 90 93	Polyvinyl acetate phthalate	0
0341	ex3905 99 90 94	Polymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, containing by weight 97 % or more but not more than 99 % of vinylpyrrolidone, in the form of a solution in water	0
0342	ex3905 99 90 95	Hexadecylated or eicosylated polyvinylpyrrolidone	0
0345	ex3906 90 90 10	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading No 3003 or 3004 (a)	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0346 ex3906 90 90 20	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for use as a stabilizer in emulsions or dispersions with a pH of more than 13 (a)	6
0344 ex3906 90 90 30	Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a molecular weight of 500 or more but not exceeding 6 000	0
0348 ex3907 20 29 10	Polymer of dextrose, sorbitol and citric acid, containing by weight 90 % or more of dextrose monomer units	0
0349 ex3907 20 99 10	Bis(2-[ω -hydroxy-poly(ethyleneoxy)]ethyl) hydroxymethylphosphonate	0
0350 ex3907 20 99 15	Poly(oxypropylene) having alkoxysilyl end-groups	0
0351 ex3907 20 99 20	Poly[oxy-1,4-phenyleneisopropylidene-1,4-phenyleneoxy-(2-hydroxytrimethylene)], of an average molecular weight of more than 26 000, in one of the forms mentioned in note 6-(b) to Chapter 39	0
0352 ex3907 20 99 25	α -4-Hydroxybutyl- ω -hydroxypoly(oxytetramethylene), containing less than 1 mg/kg of halogen and less than 1 mg/kg of metal, and of a colour not exceeding 20 units on the Hazen scale	0
0353 ex3907 20 99 30	Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin)	0
0355 ex3907 30 00 30	Epoxyde resin, without solvent, containing mineral fillers (silica), without glass fibre, of a specific weight at 25 °C of 1,55 g/cm ³ or more but not exceeding 1,60 g/cm ³	0
0358 ex3907 99 19 10 ex3907 99 99 10	Poly(oxy-1,4-phenylenecarbonyl), in the form of powder	0
0359 ex3907 99 19 20	Liquid crystal copolyester with a melting point of not less than 270 °C, whether or not containing fillers	0
0363 ex3911 90 19 10	Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene)	0
0364 ex3911 90 99 20	Copolymer of dibutyl maleate and N-vinyl-2-pyrrolidone, in one of the forms mentioned in note 6 (a) of Chapter 39	0
0365 ex3911 90 99 25	Copolymer of vinyltoluene and α -methylstyrene	0
0367 ex3911 90 99 40	Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight	0
0368 ex3911 90 99 45	Copolymer of maleic acid and methyl vinyl ether	0
0371 ex3912 39 80 10	Cellulose, both hydroxyethylated and ethylated, insoluble in water	0
0372 ex3912 39 80 20	Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms	0
0375 ex3919 10 39 10	Self-adhesive tape of metallised polyurethane containing glass beads for use in the manufacture of marine life-saving equipment (a)	0
0378 ex3919 90 31 40 ex3920 62 19 20 ex3920 62 90 20 ex3920 63 00 30 ex3920 69 00 30	Reflecting polyester sheeting embossed in a regular pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0381	ex3920 10 25 20	Film of polyethylene, of a thickness of 20 micrometres or more but not exceeding 45 micrometres, containing calcium carbonate in the mass, for the manufacture of napkins for babies or of sanitary towels or of tampons or of disposable surgical gowns (a)	0
0382	ex3920 10 25 30 ex3920 10 89 20	Film of a thickness not exceeding 0,20 mm, of a blend of polyethylene and a copolymer of ethylene with oct-1-ene, embossed in a regular rhomboidal pattern, for coating both sides of a layer of unvulcanized rubber (a)	0
0393	ex3920 62 19 10	Polyethylene terephthalate film, of a thickness of less than 11 micrometres, for the manufacture of audiodigital tapes for cassettes (a)	0
0394	ex3920 62 19 15	Polyethylene terephthalate film, not coated with an adhesive, of a thickness not exceeding 25 micrometres, either: - only dyed in the mass, or - dyed in the mass and metallized on one side	0
0395	ex3920 62 19 25	Film of polyethylene terephthalate only, of a total thickness not exceeding 120 micrometres, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0
0396	ex3920 62 19 30	Polyethylene terephthalate film, of a thickness of 20 micrometres or more but not exceeding 30 micrometres, coated on one side with silicone, for use in the manufacture of window film (a)	5.6
0397	ex3920 62 19 35	Laminated film of polyethylene terephthalate only, of a total thickness not exceeding 120 micrometres, consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0
0398	ex3920 62 19 40	Film of polyethylene terephthalate, coated or covered on one side or on both sides with a layer of modified polyester, of a total thickness of 7 micrometres or more but not exceeding 11 micrometres, for the manufacture of video tapes with a magnetic layer of metallic pigments and a width of 8 mm or of 12,7 mm (a)	0
0399	ex3920 62 19 45	Single ply film of polyethylene terephthalate only, of a thickness not exceeding 120 micrometres, which only: - contains a colouring and/or UV-absorbing material throughout the mass and - is metallised on one side, whether or not coated on one or both sides with a vinyl acrylate polymer but having no other coating or adhesive	0
0400	ex3920 62 19 50	Film of polyethylene terephthalate, of a total thickness not exceeding 120 micrometres, of a width of 100 mm or more but not exceeding 115 mm, coated on both sides with one or more layers containing different chemicals, for the manufacture of goods of subheading 3701 20 00 (a)	0
0401	ex3920 62 19 55	Film of polyethylene terephthalate, on one side metallized and coated with white ink and a protective layer and on the other side coated with a thermosensitive seal layer, of a width of 100 mm or more but not exceeding 150 mm, for the manufacture of goods of subheading 3701 20 00 (a)	0
0402	ex3920 62 19 60	Film of polyethylene terephthalate, coated on one side with a layer of modified polyester, of a thickness of 20 micrometres (\pm 0,7 micrometre) or of 30 micrometres (\pm 0,9 micrometre), for the manufacture of audio magnetic tapes of a total thickness of 33 micrometres or more (a)	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0408 ex3920 99 59 20	Film entirely of polyvinyl alcohol, of a thickness not exceeding 1 mm and containing by weight: - 2 % or less of unhydrolysed acetate groups evaluated as vinyl acetate and - 5 % or more but not more than 25 % of glycerol as plasticizer, for the manufacture of roof-windows (a)	0
0409 ex3920 99 59 25	Poly(1-chlorotrifluoroethylene) film	0
0410 ex3920 99 59 30	Film and sheet of a copolymer of ethylene with chlorotrifluoroethylene, of a thickness of 12 micrometres or more but not exceeding 400 micrometres	0
0411 ex3920 99 59 35	Film entirely of polyvinyl alcohol, of a thickness not exceeding 1 mm and of a width of 2,20 m or more, with an extension at break, in the transverse direction, of 350 % or more	0
0412 ex3920 99 59 40	Biaxially-oriented film of polyvinyl alcohol, coated on both sides, of a total thickness of less than 1 mm	0
0413 ex3920 99 59 45	Iridescent film of polyester, polyethylene and an ethylene-vinyl acetate copolymer	0
0414 ex3920 99 59 50	Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not exceeding 0,14 mm, impermeable to water vapour	0
0428 ex4805 60 90 10	Overlay paper, of a width of more than 110 cm and containing by weight more than 5 % of corundum	0
0430 ex4810 99 10 10	Bleached paper coated with kaolin, for use in the manufacture of tampons applicators (a)	0
0463 ex5603 11 10 10 ex5603 11 90 10 ex5603 12 10 10 ex5603 12 90 10 ex5603 91 10 10 ex5603 91 90 10 ex5603 92 10 10 ex5603 92 90 10	Polyvinyl alcohol non-wovens, in the piece or cut into rectangles: - of a thickness of 200 micrometres or more but not exceeding 280 micrometres and - of a weight of 20 g/m ² or more but not exceeding 50 g/m ²	0
0462 ex5603 11 10 20 ex5603 11 90 20 ex5603 12 10 20 ex5603 12 90 50	Non-wovens, containing spunbonded fibres of polypropylene, for the manufacture of napkins and napkin liners for babies and similar sanitary articles (a)	0
0466 ex5603 13 90 40 ex5603 14 90 20	Non-wovens consisting of a central layer of polycarbonate fibres, laminated on each side with spunbonded filaments of polyester, of a weight of more than 130 g/m ² but not exceeding 200 g/m ²	0
0471 ex5903 20 90 20	Tape of polyester fabric laminated with a metallised polyurethane film containing glass beads, for use in the manufacture of marine life-saving equipment (a)	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0489 ex7011 20 00 40	<p>Glass face-plate:</p> <ul style="list-style-type: none"> - with a diagonal measurement of 366,4 mm ($\pm 1,5$ mm) and of dimensions of 246,4 x 315,4 mm ($\pm 1,5$ mm), - with a diagonal measurement of 391 mm ($\pm 1,5$ mm) and of dimensions of 261,4 x 326,8 mm ($\pm 1,5$ mm), - with a diagonal measurement of 442 mm ($\pm 1,5$ mm) and of dimensions of 293,4 x 369,2 mm ($\pm 1,5$ mm), - with a diagonal measurement of 544,5 mm ($\pm 1,6$ mm) and of dimensions of 358 x 454 mm ($\pm 1,6$ mm), having a cylindrical curvature, - with a diagonal measurement of 629,8 mm (± 3 mm) and of dimensions of 406,5 x 519 mm (± 2 mm), having a cylindrical curvature, or - with a diagonal measurement of 639,3 mm (± 3 mm) and of dimensions of 413,6 x 527 mm (± 2 mm), and with a raised edge, for the manufacture of colour cathode-ray tubes (a) 	0
0496 ex7019 90 10 20	<p>Non-textile E-glass fibres, of a length not exceeding 3 mm and a diameter of 5 micrometres, for the manufacture of catalysts for the purification of smokes (a)</p>	0
0505 ex7212 50 91 10	<p>Perforated steel strip, plated or coated with nickel, of a width of 140 mm or more but not exceeding 400 mm and a thickness of 60 micrometres or more but not exceeding 90 micrometres</p>	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CN code & TARIC	Description	Rate of autonomous duty (%)
0003 ex8471 60 90 10	Input unit (so-called "touchpad"), the exterior dimensions of which do not exceed 50 x 62 mm, capable of matrix scanning and detection, consisting of 2 layers of measurement electrodes, a printed circuit, a capacitive matrix, 2 integrated circuits, discrete components and a connector	0
0004 ex8471 60 90 20	Pointing device (so-called "trackball"), consisting of printed circuit on which are mounted an optical encoder in the form of a monolithic integrated circuit and a housing comprising a ball and a retainer ring	0
0023b ex8473 30 10 18	Processor, comprising: - 8 central processing units (CPUs), - 2 input/output processor units, - 20 random-access memories (RAMs), - not more than 80 printed circuits on which memories are mounted, the whole mounted on a ceramic multiple printed circuit the exterior dimensions of which exceed 475 x 550 mm, with cooling elements	0
0029 ex8473 30 10 35	Processing system, consisting of: - 30 or more but not more than 121 monolithic integrated circuits not contained in a housing (chips), - a ceramic substrate, the whole enclosed between a metallic baseplate and a metallic plate incorporating a heat sink	0
0044 ex8483 10 80 10	Integrally forged and roughly shaped generator and turbine shafts of a weight exceeding 215 tonnes	0
0050 ex8501 10 99 78	DC motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8525 20 91 or 8527 90 91 (a)	0
0052 ex8503 00 91 31 ex8503 00 99 32	Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring	0
0058 ex8504 90 11 31	Ferrite core in cylinder form, comprising circular grooves	0
0075b ex8517 90 11 07	Modulator/demodulator (Modem), consisting of 2 or more monolithic integrated circuits mounted on a support, contained in a housing the exterior dimensions of which do not exceed 32 x 82 mm	0
0084 ex8517 90 82 30	Assembly consisting of a laser diode operating at a nominal wavelength of 780 nm, a photodiode and a lens, contained in a housing with a diameter of not more than 9 mm and a height of not more than 20 mm, with not more than 3 connections	0
0102 ex8522 90 98 39	Assembly consisting of a driver circuit, a tacho-sensor and a brushless DC motor	0
0111 ex8529 10 70 35	Ceramic filter for a centre frequency of 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 25 kHz at 6 dB and not exceeding 60 kHz at 40 dB, contained in a housing	0
0112 ex8529 10 70 45	Ceramic filter for a centre frequency of 450 kHz ($\pm 1,5$ kHz) or 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 30 kHz at 6 dB and not exceeding 70 kHz at 40 dB, contained in a housing	0
0125 ex8529 90 81 31	Demagnetisation coil, with cables and connectors	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0489 ex7011 20 00 40	Glass face-plate: <ul style="list-style-type: none"> - with a diagonal measurement of 366,4 mm ($\pm 1,5$ mm) and of dimensions of 246,4 x 315,4 mm ($\pm 1,5$ mm), - with a diagonal measurement of 391 mm ($\pm 1,5$ mm) and of dimensions of 261,4 x 326,8 mm ($\pm 1,5$ mm), - with a diagonal measurement of 442 mm ($\pm 1,5$ mm) and of dimensions of 293,4 x 369,2 mm ($\pm 1,5$ mm), - with a diagonal measurement of 544,5 mm ($\pm 1,6$ mm) and of dimensions of 358 x 454 mm ($\pm 1,6$ mm), having a cylindrical curvature, - with a diagonal measurement of 629,8 mm (± 3 mm) and of dimensions of 406,5 x 519 mm (± 2 mm), having a cylindrical curvature, or - with a diagonal measurement of 639,3 mm (± 3 mm) and of dimensions of 413,6 x 527 mm (± 2 mm), and with a raised edge, for the manufacture of colour cathode-ray tubes (a) 	0
0496 ex7019 90 10 20	Non-textile E-glass fibres, of a length not exceeding 3 mm and a diameter of 5 micrometres, for the manufacture of catalysts for the purification of smokes (a)	0
0505 ex7212 50 91 10	Perforated steel strip, plated or coated with nickel, of a width of 140 mm or more but not exceeding 400 mm and a thickness of 60 micrometres or more but not exceeding 90 micrometres	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

	CN code & TARIC	Description	Rate of autonomous duty (%)												
0804	ex8529 90 81 32	Optical unit for video projection, comprising a colour separation system, a positioning mechanism and lenses, for use in the manufacture of products falling within heading 8528 (a)	0												
0126	ex8529 90 81 34	Assembly consisting of a lens unit, having an adjustable focal length of 4 mm or more but not exceeding 69 mm and comprising a zoom encoder, a stepping motor unit, a zoom motor unit, an iris motor unit and a photo interrupter	0												
0130	ex8531 20 30 10	Dot matrix display consisting of a line of 8 characters, each character composed of 35 light-emitting diodes (LED), comprising electronic components for interface and drive functions, contained in a housing the exterior dimensions of which do not exceed 26 x 90 mm, with not more than 28 connections and bearing: <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): <table style="margin-left: 20px;"> <tr> <td>HDSP 2107</td> <td>HDSP 2111</td> <td>HDSP 2112</td> <td>HDSP 2113</td> </tr> <tr> <td>PDSP 2110</td> <td>PDSP 2111</td> <td>PDSP 2112</td> <td>PDSP 2113</td> </tr> <tr> <td colspan="4">SDA 5708-24</td> </tr> </table> or - other identification markings relating to devices complying with the abovementioned description 	HDSP 2107	HDSP 2111	HDSP 2112	HDSP 2113	PDSP 2110	PDSP 2111	PDSP 2112	PDSP 2113	SDA 5708-24				0
HDSP 2107	HDSP 2111	HDSP 2112	HDSP 2113												
PDSP 2110	PDSP 2111	PDSP 2112	PDSP 2113												
SDA 5708-24															
0141	ex8531 80 90 10	Plasma display	0												
0142	ex8531 80 90 20	Transducer, capable of producing a sound level of 85 dB or more but not exceeding 96 dB at a frequency of 2 670 Hz or more but not exceeding 3 200 Hz	0												
0143	ex8531 80 90 30	Vacuum fluorescent display, comprising electronic components providing drive and/or control functions	0												
0138	ex8531 80 90 60	Monochrome electroluminescent display, with a diagonal measurement of the screen not exceeding 36 cm, mounted on a printed circuit, comprising electronic components providing drive and/or control functions	0												
0153	ex8532 25 00 31	Plastic dielectric capacitor, with a fixed nominal capacity of 0,0015 or 0,003 µF and an nominal operating voltage of 30 kV	0												
0174	ex8536 50 15 31	Rotary switch, for use in the manufacture of remote control devices (a)	0												
0177	ex8536 69 30 31	Male or female connectors, capable of interconnecting printed circuits, consisting of 6 rows of phosphor-bronze or beryllium-copper connections plated with gold over nickel, contained in a plastic housing	0												
0185	ex8540 12 00 84	Flat screen monochrome cathode-ray tube, with a diagonal measurement of the screen of 98 mm or more but not exceeding 102 mm and an anode voltage of 5 kV or more but not exceeding 32 kV	0												
0143b	ex8540 89 11 92	Vacuum fluorescent display tube	0												
0196b	ex8540 91 00 95	Flat mask	0												
0205	ex8541 10 91 20	Silicon power rectifier diode, with a reverse peak voltage not exceeding 1 500 V and an average output current of 3 A or more but not exceeding 8 A, contained in a housing bearing: <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): <table style="margin-left: 20px;"> <tr> <td>PG151S15</td> <td>U 34</td> </tr> </table> or - other identification markings relating to devices complying with the abovementioned description 	PG151S15	U 34	0										
PG151S15	U 34														

CN code & TARIC	Description	Rate of autonomous duty (%)
0232 ex8541 29 80 60	<p>Transistor of the PNP type, having a collector-base breakdown-voltage of -200 V or more, a collector current not exceeding -100 mA and with a dissipation rate not exceeding 7 W, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): A 1406 or - other identification markings relating to devices complying with the abovementioned description 	0
0237 ex8541 30 90 30	<p>Gate turn-off thyristor, having a repetitive peak off-state voltage of 4 500 V, a peak turn-off current of 3 000 or 4 000 A, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): FG 4000GX SG 4000GX or - other identification markings relating to devices complying with the abovementioned description 	0
0242 ex8541 40 19 20	<p>Light-emitting diode, having a square base with an edge length not exceeding 8,2 mm or contained in a housing having an external diameter not exceeding 6 mm, having a lens</p>	0
0252 ex8542 13 01 13	<p>Wafer, not yet cut into chips, consisting only of microcontrollers or microcomputers with a processing capacity of 16 bits, comprising a data memory, a programme memory and with an analogue-to-digital converter and or a digital-to-analogue converter, for use in the manufacture of goods of subheading 8542 13 65 contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 784025 784026 or - other identification markings relating to devices complying with the abovementioned description (a) 	0
0284 8542 13 53 8542 14 29 8542 19 49	Other memories	0
0287 ex8542 13 63 02	<p>Microcontroller or microcomputer of N-MOS (including H-MOS) technology, with a processing capacity of 8 bits, comprising a data memory and a programme memory, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 8042 8742 MC 68705 MC 6805 or - other identification markings relating to devices complying with the abovementioned description 	0
0293 ex8542 13 63 08	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 8 bits, providing voice message storage, comprising a programme memory, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): D6305 D6351 D6455 D6471 or - other identification markings relating to devices complying with the abovementioned description 	0

CN code & TARIC	Description	Rate of autonomous duty (%)																																																				
0302 ex8542 13 63 18	<p>Microcontroller or microcomputer, with a processing capacity of 8 bits, comprising one or more data memories with a total storage capacity not exceeding 12 Kbits and a programm memory with a storage capacity of 32 Kbits or more but not exceeding 480 Kbits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): <table border="0" data-bbox="544 456 1166 734"> <tr> <td>5A41</td> <td>5B11</td> <td>76C75T</td> <td>7742</td> </tr> <tr> <td>77C82</td> <td>80C152</td> <td>80C51</td> <td>80C52</td> </tr> <tr> <td>83C055</td> <td>83C504</td> <td>83C51</td> <td>83L51</td> </tr> <tr> <td>8751</td> <td>87C055</td> <td>87C504</td> <td>87C51</td> </tr> <tr> <td>87C52</td> <td>87C54</td> <td>87C58</td> <td>87L51</td> </tr> <tr> <td>Am 79C412</td> <td>AT 89C51</td> <td>C 1900</td> <td>C 2900</td> </tr> <tr> <td>C 3900</td> <td>C 40</td> <td>CXD 80724</td> <td>CXP 80524</td> </tr> <tr> <td>L 39</td> <td>M 37450E8</td> <td>M 37450M8</td> <td>M 38063M6</td> </tr> <tr> <td>M 38063E8</td> <td>M 38067M8</td> <td>M 3812</td> <td>M50743</td> </tr> <tr> <td>M50747</td> <td>M50958</td> <td>M50959</td> <td>MC68HC05i8</td> </tr> <tr> <td>MC68HC11A8</td> <td>MC68HC705i8</td> <td>MN 1871215</td> <td>PCA 84C640</td> </tr> <tr> <td>PCA 84C840</td> <td>PCA 84C841</td> <td>PD 78014</td> <td>PD 78058</td> </tr> <tr> <td>PD 78064</td> <td>PD 78134</td> <td>TMP 87PM70</td> <td>TMP 91P642</td> </tr> </table> or - other identification markings relating to devices complying with the abovementioned description 	5A41	5B11	76C75T	7742	77C82	80C152	80C51	80C52	83C055	83C504	83C51	83L51	8751	87C055	87C504	87C51	87C52	87C54	87C58	87L51	Am 79C412	AT 89C51	C 1900	C 2900	C 3900	C 40	CXD 80724	CXP 80524	L 39	M 37450E8	M 37450M8	M 38063M6	M 38063E8	M 38067M8	M 3812	M50743	M50747	M50958	M50959	MC68HC05i8	MC68HC11A8	MC68HC705i8	MN 1871215	PCA 84C640	PCA 84C840	PCA 84C841	PD 78014	PD 78058	PD 78064	PD 78134	TMP 87PM70	TMP 91P642	0
5A41	5B11	76C75T	7742																																																			
77C82	80C152	80C51	80C52																																																			
83C055	83C504	83C51	83L51																																																			
8751	87C055	87C504	87C51																																																			
87C52	87C54	87C58	87L51																																																			
Am 79C412	AT 89C51	C 1900	C 2900																																																			
C 3900	C 40	CXD 80724	CXP 80524																																																			
L 39	M 37450E8	M 37450M8	M 38063M6																																																			
M 38063E8	M 38067M8	M 3812	M50743																																																			
M50747	M50958	M50959	MC68HC05i8																																																			
MC68HC11A8	MC68HC705i8	MN 1871215	PCA 84C640																																																			
PCA 84C840	PCA 84C841	PD 78014	PD 78058																																																			
PD 78064	PD 78134	TMP 87PM70	TMP 91P642																																																			
0305 ex8542 13 65 06	<p>Microcontroller or microcomputer of C-MOS technology, with a processing capacity of 16 bits, comprising one or more data memories with a total storage capacity of 10 Kbits or more and one or more programme memories with a total storage capacity of 384 Kbits or more, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): <table border="0" data-bbox="544 1055 1007 1077"> <tr> <td>TMS 370C16A</td> <td>TMS 370E16A</td> <td>TMS 370P16A</td> </tr> </table> or - other identification markings relating to devices complying with the abovementioned description 	TMS 370C16A	TMS 370E16A	TMS 370P16A	0																																																	
TMS 370C16A	TMS 370E16A	TMS 370P16A																																																				
0317 ex8542 13 67 01	<p>Microcontroller or microcomputer, with a processing capacity of 17 bits or more but not exceeding 31 bits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): <table border="0" data-bbox="544 1335 1209 1375"> <tr> <td>AM 79C420</td> <td>SC 14400</td> <td>SC 14401</td> <td>SC 14402</td> <td>SC 14420</td> </tr> <tr> <td>SC 14421</td> <td>SC 14460</td> <td>TMS 57070</td> <td>VY 27015</td> <td></td> </tr> </table> or - other identification markings relating to devices complying with the abovementioned description 	AM 79C420	SC 14400	SC 14401	SC 14402	SC 14420	SC 14421	SC 14460	TMS 57070	VY 27015		0																																										
AM 79C420	SC 14400	SC 14401	SC 14402	SC 14420																																																		
SC 14421	SC 14460	TMS 57070	VY 27015																																																			
Q377 ex8542 13 99 04	<p>Transmitter/receiver of C-MOS technology, with, at least one of the following characteristics:</p> <ul style="list-style-type: none"> - a) capable of connecting (terminating) line rates of 1 168, 8 448, 34 368, 53 084 or 159 252 Kbits per second, - b) for signals between an encoder/decoder using Manchester code (MED) or an interface unit and a twisted pair cable or a coaxial cable, - c) capable of data transfer at a frequency of 1,544 or 2,048 MHz, comprising an equaliser and a clock generator, in the form of a monolithic integrated circuit contained in a housing bearing: - an identification marking consisting of or including (one of) the following combination(s): <table border="0" data-bbox="544 1827 1230 1912"> <tr> <td>a) Bt 8952</td> <td>a) TXC 02050</td> <td>a) PM 5343</td> <td>a) PM 5344</td> </tr> <tr> <td>b) 83C92</td> <td>b) 83C94</td> <td>b) Am 79C98</td> <td>b) CY7C971</td> </tr> <tr> <td>b) MC 145572</td> <td>b) TMS 380C60</td> <td>c) LXT 304</td> <td>c) LXT 310</td> </tr> <tr> <td>c) LXT 311</td> <td></td> <td></td> <td></td> </tr> </table> or - other identification markings relating to devices complying with the abovementioned description 	a) Bt 8952	a) TXC 02050	a) PM 5343	a) PM 5344	b) 83C92	b) 83C94	b) Am 79C98	b) CY7C971	b) MC 145572	b) TMS 380C60	c) LXT 304	c) LXT 310	c) LXT 311				0																																				
a) Bt 8952	a) TXC 02050	a) PM 5343	a) PM 5344																																																			
b) 83C92	b) 83C94	b) Am 79C98	b) CY7C971																																																			
b) MC 145572	b) TMS 380C60	c) LXT 304	c) LXT 310																																																			
c) LXT 311																																																						

CN code & TARIC	Description	Rate of autonomous duty (%)
0378 ex8542 13 99 05	<p>Dual-tone multi-frequency (DTMF) receiver of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): M-957 MT 8862 MT 8863 TC 35219F or - other identification markings relating to devices complying with the abovementioned description 	0
0370 ex8542 13 99 08	<p>Signal processing circuit of luminance and chrominance signals for video-cameras, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): CXD 2178 HG 51CS260 MB 87E108 or - other identification markings relating to devices complying with the abovementioned description 	0
0386b ex8542 13 99 15	<p>Phoneme speech synthesiser of C-MOS technology, with a supply current of less than 10 mA, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 78 A 263 CD 54121 N2L CD 54122 N2L CD 54123 N2L CD 54147 N2L CM 54104 CM 54145 N2L CM 54146 N2L CM 54166 N2L or - other identification markings relating to devices complying with the abovementioned description 	0
0372 ex8542 13 99 25	<p>Video processing circuit of C-MOS technology, capable of detecting, decoding and discrimination signals for reception apparatus for television with a screen width/height ratio of 16/9, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): CXD 2C53 or - other identification markings relating to devices complying with the abovementioned description 	0
0365 ex8542 13 99 35	<p>Digital-to-analogue and analogue-to-digital converter of C-MOS technology, having a resolution of 14 bits, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): TLC 320V320 or - other identification markings relating to devices complying with the abovementioned description 	0
0407 ex8542 13 99 38	<p>Differential crosspoint switch of C-MOS technology, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): MT 8804 MT 8816 or - other identification markings relating to devices complying with the abovementioned description 	0

CN code & TARIC	Description	Rate of autonomous duty (%)																																																
0364 ex8542 13 99 39	<p>Video converter of C-MOS technology, providing control signal generation, line interpolation calculation and screen width/height ratio conversion, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): CXD 2428Q or - other identification markings relating to devices complying with the abovementioned description 	0																																																
0414 ex8542 13 99 47	<p>Digital-to-analogue converter of C-MOS technology, with at least one of the following characteristics:</p> <ul style="list-style-type: none"> - a) with a capacity of 8 bits, with an output buffer amplifier, a serial interface circuit and at least 12 channels, - b) with a capacity of 8 bits, capable of double buffering 8-bit words, - c) with a capacity of 8 bits, capable of converting serial data input towards 6 or 36 output channels, - d) single or triple converter, with at least one random-access memory (RAMDAC), having one or more colour palette registers, - e) with a dynamic audio range of 90 dB or more, - f) 8-, 9- or 10-bit video converter, with at least 3 channels for the separate conversion of colour signals, - g) with a capacity of 16 bits, capable of converting data in floating point form, comprising a 10-bit digital-to-analogue converter, and a shift register, <p>in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): <table data-bbox="595 1099 1326 1357" style="width: 100%; border: none;"> <tr> <td>a) M 62352P</td> <td>b) DAC 0830</td> <td>b) DAC 0831</td> <td>b) DAC 0832</td> </tr> <tr> <td>c) M 62354FP</td> <td>c) MB 88344B</td> <td>c) 357S0010</td> <td>c) 357S0011</td> </tr> <tr> <td>d) 357S0012</td> <td>d) ATT 20C490</td> <td>d) ATT 20C491</td> <td>d) ATT 20C492</td> </tr> <tr> <td>d) ATT 20C493</td> <td>d) ATT 20C497</td> <td>d) Bt445</td> <td>d) Bt451</td> </tr> <tr> <td>d) Bt458</td> <td>d) Bt459</td> <td>d) Bt460</td> <td>d) Bt461</td> </tr> <tr> <td>d) Bt462</td> <td>d) Bt463</td> <td>d) Bt467</td> <td>d) Bt473</td> </tr> <tr> <td>d) Bt475</td> <td>d) MU 9C9760</td> <td>d) SC 11482</td> <td>d) SC 11483</td> </tr> <tr> <td>d) SC 11484</td> <td>d) SC 11485</td> <td>d) SC 11487</td> <td>d) SC 11489</td> </tr> <tr> <td>d) SC 15025</td> <td>d) SC 15026</td> <td>d) TR 9C1710</td> <td>d) TVP 3020</td> </tr> <tr> <td>d) TVP 3030</td> <td>e) CS 4328</td> <td>e) CXD 2564</td> <td>e) PD 6376</td> </tr> <tr> <td>e) TMS 57010</td> <td>f) Bt 857</td> <td>f) CXD 1178</td> <td>f) CXD 2307R</td> </tr> <tr> <td>f) CXD 2309</td> <td>g) YAC 512</td> <td>g) YAC 513</td> <td></td> </tr> </table> - other identification markings relating to devices complying with the abovementioned description 	a) M 62352P	b) DAC 0830	b) DAC 0831	b) DAC 0832	c) M 62354FP	c) MB 88344B	c) 357S0010	c) 357S0011	d) 357S0012	d) ATT 20C490	d) ATT 20C491	d) ATT 20C492	d) ATT 20C493	d) ATT 20C497	d) Bt445	d) Bt451	d) Bt458	d) Bt459	d) Bt460	d) Bt461	d) Bt462	d) Bt463	d) Bt467	d) Bt473	d) Bt475	d) MU 9C9760	d) SC 11482	d) SC 11483	d) SC 11484	d) SC 11485	d) SC 11487	d) SC 11489	d) SC 15025	d) SC 15026	d) TR 9C1710	d) TVP 3020	d) TVP 3030	e) CS 4328	e) CXD 2564	e) PD 6376	e) TMS 57010	f) Bt 857	f) CXD 1178	f) CXD 2307R	f) CXD 2309	g) YAC 512	g) YAC 513		0
a) M 62352P	b) DAC 0830	b) DAC 0831	b) DAC 0832																																															
c) M 62354FP	c) MB 88344B	c) 357S0010	c) 357S0011																																															
d) 357S0012	d) ATT 20C490	d) ATT 20C491	d) ATT 20C492																																															
d) ATT 20C493	d) ATT 20C497	d) Bt445	d) Bt451																																															
d) Bt458	d) Bt459	d) Bt460	d) Bt461																																															
d) Bt462	d) Bt463	d) Bt467	d) Bt473																																															
d) Bt475	d) MU 9C9760	d) SC 11482	d) SC 11483																																															
d) SC 11484	d) SC 11485	d) SC 11487	d) SC 11489																																															
d) SC 15025	d) SC 15026	d) TR 9C1710	d) TVP 3020																																															
d) TVP 3030	e) CS 4328	e) CXD 2564	e) PD 6376																																															
e) TMS 57010	f) Bt 857	f) CXD 1178	f) CXD 2307R																																															
f) CXD 2309	g) YAC 512	g) YAC 513																																																
0424 ex8542 13 99 57	<p>Demodulator of C-MOS technology, capable of receiving and demodulating a data stream with a transfer rate of 30 Mbits/s or more, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): NDV 9000 NDV 9002 NDV 9050 or - other identification markings relating to devices complying with the abovementioned description 	0																																																
0428 ex8542 14 60 02	<p>Control circuit of bipolar technology, capable of driving 4 inductive or resistive loads each having an output current not exceeding 1,7 A at a supply voltage not exceeding 45 V, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 45980 84368 or - other identification markings relating to devices complying with the abovementioned description 	0																																																

CN code & TARIC	Description	Rate of autonomous duty (%)
0438 ex8542 14 99 06	<p>Dual line transmitter of bipolar technology, with an output voltage not exceeding 12 V, comprising amplifiers, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): DS 3691 DS 75110A SN 75110 or - other identification markings relating to devices complying with the abovementioned description 	0
0436 ex8542 14 99 10	<p>Digitizing circuit of bipolar technology, providing demodulation and analogue-to-digital conversion, comprising mixers, analogue filters, local oscillators and a voltage controlled oscillator (VCO), in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): MAX 2101 or - other identification markings relating to devices complying with the abovementioned description 	0
0437 ex8542 14 99 12	<p>Dual or quadruple line receiver of bipolar technology, with an input voltage sensitivity of 25 mV, comprising amplifiers, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): DS 3650 DS 75107 MC 3450 SN 7510B or - other identification markings relating to devices complying with the abovementioned description 	0
0480 ex8542 19 98 02	<p>Signal processing circuit of BiMOS technology, providing amplification and conversion of read signals and conversion of write signals for disk storage units, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 32 R 117 32 R 501 or - other identification markings relating to devices complying with the abovementioned description 	0
0483 ex8542 19 98 04	<p>Encoder/decoder of BiMOS technology, providing data conversion and separation and a data transfer rate of 50 Mbits per second or more, comprising a read pulse detector and a frequency synthesiser/synchroniser, in the form of a monolithic integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 3036 TF HD 153031 RF or - other identification markings relating to devices complying with the abovementioned description 	0
0508 ex8542 30 30 13	<p>Audio amplifier, having a nominal continuous output power of 500 mW at 8 Ω and a total harmonic distortion (THD) not exceeding 1 %, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): LM 4861 or - other identification markings relating to devices complying with the abovementioned description 	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0507 ex8542 30 30 20	<p>Transimpedance amplifier of gallium arsenide (GaAs) semiconductor material, with a typical input resistance of 1 500 Ω and a typical output resistance of 50 Ω, comprising an automatic gain control circuit, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): ATA 00501 ATA 0150 ATA 01201 ATA 0621 ATA 30012 or - other identification markings relating to devices complying with the abovementioned description 	0
0549 ex8542 30 50 10	<p>Voltage regulator, having an output voltage of 1 V or more but not exceeding 8 V, a typical quiescent current not exceeding 500 μA, a typical dropout voltage not exceeding 250 mV at an output current not exceeding 240 mA, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): TK 112 TK 113 TK 114 (R3) TK 115 TK 116 or - other identification markings relating to devices complying with the abovementioned description 	0
0535 ex8542 30 50 21	<p>Voltage and current regulator with pulse-width modulation switching, operating at a frequency of 200 or 500 kHz, comprising at least one resistor, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): LT 1510 LT 1511 LT 1512 or - other identification markings relating to devices complying with the abovementioned description 	0
0536 ex8542 30 50 22	<p>Voltage regulator, with an input voltage of 6 V or more but not exceeding 25 V, a typical output voltage of 5 V ($\pm 0,1$ V) and an output current not exceeding 75 mA, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 16227090 or - other identification markings relating to devices complying with the abovementioned description 	0
0537 ex8542 30 50 23	<p>Voltage regulator, with an input voltage not exceeding 14 V, a typical output voltage of 3, 4 or 5 V at an output current not exceeding 180 mA and a typical dropout voltage of 120 mV, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): TK 11430M TK 11440M TK 71350M or - other identification markings relating to devices complying with the abovementioned description 	0

0539	CN code & TARIC	Description	Rate of autonomous duty (%)	
	ex8542 30 50 24	<p>Voltage regulator, with an input voltage not exceeding 26 V, a output voltage of 2,9 V or more but not exceeding 5,1 V at an output current not exceeding 200 mA, a quiescent current not exceeding 0,01 µA and a dropout voltage not exceeding 400 mV, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): MIC 5201 or - other identification markings relating to devices complying with the abovementioned description 	0	
	0560	ex8542 30 61 05	<p>Smartpower circuit, capable of driving inductive and resistive loads having 4 outputs with a current not exceeding 8 A, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): HIP 0080 HIP 0081 HIP 0082 (100904) or - other identification markings relating to devices complying with the abovementioned description 	0
	0561	ex8542 30 61 06	<p>Smartpower circuit, capable of power supply switching in an automotive air-bag system, providing an output current not exceeding 60 mA at an output voltage of 5 V (±0,1 V), in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 16155199 16191489 or - other identification markings relating to devices complying with the abovementioned description 	0
	0612	ex8542 30 91 01	<p>Smartpower circuit, providing diagnostic functions in an automotive air-bag system, comprising a serial transmitter/receiver, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): .16199667 or - other identification markings relating to devices complying with the abovementioned description 	0
	0617	ex8542 30 95 03	<p>Signal processing circuit of C-MOS technology, providing analogue signal filtering and gain control, comprising a modulator/demodulator (Modem), in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): SC 11370 SC 11372 or - other identification markings relating to devices complying with the abovementioned description 	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0003	ex8471 60 90 10	Input unit (so-called "touchpad"), the exterior dimensions of which do not exceed 50 x 62 mm, capable of matrix scanning and detection, consisting of 2 layers of measurement electrodes, a printed circuit, a capacitive matrix, 2 integrated circuits, discrete components and a connector	0
0004	ex8471 60 90 20	Pointing device (so-called "trackball"), consisting of printed circuit on which are mounted an optical encoder in the form of a monolithic integrated circuit and a housing comprising a ball and a retainer ring	0
0023b	ex8473 30 10 18	Processor, comprising: - 8 central processing units (CPUs), - 2 input/output processor units, - 20 random-access memories (RAMs), - not more than 80 printed circuits on which memories are mounted, the whole mounted on a ceramic multiple printed circuit the exterior dimensions of which exceed 475 x 550 mm, with cooling elements	0
0029	ex8473 30 10 35	Processing system, consisting of: - 30 or more but not more than 121 monolithic integrated circuits not contained in a housing (chips), - a ceramic substrate, the whole enclosed between a metallic baseplate and a metallic plate incorporating a heat sink	0
0044	ex8483 10 80 10	Integrally forged and roughly shaped generator and turbine shafts of a weight exceeding 215 tonnes	0
0050	ex8501 10 99 78	DC motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8525 20 91 or 8527 90 91 (a)	0
0052	ex8503 00 91 31 ex8503 00 99 32	Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring	0
0058	ex8504 90 11 31	Ferrite core in cylinder form, comprising circular grooves	0
0075b	ex8517 90 11 07	Modulator/demodulator (Modem), consisting of 2 or more monolithic integrated circuits mounted on a support, contained in a housing the exterior dimensions of which do not exceed 32 x 82 mm	0
0084	ex8517 90 82 30	Assembly consisting of a laser diode operating at a nominal wavelength of 780 nm, a photodiode and a lens, contained in a housing with a diameter of not more than 9 mm and a height of not more than 20 mm, with not more than 3 connections	0
0102	ex8522 90 98 39	Assembly consisting of a driver circuit, a tacho-sensor and a brushless DC motor	0
0111	ex8529 10 70 35	Ceramic filter for a centre frequency of 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 25 kHz at 6 dB and not exceeding 60 kHz at 40 dB, contained in a housing	0
0112	ex8529 10 70 45	Ceramic filter for a centre frequency of 450 kHz ($\pm 1,5$ kHz) or 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 30 kHz at 6 dB and not exceeding 70 kHz at 40 dB, contained in a housing	0
0125	ex8529 90 81 31	Demagnetisation coil, with cables and connectors	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0371 ex8542 30 95 04	<p>Frequency synthesiser, operating with an input frequency not exceeding 130 MHz, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): BU 2622 LM 7001 or - other identification markings relating to devices complying with the abovementioned description 	0
0623 ex8542 30 95 10	<p>Encoder/decoder with pulse-code-modulation filter of C-MOS technology, with a dual-power supply, comprising an analogue-to-digital converter and a digital-to-analogue converter, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): MC 145503 MT 896 or - other identification markings relating to devices complying with the abovementioned description 	0
0638 ex8542 30 95 25	<p>Circuit for detecting pre-ignition of an automotive engine, comprising at least 1 amplifier and 1 bandpass filter, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 16205799 HIP 9010 HIP 9011 or - other identification markings relating to devices complying with the abovementioned description 	0
0611 ex8542 30 95 30	<p>Read and write signal circuit for disk storage unit, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 32R1500 32R1501 32R2200 32R2201 32R2202 32R2203 or - other identification markings relating to devices complying with the abovementioned description 	0
0613 ex8542 30 95 31	<p>Audio signal processing circuit, capable of varying high and low frequencies and generating sound effects, comprising an analogue-to-digital converter, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): PM 0006A or - other identification markings relating to devices complying with the abovementioned description 	0
0643 ex8542 30 95 32	<p>Audio circuit of C-MOS technology, with a dynamic range of 70 dB or more, comprising one or more digital-to-analogue converters and one or more analogue-to-digital converters, in the form of a monolithic integrated mixed analogue-digital circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): AD 1845 AD 1847 AD 1848 CS 4225 CS 4231 CS 4248 or - other identification markings relating to devices complying with the abovementioned description 	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0216 ex8542 30 99 05	<p>Field-effect transistor (FET) of the P-channel type, having a drain-to-source breakdown-voltage of -200 or -250 V, operating with a continuous drain-current not exceeding -3,5 A, a drain-to-source resistance not exceeding 2,4 Ω, and with a dissipation rate not exceeding 40 W, comprising a diode, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 9620 9622 J306 or - other identification markings relating to devices complying with the abovementioned description 	0
0231 ex8542 30 99 06	<p>Inverter circuit, comprising 2 bias resistors and 1 transistor of the NPN type, with a collector-base breakdown-voltage of 50 V or more, an emitter-base breakdown-voltage of 5 V or more, a collector current not exceeding 100 mA and with a dissipation rate not exceeding 100 mW, contained in a housing</p>	0
0439 ex8542 30 99 09	<p>Intermediate frequency (IF) signal processing circuit, comprising 2 mixers, 2 amplifiers, and 2 receive signal strength indicators (RSSI), in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): TA 31138 or - other identification markings relating to devices complying with the abovementioned description 	0
0440 ex8542 30 99 18	<p>FM detector, comprising a mixer, and intermediate frequency (IF) amplifier and a receive signal strength indicator (RSSI), in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): TA 31136 or - other identification markings relating to devices complying with the abovementioned description 	0
0657 ex8542 30 99 35	<p>Light detector, comprising 2 photodiodes, a voltage regulator and an amplifier, in the form of a monolithic integrated analogue circuit contained in a housing provided with an infrared filter and bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 474 or - other identification markings relating to devices complying with the abovementioned description 	0
0692b ex8542 30 99 36	<p>Frequency converter of gallium arsenide (GaAs) semiconductor material, with a conversion gain of 6 dB, capable of converting an input frequency of 950 MHz or more but not exceeding 2 050 MHz into an output frequency of 480 MHz, comprising an oscillator, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): ADC 20013 or - other identification markings relating to devices complying with the abovementioned description 	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0694 ex8542 30 99 38	<p>DC-to-DC converter, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): LT 1302 LTC 1174 MB 3799 or - other identification markings relating to devices complying with the abovementioned description 	0
0586 ex8542 30 99 43	<p>Audio signal processing circuit, providing a boost of bass frequencies and phase and amplitude correction, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): BA 3880 or - other identification markings relating to devices complying with the abovementioned description 	0
0707 ex8542 30 99 52	<p>FM-band receiver, providing FM-signal demodulation, comprising at least a mixer, an intermediate frequency (IF) amplifier and a limiter amplifier, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): MC 13156 MC 13158 SA 605 SA 607 SA 617 TA 2027F TA 31136FN-1 TA 31137FN-1 or - other identification markings relating to devices complying with the abovementioned description 	0
0659 ex8542 30 99 53	<p>Receive unit, capable of converting light pulses into electrical signals, operating at a nominal wavelength of 650 nm, comprising at least a photodiode and an amplifier with a bandwidth not exceeding 1 MHz, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): OPT 101 OPT 201 OPT 301 or - other identification markings relating to devices complying with the abovementioned description 	0
0661 ex8542 30 99 55	<p>Audio circuit, providing vocal fader functions, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): BA 3836 BA 3837 or - other identification markings relating to devices complying with the abovementioned description 	0
0662 ex8542 30 99 61	<p>Intermediate frequency (IF) receiver for the AM- and FM-band, providing FM-signal demodulation, operating at a typical supply current of 1,1 or 1,8 mA at a voltage of 1,5 V, comprising an AM/FM switch, an AM amplifier and a FM amplifier, in the form of a monolithic integrated analogue circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): TA 7765 or - other identification markings relating to devices complying with the abovementioned description 	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0023	ex8542 40 10 02	<p>Microcontroller or microcomputer with a processing capacity of 32 bits, comprising 1 or 2 microcontrollere or microcomputere and 4 or 8 static random-access memories (S-RAMs), in the form of a hybrid integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): SMJ320MCM41 SMJ320MCM42 or - other identification markings relating to devices complying with the abovementioned description 	0
0735	ex8542 40 50 01	<p>Amplifier operating with a frequency of 20 Hz or more but not exceeding 50 000 Hz, in the form of a hybrid integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): STK 401 STK 4041 STK 4151 STK 4201 or - other identification markings relating to devices complying with the abovementioned description 	0
0743	ex8542 40 50 09	<p>Amplifier with an input power of 1 mW and an output power not exceeding 3,5 W at a frequency range of 880 MHz or more but not exceeding 915 MHz, in the form of a hybrid integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): QCPM 9401 or - other identification markings relating to devices complying with the abovementioned description 	0
0730	ex8542 40 50 10	<p>Amplifier, capable of driving a colour cathode-ray tube, in the form of a hybrid integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): CVA 2415 CVA 4401 VPS 12 or - other identification markings relating to devices complying with the abovementioned description 	0
0731	ex8542 40 50 11	<p>Amplifier, operating within a frequency range of 824 MHz or more but not exceeding 905 MHz, with an output power of 1,4 W at an input power of 1 mW, in the form of a hybrid integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): PF 0067 or - other identification markings relating to devices complying with the abovementioned description 	0
0777b	ex8542 40 50 12	<p>Amplifier, operating within a frequency range of 800 MHz to 960 MHz, with an output power not exceeding 10 W (40 dBm) and an input power not exceeding 200 mW (23 dBm), in the form of a hybrid integrated circuit contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): PHW 2907 XHW 2803 or - other identification markings relating to devices complying with the abovementioned description 	0
0760	ex8542 50 00 04	<p>Silicon diode assembly, comprising a diode with a reverse recovery time not exceeding 1,5 µs and an average forward current not exceeding 5 A, in the form of a microassembly contained in a housing</p>	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0766 ex8543 89 90 32	<p>Amplifier of gallium arsenide (GaAs) semiconductor material, operating with a frequency range of 1 710 MHz to 1 785 MHz, with an output power not exceeding 3 W at an input power of 1 mW or with an input level not exceeding 5 dBm and an output level of 30,8 dBm or more, consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): FA 01314 EMC 1717 PHW 9012 or - other identification markings relating to devices complying with the abovementioned description 	0
0768 ex8543 89 90 34	<p>Amplifier, operating within a frequency range of 380 MHz or more but not exceeding 470 MHz, with at least one of the following characteristics:</p> <ul style="list-style-type: none"> - a) an output power of 3 W at an input power of 1 mW, - b) an output power of 7 W at an input power of 1 mW, - c) an output power of 20 W at an input power of 150 mW, - d) an output power not exceeding 4,5 W at an input power of 2,2 mW, <p>consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): a) MHW 704 b) MHW 2707 b) MHW 707 c) MHW 720 d) MHW 2701 or - other identification markings relating to devices complying with the abovementioned description 	0
0777 ex8543 89 90 49	<p>Amplifier, operating within a frequency range of 800 MHz to 960 MHz, with at least one of the following characteristics:</p> <ul style="list-style-type: none"> - a) an output power of 1,41 W at an input power of 5 mW, - b) an output power of 2 W at an input power of 1 mW, - c) an output power of 1,8 or 3,2 W at an input power not exceeding 2 mW, - d) an output power of 3,5 W at an input power of 1 or 100 mW, - e) an output power of 6 W at an input power of 100 mW, - f) an output power of 14 W at an input power of 1 or 100 mW, - g) an output power of 7 W at an input power of 20 mW, - h) an output power of 2,4 or 3,2 W at an input power not exceeding 5 mW, - i) an output power not exceeding 10 W and an input power not exceeding 200 mW, - j) an output power not exceeding 25 W and an input power not exceeding 159 mW, - k) an output power of 20 W at an input power of 200 mW, <p>consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): a) MHW 9002 b) MHW 803 c) PF 0144 c) PHW 902 d) MHW 953 d) XHW 903 e) SHW 5115 e) XHW 5115 f) MHW 914 f) MHW 915 g) PF 0146 h) PF 0148 i) FA 01321 i) MHW 910 j) MHW 916 j) MHW 926 j) MHW 927 j) PHW 2905 j) PHW 5113 j) PHW 925 j) XHW 2902 k) MHW 820-1 k) MHW 820-2 or - other identification markings relating to devices complying with the abovementioned description 	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0764 ex8543 89 90 60	<p>Amplifier of gallium arsenide (GaAs) semiconductor material, operating within a frequency range of 1 429 MHz to 1 453 MHz, with an output power not exceeding 1,1 W (30,5 dBm) at an input power not exceeding 1 mW (0 dBm), consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): FA 01317 or - other identification markings relating to devices complying with the abovementioned description 	0
0784 ex8543 90 90 01	<p>Dual transistor, with a dissipation rate not exceeding 300 mW, comprising at least one transistor of the NPN type operating with a collector-emitter voltage not exceeding 50 V at a collector current not exceeding 150 mA, contained in a housing</p>	0
0797 ex9002 20 00 10	<p>Filter, consisting of a plastic polarising membrane, a glass plate and a transparent protective film, mounted on a metal frame, for use in the manufacture of products falling within heading 8528 (a)</p>	0
0808 ex9002 90 90 10	<p>Optical element comprising an octagonal Fresnel lens, for use in the manufacture of overhead projectors (a)</p>	0
0809 ex9002 90 90 20	<p>Lens, mounted, having a fixed focal length of 3,8 mm ($\pm 0,19$ mm) or 8 mm ($\pm 0,4$ mm), with a relative aperture of F2.0 and a diameter not exceeding 33 mm, for use in the manufacture of charged-coupled (CCD) cameras (a)</p>	0
0810 ex9002 90 90 30	<p>Optical unit, comprising 1 or 2 rows of optical glass fibres in the form of lenses and with a diameter of 0,85 mm or more but not exceeding 1,15 mm, embedded between 2 plastic plates</p>	0
0135 ex9013 80 19 10	<p>Monochrome liquid crystal display (LCD) with an active matrix, having a diagonal measurement of the screen not exceeding 3,4 cm, consisting of a layer of liquid crystals between two glass sheets or plates</p>	0

(a)	Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.
-----	-----------------------------------------------------------------------------------------------------------------

ANNEX II

	CN code	Taric		CN code	Taric
ex	2819 90 00	20	ex	2934 90 99	35
ex	2902 90 90	15	ex	2934 90 99	37
ex	2902 90 90	40	ex	2934 90 99	38
ex	2902 90 90	45	ex	2935 00 00	30
ex	2902 90 90	70	ex	2935 00 00	40
ex	2905 39 90	30	ex	2935 00 00	45
ex	2917 39 90	35	ex	3507 90 00	65
ex	2917 39 90	75	ex	3507 90 00	70
ex	2921 19 90	30	ex	3701 30 00	10
ex	2921 30 90	20	ex	3815 19 00	03
ex	2921 59 00	60	ex	3815 19 00	11
ex	2926 90 90	15	ex	3815 19 00	13
ex	2926 90 90	25	ex	3815 19 00	14
ex	2926 90 90	65	ex	3815 19 00	15
ex	2926 90 90	75	ex	3815 19 00	16
ex	2926 90 90	80	ex	3815 90 00	15
ex	2926 90 90	85	ex	3815 90 00	20
ex	2928 00 00	50	ex	3815 90 00	25
ex	2928 00 00	60	ex	3815 90 00	35
ex	2930 90 95	04	ex	3815 90 00	55
ex	2930 90 95	06	ex	3815 90 00	70
ex	2930 90 95	09	ex	3815 90 00	75
ex	2930 90 95	11	ex	3815 90 00	80
ex	2930 90 95	15	ex	3815 90 00	86
ex	2930 90 95	17	ex	3815 90 00	87
ex	2932 29 90	15	ex	3824 90 60	02
ex	2932 29 90	30	ex	3824 90 60	03
ex	2932 29 90	55	ex	3824 90 60	04
ex	2932 29 90	61	ex	3824 90 60	06
ex	2932 29 90	62	ex	3824 90 60	07
ex	2932 29 90	70	ex	3824 90 90	01
ex	2932 29 90	75	ex	3824 90 90	02
ex	2932 29 90	76	ex	3824 90 90	03
ex	2932 29 90	77	ex	3824 90 90	04
ex	2933 39 80	14	ex	3824 90 90	05
ex	2933 39 80	18	ex	3824 90 90	07
ex	2933 39 80	23	ex	3824 90 90	08
ex	2933 39 80	28	ex	3824 90 90	11
ex	2933 39 80	29	ex	3824 90 90	12
ex	2933 59 80	10	ex	3824 90 90	13
ex	2933 69 90	20	ex	3824 90 90	14
ex	2933 69 90	30	ex	3824 90 90	15
ex	2933 69 90	35	ex	3824 90 90	16
ex	2933 69 90	40	ex	3824 90 90	18
ex	2933 90 80	23	ex	3824 90 90	19
ex	2933 90 80	24	ex	3824 90 90	21
ex	2933 90 80	27	ex	3824 90 90	22
ex	2933 90 80	28	ex	3824 90 90	23
ex	2933 90 80	30	ex	3824 90 90	26
ex	2933 90 80	31	ex	3824 90 90	27

	CN code	Taric		CN code	Taric
ex	3824 90 90	28	ex	3920 69 00	30
ex	3824 90 90	29	ex	3920 10 22	95
ex	3824 90 90	31	ex	3920 10 22	96
ex	3824 90 90	32	ex	3920 10 80	95
ex	3824 90 90	35	ex	3920 62 10	10
ex	3824 90 90	36	ex	3920 62 10	20
ex	3824 90 90	37	ex	3920 62 10	45
ex	3824 90 90	38	ex	3920 62 10	50
ex	3824 90 90	39	ex	3920 62 10	55
ex	3824 90 90	41	ex	3920 62 10	60
ex	3824 90 90	47	ex	3920 62 10	65
ex	3824 90 90	48	ex	3920 62 10	70
ex	3901 20 00	10	ex	3920 62 10	75
ex	3901 20 00	20	ex	3920 62 10	80
ex	3901 90 00	92	ex	3920 99 50	24
ex	3901 90 00	97	ex	3920 99 50	26
ex	3902 90 00	92	ex	3920 99 50	28
ex	3902 90 00	97	ex	3920 99 50	36
ex	3903 90 00	60	ex	3920 99 50	37
ex	3903 90 00	20	ex	3920 99 50	38
ex	3903 90 00	25	ex	3920 99 50	39
ex	3903 90 00	40	ex	4805 60 90	10
ex	3903 90 00	70	ex	5603 11 10	10
ex	3903 90 00	80	ex	5603 11 90	10
ex	3911 90 90	89	ex	5603 12 10	10
ex	3904 50 00	92	ex	5603 12 90	10
ex	3904 69 00	92	ex	5603 91 10	10
ex	3904 69 00	95	ex	5603 91 90	10
ex	3904 69 00	96	ex	5603 92 10	10
ex	3905 99 00	94	ex	5603 92 90	10
ex	3905 99 00	95	ex	7011 20 00	40
ex	3905 99 00	96	ex	7011 20 00	80
ex	3906 90 00	70		8202 40 00	
ex	3906 90 00	80	ex	8471 60 90	10
ex	3907 20 29	10	ex	8471 60 90	20
ex	3907 20 90	15	ex	8471 90 00	10
ex	3907 20 90	20	ex	8473 30 10	35
ex	3907 20 90	40	ex	8483 10 90	10
ex	3907 20 90	60	ex	8501 10 99	78
ex	3907 20 90	70		8504 90 11	
ex	3907 99 10	10	ex	8517 90 11	01
ex	3907 99 90	10	ex	8517 90 11	02
ex	3907 99 10	30	ex	8517 90 11	03
ex	3911 90 10	20	ex	8517 90 11	04
ex	3911 90 90	85	ex	8517 90 11	05
ex	3911 90 90	87	ex	8517 90 11	06
ex	3208 90 10	30	ex	8517 90 82	30
ex	3911 90 90	91	ex	8522 90 98	33
ex	3911 90 90	92	ex	8529 90 81	31
ex	3911 90 90	93	ex	8529 90 81	34
ex	3912 39 90	10	ex	8531 20 30	10
ex	3912 39 90	40	ex	8531 20 80	10
ex	3919 90 31	40	ex	8531 80 90	10
ex	3920 62 10	40	ex	8531 80 90	20
ex	3920 62 90	20	ex	8531 80 90	30
ex	3920 63 00	30	ex	8534 00 19	92

	CN code	Taric		CN code	Taric
ex	8540 12 00	81	ex	8542 30 50	10
ex	8540 12 00	83	ex	8542 30 69	02
ex	8541 10 91	20	ex	8542 30 95	03
ex	8541 40 19	20	ex	8542 30 95	10
ex	8542 13 11	03	ex	8542 30 95	25
ex	8542 13 13	04	ex	8542 30 95	32
	8542 13 53		ex	8542 30 95	42
	8542 14 25		ex	8542 30 99	38
	8542 19 49		ex	8542 30 99	52
ex	8542 13 63	02	ex	8542 30 99	60
ex	8542 13 63	08	ex	8542 40 50	01
ex	8542 13 63	18	ex	8542 40 50	06
ex	8542 13 67	01	ex	8542 40 50	09
ex	8542 13 67	10	ex	8542 40 90	10
ex	8542 13 99	04	ex	8542 50 00	04
ex	8542 13 99	05	ex	8543 89 90	32
ex	8542 13 99	38	ex	8543 89 90	34
ex	8542 13 99	47	ex	8543 89 90	47
ex	8542 13 99	57	ex	8543 89 90	49
ex	8542 14 99	13	ex	8543 89 90	51
ex	8542 19 98	04	ex	9002 90 91	10
ex	8542 30 30	22	ex	9002 90 91	20
ex	8542 30 30	26	ex	9002 90 99	10
ex	8542 30 30	27		9013 80 30	

FINANCIAL STATEMENT

1. Budget heading involved : Chapter 12 Article 120
2. Title of operation : Proposal for a Council Regulation amending the Annex to Council Regulation (EC) No 1255/96 temporarily suspending the autonomous Common Customs Tariff duties on certain industrial and agricultural products.
3. Legal basis : Article 28 of the EC Treaty.
4. Objective: Suspension of the CCT duties for the above products.
5. Measures aimed at prevention and protection: Checks on the end-use of some of the products covered by this Council Regulation will be carried out in accordance with Articles 291 to 304 of Commission Regulation (EEC) No 2454/93 laying down provisions for the implementation of the Community Customs Code.
6. Cost :

In order to reduce the economic problems linked with the period of validity of previous Regulations, Council Regulation (EC) No 1255/96,¹ at present in force, does not have a date marking the end of its period of validity.

This proposal of Council Regulation contains only the amendments which must be made to the Annex to the existing Regulation in order to take account of the following:

1. new requests for suspension which have been presented and accepted;
2. technical developments in products or economic trends on the market, resulting in the lifting of certain existing suspensions;
3. amendments to nomenclature codes.

Almost all these amendments take the form of two Annexes which contain, respectively, the list of new products, or products the description of which has been amended, and the list of products removed from the Annex to Regulation (EC) No 1255/96.

Obviously, only the first two amendments have a financial impact.

Annex I (addition):

This Annex, in addition to the amendments resulting from a change in CN code, contains 96 new products. The corresponding suspensions give rise to an amount of duties not collected, calculated on the basis of the expected imports into the requesting Member State for 1996, of ECU 13.60 million.

On the basis of the existing statistics for the preceding years, it appears, however, that this amount must be increased by an average factor which may be estimated at 1.8, to take account of imports into other Member States using the same suspensions. This means a loss of revenue of some ECU 24 million.

¹ OJ L158, 29 June 1996, p.1.

Annex II (removal):

This Annex provides for the removal of 29 products corresponding in 1994 (most recent statistics available) to uncollected duties of ECU 7.6 million, determined for a Community of 12. In view of the suspensions granted to the three states which joined the Community in 1995, this total must be increased by about 9%, i.e. additional revenue of some ECU 8.25 million.

Estimated cost of the present operation

For the coming year, the duty not collected as a result of from this Regulation may therefore, in the light of the approximate calculations made, be estimated at about ECU 16 million.

Comments:

Taking account of the regulation currently in force (No 1255/96), for which the duty not collected for the same year was estimated at 65 MECU², the increase in the amount of duty not collected in 1997 should therefore amount to about 81 MECU.

² Proposal for a Council Regulation, corresponding to Regulation (EC) No 1255/96.

ISSN 0254-1475

COM(96) 578 final

DOCUMENTS

EN

02 03 01 10

Catalogue number : CB-CO-96-578-EN-C

ISBN 92-78-11524-X

Office for Official Publications of the European Communities

L-2985 Luxembourg