



COMMISSION OF THE EUROPEAN COMMUNITIES

Brussels, 14.12.1999
COM(1999) 642 final

Proposal for a

COUNCIL REGULATION (EC)

**amending Regulation (EC) No 1255/96 temporarily suspending the autonomous
common customs tariff duties on certain industrial and agricultural products**

(presented by the Commission)

EXPLANATORY MEMORANDUM

During the third quarter of this year, the Commission, assisted by the Economic Tariff Questions Group, has reviewed all the requests for temporary suspension of autonomous common customs tariff duties presented to it by the Member States, including requests for extending suspensions at present in force.

The attached proposal concerns certain industrial and agricultural products.

Requests for suspension relating to the above products were examined in the light of the criteria set out in the communication from the Commission concerning autonomous tariff suspensions and quotas (see OJ C 128, 25.4.1998, p. 2).

Following this review, the Commission considers that the suspension of duties is justified for the products listed in the Annex to the attached proposal for a Regulation.

Products for which suspension is no longer in the Community's economic interests or which are exempt from duty under GATT have been withdrawn from the annex.

The period of validity of the proposed measure is unspecified, since its purpose is to amend the Annex to Council Regulation (EC) No 1255/96, the period of validity of which is itself unspecified.

Proposal for a

COUNCIL REGULATION (EC)

amending Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial and agricultural products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty establishing the European Community, and in particular Article 26 thereof,

Having regard to the proposal from the Commission¹,

Whereas:

- (1) It is in the interest of the Community to suspend partially or totally the autonomous common customs tariff duties for a number of new products not listed in the Annex to Regulation (EC) No 1255/96².
- (2) The products referred to in the said Regulation for which it is no longer in the Community's interest to maintain suspension of autonomous Common Customs Tariff duties, or which are exempt from duty under GATT or for which it is necessary to amend the description in the light of technical developments, should be withdrawn from the list in the Annex thereto.
- (3) Products whose description requires amendment should accordingly be regarded as new products.
- (4) In view of the large number of amendments with effect from 1 January 2000, the whole of the Annex to Regulation (EC) No 1255/96 should be replaced for the sake of clarity,

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EC) No 1255/96 is replaced by the text in the Annex to this Regulation.

¹ OJ C

² OJ L 158, 29.6.1996, p. 1. Regulation as last amended by Regulation (EC) No 1381/99 (OJ L 165, 30.6.1999, p. 1).

Article 2

This Regulation shall enter into force on the third day following that of its publication in the *Official Journal of the European Communities*.

It shall apply with effect from 1 January 2000.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels,

*For the Council
The President*

ANNEX

"ANNEX

CN code & TARIC		Description	Rate of autonomous duty (%)
0010	ex0603 90 00 10 ex0604 99 10 10 ex0604 99 90 10	Flowers, flower buds, foliage, leaves and other parts of plants, not further prepared than dried, dyed or bleached, for use in the manufacture of pot pourri of subheading 3307 49 00 (a)	0
0011	ex0710 21 00 10	Peas in pods, of the species <i>Pisum sativum</i> of the variety <i>Hortense axiphium</i> , frozen, of a thickness not exceeding 6 mm, to be used, in their pods, in the manufacture of prepared meals (a) (b)	0
0012	ex0711 90 60 11 ex0711 90 60 91	Mushrooms, excluding mushrooms of the species <i>Agaricus spp.</i> , provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry (a)	0
0013	ex0712 30 00 17 ex0712 30 00 24	Mushrooms, excluding mushrooms of the species <i>Agaricus spp.</i> , dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale (a) (b)	0
0014	ex0713 33 90 20	Beans, white, dried, of the species <i>Phaseolus vulgaris</i> , of which not more than 2 % by weight are retained by a screen with apertures of a diameter of 8 mm	0
0015	ex0804 10 00 11 ex0804 10 00 21	Dates, fresh or dried, for the processing industry, other than for the production of alcohol (a)	0
0016	ex0804 10 00 12 ex0804 10 00 22	Dates, fresh or dried, for packing for retail sale into immediate packings of a net content not exceeding 11 kg (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0017	ex0810 40 50 10	Fruit of the species <i>Vaccinium macrocarpon</i> , fresh	0
0018	ex0810 90 85 10	Rose-hips, fresh	0
0019	0811 90 50 0811 90 70 ex0811 90 95 66 ex0811 90 95 67	Fruit of the genus <i>Vaccinium</i> , uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0
0020	ex0811 90 95 40	Rose-hips, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0
CN code & TARIC		Description	Rate of autonomous duty (%)
0001	ex1518 00 91 10	Soya-bean oil, modified with maleic acid, for the manufacture of cosmetic products (a)	0
0002	ex2707 99 11 10	Crude light oils containing by weight: <ul style="list-style-type: none"> - 10 % or more of vinyltoluenes, - 10 % or more of indene and - 1 % or more but not more than 5 % of naphthalene 	0
0003	ex2805 30 10 10	Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0004	ex2805 30 10 20	Alloy of lanthanum and other rare-earth metals, containing by weight 43 % or more of lanthanum	0
0005	ex2805 30 90 10	Lanthanum of a purity by weight of 99 % or more	0
0006	ex2811 19 80 10	Sulfamidic acid	0
0007	ex2811 22 00 10	Silicon dioxide in the form of powder, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (a)	0
0008	ex2811 29 90 10	Tellurium dioxide	0
0009	ex2812 90 00 10	Nitrogen trifluoride	0
0010	ex2818 30 00 10	Aluminium hydroxide oxide in the form of pseudo-boehmite	4
0011	ex2819 90 90 10	Dichromium trioxide: <ul style="list-style-type: none"> - of a specific surface of 37 m²/g or more (as determined by the BET method), - of a purity by weight of 99,5 % or more calculated on the dry substance, - of a specific gravity of 1,2 g/cm³ or less, for the manufacture of magnetic chromium dioxide (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0012	ex2820 90 90 10	Manganese (II,III) oxide containing by weight 70 % or more of manganese	0
0013	ex2821 10 00 10	Diiron trioxide, in the form of powder, of a purity by weight of 99,2 % or more, for the manufacture of goods of heading No 8504 (a)	0
0014	ex2823 00 00 10	Titanium dioxide, of a purity by weight of 99,9 % or more, with an average grain-size of 1,2 µm or more but not exceeding 1,8 µm, for the manufacture of goods of heading No 8532 or 8533 (a)	0
0015	ex2825 50 00 10	Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride	0
0016	ex2826 90 90 10	Potassium hexafluorophosphate	0
0017	ex2827 39 90 10	Copper monochloride of a purity by weight of 96 % or more but not exceeding 99 %	0
0018	ex2827 60 00 10	Titanium tetraiodide	0
0019	ex2830 20 00 10	Zinc sulfide containing: <ul style="list-style-type: none"> - 20,0 mg/kg or less of chloride, - 0,2 mg/kg or less of copper, - 0,5 mg/kg or less of iron and - 1,0 mg/kg or less of lead 	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0020 ex2836 91 00 20	<p>Lithium carbonate, containing one or more of the following impurities at the concentrations indicated:</p> <ul style="list-style-type: none"> - 2 mg/kg or more of arsenic, - 200 mg/kg or more of calcium, - 200 mg/kg or more of chlorides, - 20 mg/kg or more of iron, - 150 mg/kg or more of magnesium, - 20 mg/kg or more of heavy metals, - 300 mg/kg or more of potassium, - 300 mg/kg or more of sodium, - 200 mg/kg or more of sulfates, <p>determined according to the methods specified in the European Pharmacopoeia</p>	0
0021 ex2837 19 00 10	Zinc cyanide	0
0022 ex2839 90 00 10	Lead silicate hydrate, of a lead content by weight of $(84,5 \pm 1,5) \%$, evaluated as lead monoxide, in the form of powder	0
0023 ex2843 90 90 20	Palladium monoxide	0
0024 ex2843 90 90 30	Mixture of palladium phthalocyanines	0
0025 2845 10 00	Heavy water (deuterium oxide) (<i>Euratom</i>)	0
0026 2845 90 10	Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products (<i>Euratom</i>)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0027	ex2846 10 00 10 ex3824 90 95 48	Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight	0
0028	ex2850 00 20 10	Silane	0
0029	ex2903 30 80 10	Carbon tetrafluoride (tetrafluoromethane)	0
0030	ex2903 30 80 20	1,1,1,2,3,3,3-Heptafluoropropane	0
0031	ex2903 30 80 30	Perfluoroethane	0
0032	ex2903 30 80 40	1,1-Difluoroethane	0
0033	ex2903 59 90 10	1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo=[12.2.1.1 ^{6,9} .0 ^{2,13} .0 ^{5,10}]octadeca-7,15-diene, for use in the manufacture of polyamide, polyethylene, synthetic rubber or polystyrene (a)	0
0034	ex2903 59 90 20	Hexachlorocyclopentadiene	0
0035	ex2903 69 90 10	Di- or tetrachlorotricyclo[8.2.2.2 ^{4,7}]hexadeca-1(12),4,6,10,13,15-hexaene, mixed isomers	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0036	ex2903 69 90 40	2,6-Dichlorotoluene, of a purity by weight of 99 % or more and containing: <ul style="list-style-type: none"> - 0,001 mg/kg or less of tetrachlorodibenzodioxines, - 0,001 mg/kg or less of tetrachlorodibenzofurans, - 0,2 mg/kg or less of tetrachlorobiphenyls 	0
0037	ex2903 69 90 50	1-(Chloromethyl)naphthalene	0
0038	ex2904 10 00 30	Sodium <i>p</i> -styrenesulfonate	0
0039	ex2904 20 00 10	Nitromethane	0
0040	ex2904 20 00 20	Nitroethane	0
0041	ex2904 20 00 30	1-Nitropropane	0
0042	ex2904 20 00 40	2-Nitropropane	0
0043	ex2904 90 20 10	Tosyl chloride	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0044	ex2904 90 40 10	Trichloronitromethane, for the manufacture of goods of subheading 3808 20 (a)	0
0045	ex2904 90 85 10	Quintozene (ISO)	0
0046	ex2905 19 00 10 ex3824 90 95 56	Potassium <i>tert</i> -butanolate (potassium <i>tert</i> -butoxide), whether or not in the form of a solution in tetrahydrofuran	0
0048	2905 29 10	Allyl alcohol	0
0049	ex2905 39 80 10	2-Methylpropane-1,3-diol	0
0050	ex2905 49 10 10	Ethylidynetrimethanol	0
0052	2906 11 00	Menthol	0
0053	ex2906 19 00 10	Cyclohex-1,4-ylenedimethanol	0
0054	ex2906 19 00 20	4,4'-Isopropylidenedicyclohexanol	0
0055	ex2906 29 00 10	2,2'-(<i>m</i> -Phenylene)dipropan-2-ol	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0056	ex2907 21 00 10	Resorcinol	0
0057	ex2907 29 00 10	Disodium 1,4-dihydroanthracene-9,10-diolate, in the form of an aqueous solution	0
0058	ex2907 29 00 20	4,4'-(3,3,5-Trimethylcyclohexylidene)diphenol	0
0059	ex2907 29 00 30	4,4',4''-Ethylidynetriphenol	0
0060	ex2907 29 00 40	Mixture of isomers of methylenediphenol	0
0061	ex2907 29 00 50	6,6',6''-Tricyclohexyl-4,4',4''-butane-1,1,3-triyltri(<i>m</i> -cresol)	0
0062	ex2908 20 00 10	Disodium 3-hydroxynaphthalene-2,7-disulfonate	0
0061bi	ex2908 20 00 20	Dipotassium 7-hydroxynaphthalene-1,3-disulfonate	0
0063	ex2908 90 00 10	4-Nitroso- <i>o</i> -cresol	0
0064	ex2909 19 00 10	1,2-Bis(2-chloroethoxy)ethane	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0065	ex2909 30 90 10	4-(<i>p</i> -Tolyloxy)biphenyl	0
0066	ex2909 30 90 20	1,2-Bis(<i>m</i> -tolyloxy)ethane	0
0067	ex2909 30 90 30	1,2-Diphenoxyethane	0
0068	ex2909 44 00 10	2-Hexyloxyethanol	0
0069	ex2909 49 19 10	1- <i>tert</i> -Butoxypropan-2-ol	0
0070	ex2909 50 90 10	4-(2-Methoxyethyl)phenol	0
0071	ex2910 90 00 30	2,3-Epoxypropan-1-ol (glycidol)	0
0072	ex2910 90 00 40	Perfluoroepoxypropane	0
0073	ex2910 90 00 60 ex3824 90 95 59	1,2-Epoxyoctadecane, of a purity by weight of 82 % or more	0
0074	ex2912 29 00 10	Terephthalaldehyde	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0075	ex2912 49 00 10	3-Phenoxybenzaldehyde	0
0076	ex2914 19 90 10	3,3-Dimethylbutan-2-one	0
0077	2914 21 00	Camphor	0
0078	ex2914 29 00 10	Estr-4-ene-3,17-dione	0
0079	ex2914 50 00 30	2'-Hydroxyacetophenone	0
0080	ex2914 50 00 40	4'-Hydroxyacetophenone	0
0081	ex2914 50 00 50	6'-Methoxy-2'-acetonaphthone	0
0082	ex2914 70 90 10	1-Chloro-3,3-dimethylbutan-2-one	0
0083	ex2914 70 90 30	4,4'-Dibromobenzil	0
0084	ex2915 29 00 10	Antimony triacetate	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0085	ex2915 39 90 20	5 α -Bromo-6 β -hydroxy-17-oxo-androstan-3 β -yl acetate	0
0086	ex2915 39 90 30	But-3-ene-1,2-diyl di(acetate)	0
0087	ex2915 40 00 10	Vinyl chloroacetate	0
0088	ex2915 60 19 10	2,2,4-Trimethylpentane-1,3-diol monoisobutyrate	0
0089	ex2915 90 80 20	Trimethyl orthoacetate	0
0090	ex2915 90 80 30	2-Ethylbutyric acid	0
0091	ex2915 90 80 40	Nonanoic acid (pelargonic acid)	0
0092	ex2916 12 90 10	2- <i>tert</i> -Butyl-6-(3- <i>tert</i> -butyl-2-hydroxy-5-methylbenzyl)= -4-methylphenyl acrylate	0
0093	ex2916 12 90 20	2-Ethoxyethyl acrylate	0
0094	ex2916 12 90 30	Isobutyl acrylate	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0095	ex2916 14 90 10	2,3-Epoxypropyl methacrylate	0
0096	ex2916 19 80 20	Methyl 3,3-dimethylpent-4-enoate	0
0097	ex2916 20 00 10	Methyl 3-(2,2-dichlorovinyl)-2,2-dimethylcyclopropanecarboxylate	0
0098	ex2916 20 00 30	Empenthrin (ISO)	0
0100	ex2916 39 00 10	Methyl 3-chlorobenzoate	0
0101	ex2916 39 00 20	3,5-Dichlorobenzoyl chloride	3.6
0102	ex2916 39 00 40	Vinyl 4- <i>tert</i> -butylbenzoate	0
0103	ex2916 39 00 50	3,5-Dimethylbenzoyl chloride	0
0104	ex2916 39 00 60	4-Ethylbenzoyl chloride	0
0105	ex2917 11 00 20	Bis(<i>p</i> -methylbenzyl) oxalate	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0106	ex2917 19 90 20	Sodium 1,2-bis(cyclohexyloxycarbonyl)ethanesulfonate	0
0106bi	ex2917 19 90 40	Dodecanedioic acid, of a purity by weight of more than 98,5 %	0
0107	ex2917 19 90 50	Glutaric anhydride	0
0108	ex2917 20 00 30	1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride	0
0109	ex2917 39 80 10	Dimethyl naphthalene-2,6-dicarboxylate	0
0110	ex2917 39 80 20	Benzene-1,2,4,5-tetracarboxylic acid (pyromellitic acid)	0
0111	ex2917 39 80 30	Benzene-1,2:4,5-tetracarboxylic dianhydride (pyromellitic dianhydride)	0
0112	ex2918 13 00 10	L-(-)-Di- <i>p</i> -toluoyltartaric acid	0
0113	ex2918 17 00 10	R-Phenylglycolic acid (D-mandelic acid)	0
0114	ex2918 19 99 40	L-Malic acid	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0115	ex2918 29 10 10	2-Hydroxy-1-naphthoic acid	0
0116	ex2918 29 50 10	Gallic acid, of a purity by weight of 98,5 % or more calculated on the dry weight (measured by acidimetry)	0
0117	ex2918 29 90 10	Hexamethylene bis[3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate]	0
0118	ex2918 90 90 10	3,4-Epoxy-cyclohexylmethyl 3,4-epoxy-cyclohexanecarboxylate	0
0119	ex2919 00 90 10	2,2'-Methylenebis(4,6-di- <i>tert</i> -butylphenyl) phosphate, monosodium salt	0
0120	ex2920 10 00 10	Fenitrothion (ISO)	0
0121	ex2920 10 00 20	Tolclofos-methyl (ISO)	0
0122	ex2920 90 10 10	Diethyl sulfate	0
0123	2920 90 30	Trimethyl phosphite	0
0124	ex2920 90 85 10	<i>O,O'</i> -Dioctadecyl pentaerythritol bis(phosphite)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0125	ex2920 90 85 30	<i>O,O'</i> -Bis(2,4-di- <i>tert</i> -butylphenyl)pentaerythritol bis(phosphite)	0
0126	ex2921 19 80 10	Triallylamine	0
0127	ex2921 19 80 20	Ethyl(2-methylallyl)amine	0
0128	ex2921 29 00 10	<i>N,N,N',N'</i> -Tetrabutylhexamethylenediamine	0
0129	ex2921 29 00 20	Tris[3-(dimethylamino)propyl]amine	0
0130	ex2921 29 00 30	Bis[3-(dimethylamino)propyl]methylamine	0
0131	ex2921 30 99 10	Dicyclohexyl(methyl)amine	0
0133	ex2921 42 10 10	2,6-Dichloro-4-nitroaniline	0
0134	ex2921 42 10 20	2-Bromo-4,6-dinitroaniline	0
0135	ex2921 42 10 30	4-Aminobenzene-1,3-disulfonic acid and its salts	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0136	ex2921 42 10 40	2-Bromo-6-chloro-4-nitroaniline	0
0132	ex2921 42 10 50	3-Aminobenzenesulfonic acid	0
0137	ex2921 43 00 10	5-Amino-2-chlorotoluene-4-sulfonic acid	0
0138	ex2921 43 00 20	4-Amino-6-chlorotoluene-3-sulfonic acid	0
0140	ex2921 44 00 10	Methyldiphenylamine	0
0142	ex2921 45 00 10	3-Aminonaphthalene-1,5-disulfonic acid, monosodium salt	0
0143	ex2921 45 00 20	2-Aminonaphthalene-1,5-disulfonic acid and its sodium salts	0
0144	ex2921 45 00 30	2-Aminonaphthalene-1-sulfonic acid	0
0141	ex2921 45 00 40	1-Naphthylamine	0
0145	ex2921 49 10 20	Pendimethalin (ISO)	3.5

CN code & TARIC		Description	Rate of autonomous duty (%)
0146	ex2921 49 90 10	8-Anilino-naphthalene-1-sulfonic acid	0
0147	ex2921 59 90 10	Mixture of isomers of 3,5-diethyltoluenediamine	0
0139	ex2921 59 90 20 ex3824 90 95 68	4-(4-Aminoanilino)-3-nitrobenzenesulfonic acid	0
0149	ex2922 19 90 55	4,4-Dimethoxybutylamine	0
0150	ex2922 19 90 60	2-[2-(Dimethylamino)ethyl(methyl)amino]ethanol	0
0151	ex2922 19 90 70	<i>N,N,N',N'</i> -Tetramethyl-2,2'-oxybis(ethylamine)	0
0152	ex2922 21 00 10	2-Amino-5-hydroxynaphthalene-1,7-disulfonic acid and its salts, of a purity by weight of 60 % or more	0
0153	ex2922 21 00 20	4-Hydroxy-7-methylaminonaphthalene-2-sulfonic acid	0
0154	ex2922 21 00 30	6-Amino-4-hydroxynaphthalene-2-sulfonic acid	0
0155	ex2922 21 00 40	7-Amino-4-hydroxynaphthalene-2-sulfonic acid	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0157	ex2922 22 00 10	Anisidines	0
0159	ex2922 29 00 10	2-Methyl- <i>N</i> -phenyl- <i>p</i> -anisidine	0
0160	ex2922 29 00 20	3-Aminophenol	0
0161	ex2922 29 00 30	4-Amino-5-methoxy-2-methylbenzenesulfonic acid	0
0162	ex2922 29 00 40	2-Amino-4- <i>tert</i> -pentyl-6-nitrophenol	0
0163	ex2922 29 00 50	6-Methoxy- <i>m</i> -toluidine	0
0164	ex2922 29 00 60	3,5-Dichloro-4-(1,1,2,2-tetrafluoroethoxy)aniline	0
0165	ex2922 29 00 70	4-Nitro- <i>o</i> -anisidine	0
0166	ex2922 30 00 10	1-Amino-4-bromo-9,10-dioxoanthracene-2-sulfonic acid and its salts	0
0167	ex2922 30 00 20	1-Aminoanthraquinone	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0168	ex2922 49 70 10	Ornithine aspartate (INN)	0
0169	ex2922 50 00 50	2-(4-Dibutylaminosalicyloyl)benzoic acid	0
0170	ex2923 90 00 10	Tetramethylammonium hydroxide, in the form of an aqueous solution containing: <ul style="list-style-type: none"> - (25 ± 0,5) % by weight of tetramethylammonium hydroxide, - 500 mg/kg or less of carbonate, - 200 mg/kg or less of chloride and - 5 mg/kg or less of potassium 	0
0172	ex2924 10 00 20	2-Acrylamido-2-methylpropanesulfonic acid and its sodium or ammonium salts	0
0173	ex2924 10 00 30	N-(1,1-Dimethyl-3-oxobutyl)acrylamide	0
0171	ex2924 10 00 40	N,N'-Methylenediacrylamide	0
0174	ex2924 21 90 10 ex3824 90 95 62	4,4'-Dihydroxy-7,7'-ureylenedi(naphthalene-2-sulfonic acid) and its sodium salts	0
0175	ex2924 29 90 10	Alachlor (ISO)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0176	ex2924 29 90 15	Acetochlor (ISO)	0
0177	ex2924 29 90 20	3'-Amino-4'-methoxyacetanilide	0
0178	ex2924 29 90 25	3'-Diethylaminoacetanilide	0
0180	ex2924 29 90 35	Propachlor (ISO)	0
0181	ex2924 29 90 40	Diethofencarb (ISO)	0
0182	ex2924 29 90 45	7-Acetamido-4-hydroxynaphthalene-2-sulfonic acid and its sodium salts	0
0183	ex2924 29 90 50	3'-Diethylamino-4'-methoxyacetanilide	0
0184	ex2924 29 90 60	5-[N-(2-Acetoxyethyl)acetoxyacetamido]-N,N'-bis(2,3-diacetoxy= propyl)-2,4,6-triiodoisophthalamide	0
0185	ex2924 29 90 70	4'-Amino-N-methylacetanilide	0
0187	ex2925 11 00 20	Saccharin and its sodium salt	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0188	ex2925 19 80 10	<i>N</i> -Phenylmaleimide	0
0189	ex2925 20 00 10	Dicyclohexylcarbodiimide	0
0191	ex2926 90 99 10	Methacrylonitrile	0
0192	ex2926 90 99 30	2-Amino-5-nitrobenzonitrile	0
0193	ex2926 90 99 40	Chlorothalonil (ISO)	0
0194	ex2926 90 99 45	2-Cyanoacetamide	0
0195	ex2926 90 99 50	Alkyl or alkoxyalkyl esters of cyanoacetic acid	0
0196	ex2926 90 99 60	Cyanoacetic acid in crystalline form	0
0197	ex2926 90 99 65	Malononitrile	0
0190	ex2926 90 99 70	Tetrachloroterephthalonitrile	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0199	ex2927 00 00 10	2,2'-Dimethyl-2,2'-azodipropionamide dihydrochloride	0
0200	ex2927 00 00 20	4-Anilino-2-methoxybenzenediazonium hydrogen sulfate	0
0198	ex2927 00 00 30 ex3824 90 95 69	4'-Aminoazobenzene-4-sulfonic acid	0
0203	ex2928 00 90 10	3,3'-Bis(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)- <i>N,N'</i> -bipropionamide	0
0204	ex2928 00 90 20	2,4,6-Trichlorophenylhydrazine	0
0205	ex2928 00 90 30	<i>tert</i> -Butylhydrazine hydrochloride, for the manufacture of goods of subheading 3808 10 (a)	0
0201	ex2928 00 90 40	<i>O</i> -Ethylhydroxylamine, in the form of an aqueous solution	0
0202	ex2928 00 90 50	<i>N</i> -Isopropylhydroxylamine, in the form of an aqueous solution	0
0206	ex2929 10 90 10	Methylenedicyclohexyl diisocyanate, mixed isomers	0
0207	ex2929 10 90 30	3,3'-Dimethylbiphenyl-4,4'-diyl diisocyanate	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0208	ex2929 10 90 40	<i>m</i> -Isopropenyl- α , α -dimethylbenzyl isocyanate	0
0209	ex2929 10 90 50	<i>m</i> -Phenylenediisopropylidene diisocyanate	0
0210	ex2929 10 90 60	Trimethylhexamethylene diisocyanate, mixed isomers	0
0212	ex2930 90 70 10	Thiophenol	0
0213	ex2930 90 70 15	Ethoprophos (ISO)	0
0214	ex2930 90 70 20	3,3-Dimethyl-1-methylthiobutanone oxime	0
0215	ex2930 90 70 25	Thiophanate-methyl (ISO)	0
0216	ex2930 90 70 30	4-(4-Isopropoxyphenylsulfonyl)phenol	0
0217	ex2930 90 70 40	3,3'-Thiodi(propionic acid)	0
0218	ex2930 90 70 45	2-[(<i>p</i> -Aminophenyl)sulfonyl]ethyl hydrogen sulfate	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0219	ex2930 90 70 50 ex3824 90 95 51	2-Chlorophenylsulfonyl isocyanate, in the form of a solution in xylene	0
0220	ex2930 90 70 55 ex3824 90 95 52	Methyl 2-(isocyanatosulfonyl)methylbenzoate, in the form of a solution in xylene	0
0221	ex2930 90 70 60	Methyl phenyl sulfide	0
0211a	ex2930 90 70 65	Diiodomethyl <i>p</i> -tolyl sulfone	0
0405	ex2930 90 70 70 ex3824 90 95 71	2-Aminophenyl phenyl sulfone, of a purity by weight of 75 % or more	0
0222	2931 00 10	Dimethyl methylphosphonate	0
0223	ex2931 00 95 10	2-Diphenylphosphinobenzoic acid	0
0225	ex2931 00 95 20	Bis(2-chloroethyl) 2-chloroethylphosphonate	0
0226	ex2931 00 95 25	Sodium phenylphosphinate	0
0227	ex2931 00 95 30	Bis(2-chloroethyl) vinylphosphonate	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0228	ex2931 00 95 35	Sodium tetraphenylborate	0
0229	ex2931 00 95 40	N-(Phosphonomethyl)iminodiacetic acid	0
0230	ex2931 00 95 45	Tributylphosphine	0
0231	ex2931 00 95 50	Bis(2,4,4-trimethylpentyl)phosphinic acid	0
0232	ex2931 00 95 55	Dimethyl[dimethylsilyldiindenyl]hafnium	0
0233	ex2931 00 95 60	Trioctylphosphine oxide	0
0234	ex2931 00 95 65	Triethylborane	0
0235	ex2932 11 00 10	Tetrahydrofuran, containing not more than 40 mg per litre in total of tetrahydro-2-methylfuran and tetrahydro-3-methylfuran, for the manufacture of α -4-hydroxybutyl- ω -hydroxypoly(oxytetramethylene) (a)	0
0236	ex2932 13 00 10	Tetrahydrofurfuryl alcohol	0
0237	ex2932 19 00 40	Furan of a purity by weight of 99 % or more	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0238	ex2932 19 00 50	2,3-Dihydrofuran	0
0239	ex2932 29 80 10	2'-Anilino-6'-[ethyl(isopentyl)amino]-3'-methylspiro[isobenzofuran=1(3H),9'-xanthen]-3-one	0
0240	ex2932 29 80 15	13,14,15,16-Tetranorlabdano-12,8 α -lactone	0
0241	ex2932 29 80 25	2'-(2-Chloroanilino)-6'-dibutylaminospiro[isobenzofuran=1(3H),9'-xanthen]-3-one	0
0242	ex2932 29 80 30	2'-Anilino-3'-methyl-6'-methyl(propyl)aminospiro[isobenzofuran=1(3H),9'-xanthen]-3-one	0
0243	ex2932 29 80 35	6'-Diethylamino-3'-methyl-2'-(2,4-xylidino)spiro[isobenzofuran=1(3H),9'-xanthen]-3-one	0
0244	ex2932 29 80 40	2'-Anilino-6'-(N-ethyl-p-toluidino)-3'-methylspiro[isobenzofuran=1(3H),9'-xanthen]-3-one	0
0245	ex2932 29 80 45	2'-Anilino-6'-ethyl(isobutyl)amino-3'-methylspiro[isobenzofuran=1(3H),9'-xanthen]-3-one	0
0246	ex2932 29 80 50	2'-Anilino-6'-cyclohexyl(methyl)amino-3'-methylspiro[isobenzofuran=1(3H),9'-xanthen]-3-one	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0247	ex2932 29 80 55	6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide	0
0248	ex2932 99 70 10	Bendiocarb (ISO)	0
0249	ex2932 99 70 20	Androsta-1,4-diene-3,17-dione 17-(2,2-dimethylpropylene) acetal	0
0250	ex2933 21 00 10	Hydantoin	0
0251	ex2933 21 00 20	2-(3-Benzyl-2,5-dioxoimidazolidin-1-yl)-2'-chloro-5'-(3-dodecyl= sulfonyl-2-methylpropionamido)-4,4-dimethyl-3-oxovaleranilide	0
0252	ex2933 21 00 30	3'-[4,4-Dimethyl-2-(4,4-dimethyl-2,5-dioxoimidazolin-1-yl)= oxovalerylamino]-4'-methoxystearanilide	-3- 0
0253	ex2933 21 00 40	1-[1,3-Bis(hydroxymethyl)-2,5-dioxoimidazolidin-4-yl]= bis(hydroxymethyl)urea	-1,3- 0
0254	ex2933 29 90 20	Reaction product consisting of the methyl esters of (±)-6-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)- <i>m</i> -toluic acid and (±)-2-(4-isopropyl-4-methyl-5-oxo-2-imidazolin-2-yl)- <i>p</i> -toluic acid (Imazamethabenz-methyl)	4
0255	ex2933 29 90 40	Triflumizole (ISO)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0256	ex2933 39 95 10	Cloperastine fendizoate (INN ^M)	0
0257	ex2933 39 95 15	Pyridine-2,3-dicarboxylic acid	0
0258	ex2933 39 95 20	5-Methyl-2-pyridylamine	0
0259	ex2933 39 95 25	Imazethapyr (ISO)	0
0260	ex2933 39 95 30	4,4'-Trimethylenedipiperidine	0
0262	ex2933 40 10 10	Quinmerac (ISO)	0
0263	ex2933 40 90 20	5,7-Dichloro-4-(4-fluorophenoxy)quinoline	0
0265	ex2933 40 90 40	<i>N</i> -Ethyl-5,6,7,8-tetrahydroquinolinium <i>p</i> -toluenesulfonate, in the form of a solution in water	0
0267	ex2933 59 70 10	1-Ethyl-6-fluoro-1,4-dihydro-4-oxo-7-piperazin-1-yl-1,8-naphthyridine-3-carboxylic acid and its salts and esters	0
0268	ex2933 59 70 20	2,4-Diamino-6-chloropyrimidine	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0266	ex2933 59 70 30	Mepanipirim (ISO)	0
0269	ex2933 69 80 10	1,3,5-Tris(4- <i>tert</i> -butyl-3-hydroxy-2,6-dimethylbenzyl)-1,3,5-triazine= 2,4,6(1 <i>H</i> ,3 <i>H</i> ,5 <i>H</i>)-trione	0
0270	ex2933 69 80 20	1,3,5-Tris[(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)methyl]-1,3,5-triazine= 2,4,6(1 <i>H</i> ,3 <i>H</i> ,5 <i>H</i>)-trione	0
0271	ex2933 69 80 40	Cyanazine (ISO)	0
0272	ex2933 90 50 10	Azepane, for the manufacture of goods of subheading 3808 30 (a)	0
0273	ex2933 90 95 10	2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-di- <i>tert</i> -butylphenol	0
0274	ex2933 90 95 15	2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-di- <i>tert</i> -pentylphenol	0
0275	ex2933 90 95 20	2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol	0
0276	ex2933 90 95 25	6,6'-Di-2 <i>H</i> -benzotriazol-2-yl-4,4'-bis(1,1,3,3-tetramethylbutyl)= methylenediphenol	0
0277	ex2933 90 95 30	Quizalofop-P-ethyl (ISO)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0278	ex2933 90 95 35	Indoline	0
0279	ex2933 90 95 45	Maleic hydrazide (ISO)	0
0280	ex2933 90 95 50	Metconazole (ISO)	3.2
0281	ex2933 90 95 55	5-Nitroindole	0
0282	ex2933 90 95 60	1,3-Bis(3-isocyanatomethylphenyl)-1,3-diazetidone-2,4-dione (dimeric 2,4-toluene diisocyanate)	0
0283	ex2933 90 95 65	Candesartan cilexetil (INNM)	0
0284	ex2934 10 00 10	Hexythiazox (ISO)	0
0285	ex2934 10 00 20	2-(4-Methylthiazol-5-yl)ethanol	0
0286	ex2934 20 80 10	4-Chloro-1,3-benzothiazol-2(3H)-one	0
0287	ex2934 90 96 10	7-Chloro-5-methyl-2H-1,4-benzothiazin-3-(4H)-one	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0288	ex2934 90 96 15	Carboxin (ISO)	0
0289	ex2934 90 96 20	4-[4-(Tridecyl[branched]oxy)phenyl]-1,4-thiazinane 1,1-dioxide	0
0290	ex2934 90 96 25	Oxycarboxin (ISO)	0
0291	ex2934 90 96 30	Etridiazole (ISO)	0
0292	ex2934 90 96 35	Dimethenamide (ISO)	0
0293	ex2934 90 96 40	2,3,5,6-Tetrahydroxy-1,4-diisobutyl-1,4-dioxo-1,4-diphosphinane	0
0294	ex2934 90 96 45	Tris(2,3-epoxypropyl)-1,3,5-triazinetrione	0
0295	ex2934 90 96 50	1-[2-(1,3-Dioxan-2-yl)ethyl]-2-ethylpyridinium bromide	0
0296	ex2934 90 96 55	Naphth[1,2- <i>d</i>][1,2,3]oxadiazole-5-sulfonic acid	0
0438	ex2934 90 96 60 ex3824 90 95 41	7-Nitronaphth[1,2- <i>d</i>][1,2,3]oxadiazole-5-sulfonic acid of a purity by weight of 60 % or more	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0297	ex2935 00 90 10	Salts of sulfathiazole (INN)	0
0298	ex2935 00 90 20	Toluenesulfonamides	0
0299	ex2935 00 90 30	Mixture of isomers consisting of <i>N</i> -ethyltoluene-2-sulfonamide and <i>N</i> -ethyltoluene-4-sulfonamide	0
0300	ex2935 00 90 40	1-(4,6-Dimethoxypyrimidin-2-yl)-3-(2-ethylsulfonylimidazo[1,2-a]pyridin-3-ylsulfonyl)urea (sulfosulfuron)	0
0301	ex2935 00 90 50	4,4'-Oxydi(benzenesulfonylhydrazide)	0
0302	ex2935 00 90 60	5-Amino- <i>N</i> -(2,6-dichloro- <i>m</i> -tolyl)-1 <i>H</i> -1,2,4-triazole-3-sulfonamide	0
0303	ex2935 00 90 70	Methyl 3-aminosulfonylthiophene-2-carboxylate	0
0304	3201 20 00	Wattle extract	0
0305	ex3201 90 90 10	Tanning extracts of eucalyptus	3.2
0306	ex3201 90 90 20	Tanning extracts derived from gambier and myrobalan fruits	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0307	ex3204 15 00 10	Dye C.I. Vat Orange 7	0
0308	ex3204 15 00 20	Dye C.I. Vat Red 15	0
0309	ex3204 15 00 30	Dye C.I. Vat Red 14	0
0310	ex3204 15 00 40	Dye C.I. Vat Brown 57	0
0311	ex3204 17 00 10	Dye C.I. Pigment Yellow 81	0
0312	ex3204 19 00 10	Nickel bis{4-methoxy-2-[6-(pentafluoroethylthio)benzothiazol-2-ylazo]= 5-(dipropylamino)benzenesulfonate}	0
0313	ex3204 19 00 20	13-Ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo= [h]indeno[2,1-f]chromen-13-ol	0
0314	ex3204 19 00 30	13-Isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo= [h]indeno[2,1-f]chromen-13-ol	0
0315	ex3204 19 00 40	Methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1 <i>H</i> -indole= 2,3'-naphtho[2,1- <i>b</i>][1,4]oxazine]-9'-carboxylate	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0316	ex3204 19 00 50	Methyl 6-(isobutyryloxy)-2,2-diphenyl-2 <i>H</i> -benzo[<i>h</i>]chromene-5-carboxylate	0
0317	ex3204 19 00 60	Ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2 <i>H</i> -benzo[<i>h</i>]chromene-5-carboxylate	0
0318	ex3206 42 00 10	Lithopone	0
0319	ex3206 49 90 10	Black preparation of iron-oxide pigments, in liquid form, with a maximum particle size not exceeding 20 nanometres and containing by weight 25 % or more of iron evaluated as Fe ₂ O ₃ , for the manufacture of goods of heading No 3304 or 9608 (a)	0
0320	ex3208 20 10 10	Copolymer of <i>N</i> -vinylcaprolactam, <i>N</i> -vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer	0
0321	ex3208 20 10 20 ex3905 91 00 92	Copolymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, partially quaternized by diethyl sulfate, in the form of a solution in ethanol	0
0322	ex3208 20 10 30	Solution of diundecyl phthalate and a copolymer of dibutyl maleate and isobutyl methacrylate in a hydrocarbon solvent	0
0323	ex3208 90 19 10 ex3911 90 99 35	Copolymer of maleic acid and methyl vinyl ether, monoesterified with ethyl and/or isopropyl and/or butyl groups, in the form of a solution in ethanol, ethanol and butanol, isopropanol or isopropanol and butanol	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0324	ex3208 90 19 20	Copolymer of polyurethane and silicone, in the form of a solution in a mixture of butanone, toluene and cyclohexanone, containing by weight 13 % or more but not more than 16 % of copolymer	0
0529	ex3208 90 19 30	Solution containing: <ul style="list-style-type: none"> - (30 ± 5) % by weight of polyamide resin, - (6,5 ± 3,5) % by weight of diazonaphthoquinone, - (55 ± 5) % by weight of 1-methyl-2-pyrrolidone, - 1 000 µg/kg or less of chloride, - 1 000 µg/kg or less of potassium and - 1 000 µg/kg or less of iron 	0
0325	ex3208 90 99 10	Solution based on chemically modified natural polymers, containing two or more of the following dyes: <ul style="list-style-type: none"> - methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1<i>H</i>-indole= -2,3'-naphtho[2,1-<i>b</i>][1,4]oxazine]-9'-carboxylate, - methyl 6-(isobutyryloxy)-2,2-diphenyl-2<i>H</i>-benzo[<i>h</i>]chromene= -5-carboxylate, - 13-isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo= [i>h]indeno[2,1-<i>f</i>]chromen-13-ol, - ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2<i>H</i>-benzo[<i>h</i>]chromene-5-carboxylate, - 13-ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo= [i>h]indeno[2,1-<i>f</i>]chromen-13-ol 	0
0326	ex3215 90 80 10	Ink formulation, for use in the manufacture of ink-jet cartridges (a)	0
0327	3301 12 10	Essential oil of orange, not deterpenated	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0328	ex3402 90 10 20	Mixture of docusate sodium (INN) and sodium benzoate	0
0329	ex3402 90 10 30	Non-aqueous surface-active preparation, containing: <ul style="list-style-type: none"> - polyethylene glycol alkylphenyl ether, - 2,4,7,9-tetramethyldec-5-yne-4,7-diol and - phosphoric acid esters 	0
0330	ex3402 90 90 10	Crystalline powder obtained by the reaction of trisodium phosphate with a mixture of sodium hypochlorite and sodium chloride ("chlorinated trisodium phosphate"), containing by weight: <ul style="list-style-type: none"> - 3,5 % or more of available chlorine, measured iodometrically and - 17,0 % or more of phosphorus evaluated as P₂O₅ 	0
0331	ex3403 99 90 10	Cutting-fluid preparation based on an aqueous solution of synthetic polypeptides	0
0332	ex3504 00 00 10	Purified antigens obtained from genetically manipulated yeast cells, for the manufacture of detection tests for hepatitis-C (a)	0
0333	ex3504 00 00 20	Glycoprotein 160 obtained from Human Immunodeficiency Virus, HIV-1 strain	0
0334	ex3505 10 50 20	O-(2-Hydroxyethyl)-derivative of hydrolysed waxy maize starch	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0335	ex3506 91 00 10	Adhesive based on an aqueous dispersion of a mixture of dimerised rosin and a copolymer of ethylene and vinyl acetate (EVA)	0
0336	ex3506 91 00 20	Heat-activated adhesive based on phenolic resin and rubber, in the form of a film on a release paper, for use in the manufacture of brake pads for the automotive industry (a)	0
0337	ex3507 90 90 10	Asparaginase	0
0338	ex3507 90 90 20	Enzymatic preparation based on thermolysine	0
0339	ex3507 90 90 40	Avian myeloblastosis virus (AMV) reverse transcriptase	0
0340	ex3701 30 00 10	Letterpress printing plates, consisting of a metal substrate covered with a photopolymer layer, of a total thickness of 0,5 mm or more but not exceeding 0,8 mm	0
0341	ex3701 99 00 10	Plate of quartz or of glass, covered with a film of chromium and coated with a photosensitive or electron-sensitive resin, for the manufacture of masks for the goods of heading No 8541 or 8542 (a)	0
0342	ex3702 31 99 10	Colour negative film, for the manufacture of instant-picture film-packs (a)	0
0343	ex3702 43 00 10 ex3702 44 00 10	Photographic film, of a nominal width of 459, 669 or 761 mm, composed of several layers, including two polyester films, a carbon layer, an adhesive layer and a layer of a copolymer of styrene with acrylonitrile	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0344	ex3703 90 10 10	Paper sheet, coated with silver halide emulsion, for the manufacture of goods of subheading 3701 20 00 (a)	0
0345	ex3707 10 00 10	Photosensitive emulsion for the sensitization of silicon discs (a)	0
0346	ex3707 90 30 10	Toner, in the form of powder, consisting of a copolymer of styrene and butyl acrylate and magnetite, for use as a developer in the manufacture of cartridges for facsimile machines (a)	0
0347	3805 20 00	Pine oil	1.7
0348	ex3808 20 80 10	Fungicide in the form of a powder, containing by weight 65 % or more but not more than 75 % of hymexazole (ISO), not put up for retail sale	0
0211b	ex3808 20 80 20	Preparation based on diiodomethyl <i>p</i> -tolyl sulfone, not put up for retail sale	0
0349	ex3808 40 20 10	Preparation containing by weight: <ul style="list-style-type: none"> - 58 % or more but not more than 62 % of 1-bromo-3-chloro-5,5-dimethylhydantoin, - 26 % or more but not more than 29 % of 1,3-dichloro-5,5-dimethylhydantoin, - 10 % or more but not more than 12 % of 1,3-dichloro-5-ethyl-5-methylhydantoin, for the manufacture of swimming-pool disinfectants (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0350	ex3808 40 90 10	1-Dodecylguanidine hydrochloride, in the form of a solution in isopropanol and water, containing by weight 40 % or less of 1-dodecylguanidine hydrochloride	0
0351	ex3809 91 00 10	Mixture of 5-ethyl-2-methyl-2-oxo-1,3,2λ ⁵ -dioxaphosporan-5-ylmethyl methyl methylphosphonate and bis(5-ethyl-2-methyl-2-oxo-1,3,2λ ⁵ -dioxaphosporan-5-ylmethyl) methylphosphonate	0
0352	ex3809 92 00 10	Paper anti-fading agent, consisting of a mixture of magnesium trisilicate and monosodium salt of 2,2'-methylenebis(4,6-di- <i>tert</i> -butylphenyl) phosphate	0
0353	ex3811 21 00 10	Salts of dinonylnaphthalenesulfonic acid, in the form of a solution in mineral oils	0
0354	ex3812 30 80 10	Tetraaluminium nonamagnesium dicarbonate hexacosahydroxide heptahydrate, coated with a surface-active agent	0
0355	ex3812 30 80 20	Mixture containing predominantly bis(2,2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate	0
0356	ex3812 30 80 30	Compound stabilisers containing by weight 15 % or more but not more than 40 % of sodium perchlorate and not more than 70 % of 2-(2-methoxyethoxy)ethanol	0
0357	ex3812 30 80 40	Dialuminium tetramagnesium monocarbonate dodecahydroxide monohydrate, coated with a surface-active agent	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0358	ex3812 30 80 50	Aluminium magnesium zinc hydroxide carbonate hydrate, coated with a surface-active agent	0
0359	ex3814 00 90 10	Mixture containing by weight 25 % or more but not more than 35 % of dimethyl sulfoxide and 65 % or more but not more than 75 % of monoethanolamine	3
0360	ex3815 12 00 10	Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not exceeding 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 20 % of silver	0
0361	ex3815 12 00 20	Catalyst consisting of palladium and rhenium, fixed on a support of active carbon, in the form of powder, containing: <ul style="list-style-type: none"> - 0,5 % or more but not more than 1,5 % by weight of palladium, - 3 % or more but not more than 5 % by weight of rhenium and - 0,1 mole % or more but not more than 1 mole % of alkaline metals, <p>for use in the manufacture of tetrahydrofuran (a)</p>	0
0362	ex3815 19 90 10	Catalyst, consisting of chromium trioxide or dichromium trioxide fixed on a support of silicon dioxide, of a pore volume, as determined by the nitrogen absorption method, of 2 cm ³ /g or more	0
0363	ex3815 19 90 15	Catalyst, in the form of a powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, containing by weight 20 % or more but not more than 40 % of molybdenum, bismuth and iron evaluated together, for use in the manufacture of acrylonitrile (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0364	ex3815 19 90 20	Catalyst consisting of chromium oxides and titanium dioxide fixed on a support of silicon dioxide, aluminium oxide or aluminium phosphate	0
0365	ex3815 19 90 30	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene (a)	0
0366	ex3815 19 90 40	Catalyst, in the form of spheres of a diameter of 4,2 mm or more but not exceeding 9 mm, consisting of a mixture of metals oxides containing predominantly oxides of molybdenum, vanadium and copper, on a support of silicon dioxide and/or aluminium oxide, for use in the manufacture of acrylic acid (a)	0
0367	ex3815 19 90 45	Catalyst, consisting predominantly of dichromium copper tetraoxide and copper (II) oxide, containing by weight 38 % or more but not more than 48 % of copper, evaluated as copper (II) oxide, fixed on a support of silicon dioxide, for the hydrogenation of acetophenones (a)	0
0368	ex3815 19 90 50	Catalyst consisting of organo-metallic compounds of titanium, magnesium and aluminium on a support of silicon dioxide, in the form of a suspension in tetrahydrofuran	0
0369	ex3815 19 90 55	Catalyst consisting of a mixture of metal oxides containing chromium trioxide, fixed on a support of silicon dioxide	0
0370	ex3815 19 90 60	Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide	0
0371	ex3815 19 90 65	Catalyst consisting of phosphoric acid chemically bonded to a support of silicon dioxide	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0372	ex3815 19 90 70	Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide	0
0373	ex3815 19 90 75	Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide	0
0374	ex3815 19 90 80	Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil	0
0375	ex3815 19 90 85	Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder	0
0376	ex3815 90 90 15	Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, vanadium, nickel and antimony, whether or not mixed with porcelain balls, for use in the manufacture of acrylic acid (a)	0
0377	ex3815 90 90 20	Catalyst, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing by weight: <ul style="list-style-type: none"> - 20 % or more but not more than 30 % of titanium and - 55 % or more but not more than 72 % of chlorine 	0
0378	ex3815 90 90 25	Catalyst, consisting of a mixture of oxides containing by weight more than 96 % of oxides of molybdenum, bismuth, nickel, iron and silicon, whether or not mixed with porcelain balls, for use in the manufacture of acrylaldehyde (a)	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0379	ex3815 90 90 30 Catalyst, in the form of a powder, containing by weight 82 % or more of copper and of a specific surface of 0,5 m ² /g or more but not exceeding 8 m ² /g	0
0380	ex3815 90 90 35 Catalyst, in the form of a suspension in oil, consisting of titanium trichloride and aluminium trichloride, containing by weight (on an oil-free basis): - 15 % or more but not more than 30 % of titanium and - 40 % or more but not more than 72 % of chlorine	0
0381	ex3815 90 90 40 Catalyst, in the form of rodlets of a length of 5 mm or more but not exceeding 8 mm, consisting of a mixture of metals oxides containing predominantly oxides of iron, molybdenum and bismuth, whether or not containing silicon dioxide as filler, for use in the manufacture of acrylic acid (a)	0
0382	ex3815 90 90 50 Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium	0
0383	ex3815 90 90 55 Reaction initiator, consisting of a mixture of <i>N,N,N',N'</i> -tetramethyl-2,2'-oxybis(ethylamine) and dipropylene glycols	0
0384	ex3815 90 90 60 Catalyst, in the form of rodlets, consisting of an acid aluminosilicate (zeolite): - with a mole-ratio of silicon dioxide : dialuminium trioxide of not less than 500 : 1 and - containing by weight 0,2 % or more but not more than 0,8 % of platinum	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0385	ex3815 90 90 65	Catalyst based on a mordenite zeolite, in the form of granules, for use in the manufacture of mixtures of methylamines containing by weight 50 % or more of dimethylamine (a)	0
0386	ex3815 90 90 70	Catalyst, consisting of a mixture of (2-hydroxypropyl)trimethylammonium formate and dipropylene glycols	0
0387	ex3815 90 90 75	Catalyst, consisting of a mixture of 1,4-diazabicyclo[2.2.2]octane, 2-hydroxyethyliminodi(acetic acid) and dibutyltin di(acetate), containing by weight 5 % or more but not more than 10 % of 1,4-diazabicyclo[2.2.2]octane	0
0388	ex3815 90 90 80	Catalyst consisting predominantly of dinonylnaphthalenedisulfonic acid in the form of a solution in isobutanol	0
0389	ex3815 90 90 81	Catalyst, containing by weight 38 % or more but not more than 48 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate	0
0390	ex3815 90 90 82	Catalyst, containing by weight 35 % or more but not more than 55 % of (2-hydroxy-1-methylethyl)trimethylammonium formate and formic acid	0
0391	ex3815 90 90 83	Catalyst, in the form of powder, containing aluminium magnesium hydroxide hydrate, rare-earth metals oxides and divanadium pentaoxide	0
0392	ex3815 90 90 85	Catalyst based on aluminosilicate (zeolite), for the transalkylation of alkylaromatic hydrocarbons or the oligomerization of olefins (a)	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0397	ex3823 19 10 91	Mixture of fatty acids containing by weight: <ul style="list-style-type: none"> - 2 % or more but not more than 6 % of hexanoic acid, - 53 % or more but not more than 60 % of octanoic acid, - 34 % or more but not more than 42 % of decanoic acid and - not more than 2 % of dodecanoic acid 	0
0398	ex3824 90 15 10	Acid aluminosilicate (artificial zeolite of the Y type) in the sodium form, containing by weight not more than 11 % of sodium evaluated as sodium oxide, in the form of rodlets	0
0399	ex3824 90 64 01	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Micromonospora purpurea</i> , whether or not dried	0
0400	ex3824 90 64 02	Cholic acid and 3 α ,12 α -dihydroxy-5 β -cholan-24-oic acid (deoxycholic acid), crude	0
0401	ex3824 90 64 03	Products obtained by the N-ethylation of sisomycin (INN)	0
0402	ex3824 90 64 04	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of <i>Micromonospora inyoensis</i> , whether or not dried	0
0403	ex3824 90 64 05	Residues of manufacture containing by weight 40 % or more of 11 β ,17,20,21-tetrahydroxy-6-methylpregna-1,4-dien-3-one 21-acetate	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0407	ex3824 90 95 01	Colloidal diantimony pentaoxide	0
0408	ex3824 90 95 02	Mixture of nitromethane and 1,2-epoxybutane	0
0409	ex3824 90 95 03	Grains or granules, consisting of a mixture of dialuminium trioxide and zirconium dioxide, containing by weight: <ul style="list-style-type: none"> - 70 % or more but not more than 78 % of dialuminium trioxide and - 19 % or more but not more than 26 % of zirconium dioxide 	5.2
0410	ex3824 90 95 04	Crude lithium hypochlorite	0
0411	ex3824 90 95 06	Preparation, in the form of powder, containing by weight 75 % or more of zinc bis[3,5-bis(1-phenylethyl)salicylate]	0
0412	ex3824 90 95 07	Film consisting of the oxides of either barium or calcium and either titanium or zirconium, mixed with binding materials	0
0413	ex3824 90 95 08	Preparation consisting essentially of alkaline asphalt sulfonate, of: <ul style="list-style-type: none"> - a specific gravity of 0,9 or more but not exceeding 1,5 and - a solubility in water of 70 % by weight or more 	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0414 ex3824 90 95 09	Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulfonic acid, either: <ul style="list-style-type: none"> - on a support of mineral wax, whether or not modified chemically, or - in the form of a solution in an organic solvent 	0
0415 ex3824 90 95 10	Calcined bauxite (refractory grade)	0
0416 ex3824 90 95 11	Magnetisable iron oxide, in the form of powder, containing by weight: <ul style="list-style-type: none"> - 30 % or more but not more than 38 % of bivalent iron in relation to the total iron and - 1 % or more but not more than 4 % of cobalt 	0
0417 ex3824 90 95 12	Spent catalyst, in the form of rodlets of diameter of 1 mm or more but not exceeding 3 mm, containing a mixture of sulfides of tungsten and of nickel on a support of zeolite, containing by weight not more than 10 % of tungsten and not more than 10 % of nickel, for regeneration as a catalyst for hydrocarbon cracking (a)	0
0418 ex3824 90 95 13	Mixture containing by weight: <ul style="list-style-type: none"> - 7 % or more but not more than 9 % of 2-methyl-1,3-phenylene diisocyanate, - 31 % or more but not more than 34 % of 4-methyl-1,3-phenylene diisocyanate, - 10 % or more but not more than 13 % of 2,4'-methylenediphenyl diisocyanate, - 46 % or more but not more than 49 % of 4,4'-methylenediphenyl diisocyanate 	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0419	ex3824 90 95 14	Mixture of magnesium bromide 2-oxoperhydroazepin-1-ide and ϵ -caprolactam	0
0420	ex3824 90 95 15	Mixture of disodium <i>N</i> -benzyloxycarbonyl-L-aspartate and sodium chloride, in the form of a solution in water	0
0421	ex3824 90 95 16	Disodium 9,10-dihydro-9,10-dioxoanthracene-2,7-disulfonate, containing by weight 10 % or more but not more than 20 % of sodium sulfate	0
0422	ex3824 90 95 17	Eutectic alloy wholly of potassium and sodium, containing by weight 77 % or more but not more than 79 % of potassium	0
0423	ex3824 90 95 18	Blend of terephthaloyl dichloride and isophthaloyl dichloride	0
0424	ex3824 90 95 20	Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing by weight 7 % or more of tricyclopentadiene, and: <ul style="list-style-type: none"> - either an aluminium-alkyl compound, - or an organic complex of tungsten - or an organic complex of molybdenum 	0
0425	ex3824 90 95 21	Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of methylphosphonic acid and phosphoric acid with ethane-1,2-diol	0
0426	ex3824 90 95 22	Mixture of tris[2-chloro-1-(chloromethyl)ethyl] phosphate and oligomers of 2-chloroethyl phosphate with ethane-1,2-diol	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0427	ex3824 90 95 23	Mixture of sucrose esters, derived from the esterification of sucrose with industrial stearic acid	0
0428	ex3824 90 95 24	Preparations consisting predominantly of phosphabicyclononanes and <i>P</i> -alkyl derivatives thereof, in the form of a solution in 4- <i>tert</i> -butyltoluene	0
0429	ex3824 90 95 25	Lithium tantalate wafers, undoped	0
0430	ex3824 90 95 28	Preparation consisting predominantly of ethylene glycol and <i>N,N</i> -dimethylformamide or ethylene glycol and γ -butyrolactone, for the manufacture of electrolytic capacitors (a)	0
0431	ex3824 90 95 29	Preparation consisting predominantly of γ -butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors (a)	0
0432	ex3824 90 95 30	2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated	0
0433	ex3824 90 95 31	Copper zinc ferrite, coated with a silicone resin, in the form of granules of a size not exceeding 120 μm	0
0434	ex3824 90 95 32	Styrene oligomer	0
0435	ex3824 90 95 33	Preparation consisting of α -(4-allyloxycarbonylbenzoyl)- ω -allyloxypoly=[oxy(2-methylethylene)oxyterephthaloyl] and either diallyl-2,2'-oxydiethyl dicarbonate or diallyl isophthalate	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0436	ex3824 90 95 39	Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid	0
0437	ex3824 90 95 40	Azelaic acid of a purity by weight of 75 % or more but not exceeding 85 %	0
0439	ex3824 90 95 42	<p>Mixed metals oxides, in the form of powder, containing by weight:</p> <ul style="list-style-type: none"> - either 5 % or more of barium, neodymium or magnesium and 15 % or more of titanium, - or 30 % or more of lead and 5 % or more of niobium, <p>for use in the manufacture of dielectric films or for use as dielectric materials in the manufacture of multilayer ceramic capacitors (a)</p>	0
0440	ex3824 90 95 43	7-Aminonaphthalene-1,3,6-trisulfonic acid and its salts, of a purity by weight of 65 % or more	0
0441	ex3824 90 95 44	<p>Mixture containing by weight:</p> <ul style="list-style-type: none"> - 60 % or more of 2-[N-(2-cyanoethyl)anilino]ethyl acetate and - 20 % or more of acetic acid 	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0442	ex3824 90 95 45	Preparations consisting predominantly of ethylene glycol and: <ul style="list-style-type: none"> - either diethylene glycol, dodecandioic acid and ammonia water, - or silicon oxide, - or ammonium hydrogen azelate, - or ammonium hydrogen azelate and silicon oxide, - or dodecandioic acid, ammonia water and silicon oxide, for the manufacture of electrolytic capacitors (a)	0
0443	ex3824 90 95 46	Carboxylic acid anhydride based hardener for epoxyde resin, in liquid form, of a specific weight at 25 °C of 1,15 g/cm ³ or more but not exceeding 1,18 g/cm ³	0
0444	ex3824 90 95 49	Mixed oxides of metals, in the form of powder, containing by weight: <ul style="list-style-type: none"> - 70 % or more but not more than 75 % of iron oxide, - 10 % or more but not more than 20 % of zinc oxide, - 10 % or more but not more than 15 % of magnesium oxide, - 1 % or more but not more than 5 % of manganese oxide and - 1 % or more but not more than 3 % of copper oxide 	0
0445	ex3824 90 95 50	Zeolites consisting of oxides of barium, aluminium and silicon, containing by weight 30 % or more but not more than 40 % of barium oxide, in the form of spheres of which 80 % or more by weight have a diameter of 0,3 mm or more but not more than 1,2 mm	0
0446	ex3824 90 95 53	Sodium 4-hydroxynaphthalene-1-sulfonate, of a purity by weight of 70 % or more but not exceeding 80 %	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0447	ex3824 90 95 54	2-Hydroxybenzotrile, in the form of a solution in <i>N,N</i> -dimethylformamide, containing by weight 45 % or more but not more than 50 % of 2-hydroxybenzotrile	0
0448	ex3824 90 95 55	Mixture containing by weight 75 % or more of pentaerythritol triallyl ether	0
0449	ex3824 90 95 57	Mixture of trialkylphosphine oxides	0
0450	ex3824 90 95 58	Platinum oxide fixed on a porous support of aluminium oxide, containing by weight 0,1 % or more but not more than 1 % of platinum and 0,5 % or more but not more than 5 % of ethylaluminium dichloride	0
0451	ex3824 90 95 60	α -Phenoxy-carbonyl- ω -phenoxy-poly[oxy(2,6-dibromo-1,4-phenylene)=isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]	0
0452	ex3824 90 95 61	<p>Mixture of metal oxides, in the form of powder, containing by weight:</p> <ul style="list-style-type: none"> - 20 % or more of barium, - 10 % or more of titanium and - 4 % or more of lead or 3 % or more of niobium or 0,7 % or more of zirconium, <p>for use as dielectric material in the manufacture of multilayer ceramic capacitors (a)</p>	0
0453	ex3824 90 95 63	Triethylborane, in the form of a solution in tetrahydrofuran	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0454 ex3824 90 95 64	Aluminium sodium silicate, in the form of spheres of a diameter of: – either 1,6 mm or more but not exceeding 3,4 mm, – or 4 mm or more but not exceeding 6 mm	0
0455 ex3824 90 95 65	Mixture of tris(alkoxycarbonylamino)-1,3,5-triazines in which alkoxy groups are methoxy and butoxy	0
0456 ex3824 90 95 66	Mixture of primary <i>tert</i> -alkylamines	0
0457 ex3824 90 95 67	Preparation consisting of indium tin oxide dispersed in organic solvents	0
0404 ex3824 90 95 72	Solution containing by weight 80 % or more of 2,4,6-trimethylbenzaldehyde in acetone	0
0406 ex3824 90 95 73	Particles of silicon dioxide on which are covalently bonded organic compounds, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges (a)	0
0459 ex3901 10 10 10	Linear polyethylene, of a specific gravity of 0,928 or more but not exceeding 0,935 and of a melt flow index of less than 0,6 g/min, for the manufacture of shrinkmelt binder fibres (a)	0
0460 ex3901 10 90 10	Polyethylene for the manufacture of photo-resist film for semiconductors or printed circuits (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0461	ex3901 10 90 20	Polyethylene, in the form of granules, of a specific gravity of 0,925 ($\pm 0,0015$), a melt flow index of 0,3 g/10 min ($\pm 0,05$ g/10 min), for the manufacture of blown films of a Haze value not exceeding 6 % and an elongation at break (MD/TD) of 210/340 (a)	0
0462	ex3901 20 90 10	Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, of a specific gravity of 0,945 or more but not exceeding 0,985, for the manufacture of films for typewriter ribbon or similar ribbon (a)	0
0463	ex3901 20 90 20	Polyethylene, containing by weight 35 % or more but not more than 45 % of mica	0
0464	ex3901 90 90 91	Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid	4
0465	ex3901 90 90 93	Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticizer in the manufacture of roof sheets (a)	0
0466	ex3901 90 90 94	Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene	0
0467	ex3901 90 90 95 ex3902 90 90 95	Copolymer of ethylene and butylene, having hydroxyl or acrylate end-groups, containing by weight 40 % or more but not more than 60 % of butylene	0
0468	ex3901 90 90 96 ex3902 90 90 96 ex3903 90 90 50	Linear A-B block copolymer of polyisoprene, whether or not epoxidized, and either ethylene-butylene copolymer or styrene-ethylene-butylene copolymer, having hydroxyl end-groups	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0470	ex3902 10 00 10	Polypropylene containing no plasticizer and not more than: <ul style="list-style-type: none"> - 7 mg/kg of aluminium, - 2 mg/kg of iron, - 1 mg/kg of magnesium, - 8 mg/kg of chloride 	0
0471	ex3902 10 00 20	Polypropylene, containing no plasticiser, <ul style="list-style-type: none"> - of a melting point of more than 150 °C (as determined by the ASTM D 3417 method), - of a heat of fusion of 15 J/g or more but not exceeding 70 J/g, - of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method), - of a tensile modulus of 69 MPa or more but not exceeding 379 MPa (as determined by the ASTM D 638 method) 	0
0469	ex3902 10 00 30	Polypropylene, containing not more than 1 mg/kg of aluminium, 0,05 mg/kg of iron, 1 mg/kg of magnesium and 1 mg/kg of chloride, for use in the manufacture of packaging for disposable contact lenses (a)	0
0473	ex3902 30 00 91 ex3903 90 90 25	A-B Block copolymer of polystyrene and an ethylene-propylene copolymer, containing by weight 40 % or less of styrene, in one of the forms mentioned in note 6 (b) to Chapter 39	0
0474	ex3902 30 00 92	Copolymer of propylene, butylene and ethylene, containing by weight more than 65 % but less than 80 % of propylene and not less than 20 % of butylene	0
0476	ex3902 90 90 92	Polymers of 4-methylpent-1-ene	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0475	ex3902 90 90 97	Hydrogenated polyisobutene, in liquid form	0
0477	ex3903 19 00 20	Polystyrene of a molecular weight (M_n) not exceeding 5 000	0
0478	ex3903 90 90 10	Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, whether or not containing a styrene-butadiene block copolymer, in one of the forms mentioned in note 6 (b) to Chapter 39, for the manufacture of sheetings for head-liners for cars (a)	0
0479	ex3903 90 90 15	Copolymer, entirely of styrene with maleic anhydride, or entirely of styrene with maleic anhydride and an acrylic monomer, also partially esterified, of an average molecular weight (M_n) not exceeding 3 000, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39	0
0480	ex3903 90 90 20	Copolymer of styrene with 2-ethylhexyl acrylate or with <i>n</i> -butyl acrylate, containing: <ul style="list-style-type: none"> - 10 mole % or more but not more than 16 mole % of acrylate, - 0,2 mg/kg or less of sodium and - 0,1 mg/kg or less of calcium 	0
0481	ex3903 90 90 35 ex3911 90 99 30	Copolymer of α -methylstyrene and styrene, having a softening point exceeding 113 °C	0
0482	ex3903 90 90 40 ex3906 90 90 40 ex3911 90 99 50	Copolymer of styrene with α -methylstyrene and acrylic acid, of a molecular weight (M_n) of 500 or more but not exceeding 6 000	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0483 ex3903 90 90 55 ex3906 90 90 45	Copolymer of styrene, methyl methacrylate, butyl acrylate and either acrylic acid or hydroxyethyl methacrylate, of a molecular weight (M_n) of 500 or more but not exceeding 6 000	0
0484 ex3903 90 90 65	Copolymer of styrene, butyl acrylate, butyl methacrylate, methyl methacrylate and acrylic acid, in the form of powder, containing by weight (81 ± 1) % of styrene, (6 ± 1) % of butyl acrylate, (5 ± 1) % of butyl methacrylate, (7 ± 1) % of methyl methacrylate and (1 ± 0,5) % of acrylic acid	0
0485 ex3903 90 90 70	Ammonium polystyrenesulfonate, in the form of an aqueous solution	0
0486 ex3904 30 00 10	<p>Copolymer of vinyl chloride with vinyl acetate and maleic acid, containing by weight:</p> <ul style="list-style-type: none"> - 81,5 % or more but not more than 84,5 % of vinyl chloride, - 13,8 % or more but not more than 16,2 % of vinyl acetate and - 0,8 % or more but not more than 1,2 % of maleic acid, <p>for the manufacture of goods of heading No 3215 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a)</p>	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0487	ex3904 40 00 91	<p>Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight:</p> <ul style="list-style-type: none"> - 87 % or more but not more than 92 % of vinyl chloride, - 2 % or more but not more than 9 % of vinyl acetate and - 1 % or more but not more than 8 % of vinyl alcohol, <p>in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of goods of heading No 3215 or 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink (a)</p>	0
0488	ex3904 40 00 92	<p>Copolymer of vinyl chloride, vinyl acetate, hydroxypropyl acrylate and maleic acid, containing by weight 80 % or more but not more than 83 % of vinyl chloride, 1,6 % or more but not more than 2 % of hydroxy groups and 0,25 % or more but not more than 0,38 % of carboxyl groups</p>	0
0489	ex3904 50 90 91	<p>Copolymer of vinylidene chloride with vinyl chloride, containing by weight 79,5 % or more of vinylidene chloride, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of fibres, monofilament or strip (a)</p>	0
0490	ex3904 61 00 10	<p>Mixture of polytetrafluoroethylene and mica, in one of the forms mentioned in note 6 (b) to Chapter 39</p>	0
0491	ex3904 61 00 20	<p>Copolymer of tetrafluoroethylene and trifluoro(heptafluoropropoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(heptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions</p>	0
0492	ex3904 69 90 92	<p>Copolymer of tetrafluoroethylene and trifluoro(trifluoromethoxy)ethylene</p>	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0493	ex3904 69 90 93	Copolymer of ethylene with chlorotrifluoroethylene, in one of the forms mentioned in note 6 (b) to Chapter 39	0
0494	ex3904 69 90 94	Copolymer of ethylene and tetrafluoroethylene	0
0495	ex3904 69 90 96	Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39	0
0496	ex3905 91 00 91	Copolymer of <i>N</i> -vinylcaprolactam, <i>N</i> -vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate	0
0497	ex3905 91 00 93	Copolymer of ethylene and vinyl alcohol (EVOH)	0
0498	ex3905 99 90 93	Polyvinyl acetate phthalate	0
0499	ex3905 99 90 94	Polymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, containing by weight 97 % or more but not more than 99 % of vinylpyrrolidone, in the form of a solution in water	0
0500	ex3905 99 90 95	Hexadecylated or eicosylated polyvinylpyrrolidone	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0501	ex3905 99 90 96	<p>Poly(vinyl formal), in one of the forms mentioned in note 6 (b) to Chapter 39, of a molecular weight (M_w) of 25 000 or more but not exceeding 150 000 and containing by weight:</p> <ul style="list-style-type: none"> - 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl acetate and - 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol 	0
0502	ex3906 10 00 10	Polymethyl methacrylate, in the form of expansible beads containing 2-methylpentane as blowing agent	0
0503	3906 90 60	Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide	0
0504	ex3906 90 90 10	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading No 3003 or 3004 (a)	0
0505	ex3906 90 90 20	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for use as a stabilizer in emulsions or dispersions with a pH of more than 13 (a)	6
0506	ex3906 90 90 30	Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a molecular weight (M_n) of 500 or more but not exceeding 6 000	0
0507	ex3906 90 90 50	Acrylic polymers, containing by weight 2,5 % or more of chloroethyl vinyl ether or chloromethyl acrylate, in one of the forms mentioned in note 6 (b) to Chapter 39	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0508	ex3907 20 11 10	Poly(ethylene oxide) of an average molecular weight (M_n) of 100 000 or more	0
0509	ex3907 20 29 10	Polymer of dextrose, sorbitol and citric or phosphoric acid, containing by weight 90 % or more of dextrose monomer units	0
0510	ex3907 20 29 20	Poly[oxy-1,4-phenyleneisopropylidene-1,4-phenyleneoxy-(2-hydroxytrimethylene)], of an average molecular weight (M_w) of more than 26 000, in one of the forms mentioned in note 6 (b) to Chapter 39	0
0511	ex3907 20 99 10	Bis{2-[ω -hydroxy-poly(ethyleneoxy)]ethyl} hydroxymethylphosphonate	0
0512	ex3907 20 99 15	Poly(oxypropylene) having alkoxyethyl end-groups	0
0513	ex3907 20 99 25	α -4-Hydroxybutyl- ω -hydroxypoly(oxytetramethylene), containing less than 1 mg/kg of halogen and less than 1 mg/kg of metal, and of a colour not exceeding 20 units on the Hazen scale	0
0514	ex3907 20 99 30	Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin)	0
0515	ex3907 30 00 20	Epoxyde resin in the form of powder, containing by weight 44 % or more but not more than 55 % of quartz and 0,5 % or more but not more than 1 % of diantimony trioxide, for the coating of film capacitors (a)	0
0516	ex3907 30 00 30	Epoxyde resin, without solvent, containing mineral fillers (silica), without glass fibre, of a specific weight at 25 °C of 1,55 g/cm ³ or more but not exceeding 1,60 g/cm ³	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0517	ex3907 30 00 40	Epoxyde resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of heading No 8533, 8535, 8536, 8541, 8542 or 8548 (a)	0
0518	ex3907 40 00 10	Copolymer of hexane-1,6-diol, cyclohexane-1,4-dimethanol and ethylene carbonate	0
0519	ex3907 91 90 10	Diallyl phthalate prepolymer, in the form of powder	0
0520	ex3907 99 19 10 ex3907 99 99 10	Poly(oxy-1,4-phenylenecarbonyl), in the form of powder	0
0521	ex3907 99 19 20	Liquid crystal copolyester with a melting point of not less than 270 °C, whether or not containing fillers	0
0523	ex3908 90 00 10	Poly(iminomethylene-1,3-phenylenemethyleneiminoadipoyl), in one of the forms mentioned in note 6 (b) to Chapter 39	0
0522	ex3908 90 00 20	Copolymer consisting of hexamethylenediamine, isophthalic acid and terephthalic acid, in one of the forms mentioned in note 6(b) to Chapter 39	0
0524	ex3909 40 00 10	Polycondensation product of phenol with formaldehyde, in the form of hollow spheres of a diameter of less than 150 µm	0
0525	ex3910 00 00 10	3-[(2-Aminoethyl)amino]propyl(methyl)cyclosiloxane	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0526	ex3910 00 00 20	Block copolymer of poly(methyl-3,3,3-trifluoropropylsiloxane) and poly[methyl(vinyl)siloxane]	0
0527	ex3911 90 19 10	Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene)	0
0528	ex3911 90 19 20	Hydrocarbon prepolymer, obtained by the reaction of cyclopentadiene and 1,3-pentadiene	0
0530	ex3911 90 99 20	Copolymer of dibutyl maleate and <i>N</i> -vinyl-2-pyrrolidone, in one of the forms mentioned in note 6 (a) of Chapter 39	0
0531	ex3911 90 99 25	Copolymer of vinyltoluene and α -methylstyrene	0
0532	ex3911 90 99 40	Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight	0
0533	ex3911 90 99 45	Copolymer of maleic acid and methyl vinyl ether	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0534	ex3911 90 99 55	<p>Solution containing:</p> <ul style="list-style-type: none"> - (36 ± 0,5) % by weight of polyamide with lateral ester groups, - (2 ± 0,5) % by weight of acrylic ester, - (48 ± 0,5) % by weight of 1-methyl-2-pyrrolidone, - (12 ± 0,5) % by weight of bis(2-methoxyethyl) ether, - 500 µg/kg or less of potassium and - 500 µg/kg or less of iron, <p>for use in the manufacture of goods of heading No 8542 (a)</p>	0
0535	ex3912 11 00 10	Non-plasticized cellulose triacetate, in the form of flakes, for the manufacture of cellulose triacetate yarn (a)	0
0537	ex3912 39 10 10	Ethylcellulose, not plasticized	0
0536	ex3912 39 10 20	Ethylcellulose, in the form of aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulfate, containing by weight (27 ± 3) % of ethylcellulose	0
0538	ex3912 39 80 10	Cellulose, both hydroxyethylated and ethylated, insoluble in water	0
0539	ex3912 39 80 20	Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0540 ex3912 90 10 10	Cellulose acetate propionate, non-plasticised, in the form of powder: <ul style="list-style-type: none"> <li data-bbox="563 398 1193 465">– containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) and <li data-bbox="563 477 1142 521">– of a viscosity not exceeding 120 poise (as determined by the ASTM D 817-72 method), for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings (a)	0
0541 ex3913 90 80 30	Chondroitinsulfuric acid, sodium salt	0
0542 ex3915 90 93 30	Waste, parings and scrap of photographic, cinematographic and radiographic films	0
0543 ex3917 32 10 10	Flexible pipe of silicone foam, with continuous channels, of a Shore A hardness of 7 or more but not exceeding 48 and a density of 0,28 g/cm ³ or more but not exceeding 0,92 g/cm ³	0
0544 ex3917 32 39 20	Pipe consisting of a block copolymer of polytetrafluoroethylene and polyperfluoroalkoxytrifluoroethylene, having a length of not more than 570 mm, a diameter of not more than 50 mm and a wall-thickness of not less than 30 and not more than 110 µm	0
0547 ex3919 10 38 10	Self-adhesive tape of metallised polyurethane containing glass beads for use in the manufacture of marine life-saving equipment (a)	0
0545 ex3919 10 38 20 ex3919 90 38 10	Reflecting film, consisting of a layer of polyurethane with security imprints and embedded glass beads on one side and an adhesive layer on the other side, covered on one or both sides with a release layer	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0546	ex3919 10 61 91 ex3919 90 61 94	Reflecting film, consisting of a layer of polyvinylchloride, a layer of alkyd polyester, with security imprints and embedded glass beads, and an adhesive layer covered with a release layer	0
0548	ex3919 90 10 10	Shaped sheet of plastic, with an adhesive layer containing polyisobutylene and pectin, for the manufacture of colostomy bags (a)	0
0549	ex3919 90 31 40 ex3920 62 19 20 ex3920 62 90 20 ex3920 63 00 30 ex3920 69 00 30	Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers (a)	0
0550	ex3919 90 61 92 ex3919 90 69 92	Polyvinyl chloride sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded glass balls of a diameter not exceeding 100 µm	0
0551	ex3919 90 61 93 ex3919 90 69 93 ex3920 10 89 25	Adhesive film consisting of a base of a copolymer of ethylene and vinyl acetate (EVA) of a thickness of 120 µm or more and an adhesive part of acrylic type of a thickness of 10 µm or more, for the protection of the surface of silicon discs (a)	0
0552	ex3919 90 69 94	Reflecting laminated sheet, consisting of a film of polymethyl methacrylate embossed on one side in a regular pyramidal or other shaped pattern, a film of polymethyl methacrylate containing glass microprisms or microspheres, an adhesive layer and a release sheet	0
0553	ex3920 10 26 20	Film of polyethylene, of a thickness of 20 µm or more but not exceeding 45 µm, containing calcium carbonate in the mass, for the manufacture of napkins for babies or of sanitary towels or of tampons or of disposable surgical gowns (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0554	ex3920 10 26 30 ex3920 10 89 20	Film of a thickness not exceeding 0,20 mm, of a blend of polyethylene and a copolymer of ethylene with oct-1-ene, embossed in a regular rhomboidal pattern, for coating both sides of a layer of unvulcanized rubber (a)	0
0559	ex3920 10 28 92 ex3920 10 89 30	Polyethylene sheet, of a thickness of 0,025 mm or more but not exceeding 3 mm, of an elongation at break of 100 % or more but not exceeding 1 100 % (as determined by the ASTM D 638 and 882 methods), in rolls of a width of 4,6 m, 4,8 m, 7,0 m or 9,3 m (a)	0
0555	ex3920 10 40 91	Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polyethylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing polyvinyl alcohol dissolved in water as the moistening agent	0
0556	ex3920 10 40 92	Laminated sheet or strip consisting of a film composed of a blend of a copolymer of ethylene with vinyl acetate and a modified ethylene-propylene-elastomer (EPM) or a modified ethylene-propylene-diene elastomer (EPDM), coated or covered on both sides with a film of a copolymer of ethylene with vinyl acetate	0
0558	ex3920 10 89 35	Reflecting film, consisting of a layer of polyethylene with security imprints and embedded glass beads on one side and a hot-melt adhesive layer on the other side, the first side covered with a release layer	0
0560	ex3920 20 29 91	<p>Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, having:</p> <ul style="list-style-type: none"> - a thickness of 55 µm or more but not exceeding 97 µm, - a tensile modulus in the machine direction of 0,75 GPa or more but not exceeding 1,45 GPa and - a tensile modulus in the transverse direction of 0,20 GPa or more but not exceeding 0,55 GPa 	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0561 ex3920 20 90 91	Synthetic paper pulp, in the form of moist sheets, made from unconnected finely-branched polypropylene fibrils, whether or not blended with cellulose fibres in a quantity not exceeding 15 %, containing polyvinyl alcohol dissolved in water as the moistening agent	0
0562 ex3920 20 90 92	Laminated sheet or strip, consisting of a film of a thickness of 181 µm or more but not exceeding 223 µm composed of a blend of a copolymer of propylene with ethylene and a copolymer of styrene-ethylene-butylene-styrene (SEBS) coated or covered on one side with a layer of a copolymer of styrene-ethylene-butylene-styrene (SEBS) and a layer of polyester	0
0563 ex3920 30 00 20	Laminated sheet or strip, consisting of a film composed of a blend of a thermoplastic elastomer (TPE) of styrene-butadiene-styrene (SBS) with polyethylene or polypropylene, of a thickness of 100 µm or more but not exceeding 200 µm, coated or covered on both sides with a film of polypropylene of a thickness not exceeding 20 µm	0
0564 ex3920 42 11 92 ex3920 42 91 92	Reflecting sheeting, consisting solely of a single layer of polyvinyl chloride, wholly embossed on one side in a regular pyramidal pattern	0
0565 ex3920 42 91 93	Sheeting of polyvinyl chloride, stabilized against ultraviolet rays, without any holes, even microscopic, of a thickness of 60 µm or more but not exceeding 80 µm, containing 30 or more but not more than 40 parts of plasticizer to 100 parts of polyvinyl chloride	0
0566 ex3920 42 91 94	Polyvinyl chloride sheet, with relief printing, for the manufacture of templates for textile printing (a)	0
0567 ex3920 51 00 10	Polymethyl methacrylate plate, with an antistatic coating, of dimensions of 738 × 972 mm (± 1,5 mm)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0568	ex3920 51 00 20	Plate of polymethyl methacrylate containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not exceeding 19 mm	0
0569	ex3920 61 00 10	Polycarbonate film of a thickness not exceeding 15 µm, for the manufacture of film capacitors (a)	0
0572	ex3920 62 19 10	Polyethylene terephthalate film, of a thickness of less than 11 µm, for the manufacture of audiodigital tapes for cassettes (a)	0
0573	ex3920 62 19 15	Polyethylene terephthalate film, not coated with an adhesive, of a thickness not exceeding 25 µm, either: <ul style="list-style-type: none"> - only dyed in the mass, or - dyed in the mass and metallized on one side 	0
0574	ex3920 62 19 25	Film of polyethylene terephthalate only, of a total thickness not exceeding 120 µm, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0
0575	ex3920 62 19 30	Polyethylene terephthalate film, of a thickness of 20 µm or more but not exceeding 30 µm, coated on one side with silicone, for use in the manufacture of window film (a)	5.6
0576	ex3920 62 19 35	Laminated film of polyethylene terephthalate only, of a total thickness not exceeding 120 µm, consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0577	ex3920 62 19 40	Film of polyethylene terephthalate, coated or covered on one side or on both sides with a layer of modified polyester, of a total thickness of 7 µm or more but not exceeding 11 µm, for the manufacture of video tapes with a magnetic layer of metallic pigments and a width of 8 mm or of 12,7 mm (a)	0
0578	ex3920 62 19 45	Single ply film of polyethylene terephthalate only, of a thickness not exceeding 120 µm, which only: <ul style="list-style-type: none"> <li data-bbox="563 667 1118 734">– contains a colouring and/or UV-absorbing material throughout the mass and <li data-bbox="563 745 935 768">– is metallised on one side, whether or not coated on one or both sides with a vinyl acrylate polymer but having no other coating or adhesive	0
0579	ex3920 62 19 50	Film of polyethylene terephthalate, of a total thickness not exceeding 120 µm, of a width of 100 mm or more but not exceeding 115 mm, coated on both sides with one or more layers containing different chemicals, for the manufacture of goods of subheading 3701 20 00 (a)	0
0580	ex3920 62 19 55	Film of polyethylene terephthalate, on one side metallised and coated with white ink and a protective layer and on the other side coated with a thermosensitive seal layer, of a width of 100 mm or more but not exceeding 150 mm, for the manufacture of goods of subheading 3701 20 00 (a)	0
0581	ex3920 62 19 60	Film of polyethylene terephthalate, coated on one side with a layer of modified polyester, of a thickness of 20 µm (± 0,7 µm) or of 30 µm (± 0,9 µm), for the manufacture of audio magnetic tapes of a total thickness of 33 µm or more (a)	0
0570	ex3920 62 19 62	Polyethylene terephthalate film, of a thickness not exceeding 12 µm, coated on one side with a layer of aluminium oxide of a thickness not exceeding 350 Å	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0571	ex3920 62 19 64	<p>Polyethylene terephthalate film, of a thickness of 18 µm or more but not exceeding 25 µm, having:</p> <ul style="list-style-type: none"> - a shrinkage of (3,4 ± 0,1) % in the machine direction (as determined by the ASTM D 1204 method) and - a shrinkage of (0,3 ± 0,2) % in the transverse direction (as determined by the ASTM D 1204 method) 	0
0582	ex3920 62 19 65	Polyethylene terephthalate film, of a thickness not exceeding 19 µm or of a weight of 20 g/m ² or more but not exceeding 26,7 g/m ² , for use in the manufacture of photo-resist film (a)	0
0583	ex3920 62 19 70	Film of polyethylene terephthalate, coated on both sides with a layer of epoxy acrylic resin, of a total thickness of 37 µm (± 3 µm)	0
0584	ex3920 62 19 75	Film of polyethylene terephthalate, coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness not exceeding 300 µm and having a surface resistivity not exceeding 10 000 ohms (per square) (as determined by the ASTM D 257-93 method)	0
0585	ex3920 62 19 80	Mat film of polyethylene terephthalate, of a gloss of 15 at an angle of 45° and 18 at an angle of 60° (as determined by the ASTM D 523 method) and a width of 1 600 mm or more	0
0586	ex3920 62 19 81	Film of white polyethylene terephthalate, dyed in the mass, of a thickness of 185 µm or more but not exceeding 253 µm, coated on both sides with an antistatic layer	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0587	ex3920 62 19 85	Film of a total thickness of 4,5 µm (± 0,16 µm), consisting of a biaxially-oriented polyethylene terephthalate film, of a thickness of 4,4 µm, an elastic modulus (in the machine direction) of 12 kg/mm ² (± 2 kg/mm ²) and a tensile strength (in the machine direction) of more than 28 kg/mm ² , and of an anti-adherent coating of a thickness of 0,1 µm	0
0588	ex3920 62 19 87	Polyethylene terephthalate film, coated with a wax layer, a scratch resistant layer and a thermoadhesive layer, of a nominal width of 790 mm and a total thickness of 23 µm or more but not exceeding 26 µm	0
0589	ex3920 62 19 89	Multilayer film of a thickness not exceeding 150 µm, consisting of a polyester film coated on one side with polycarbonate resin, metallized on the other side with titanium coated with polycarbonate resin and other layers containing <i>N,N'</i> -diphenyl- <i>N,N'</i> -di- <i>m</i> -tolylbiphenyl-4,4'-ylenediamine	0
0590	ex3920 62 90 30	Film of polyethylene terephthalate, of a thickness of 500 µm (± 25 µm)	0
0591	ex3920 69 00 20	Film of polyethylene naphthalene-2,6-dicarboxylate, of a thickness of 82 µm or more but not exceeding 88 µm	0
0592	ex3920 69 00 40	Iridescent film of polyester and polymethyl methacrylate	0
0593	ex3920 69 00 50	Polycondensation product of terephthalic acid with a mixture of cyclohex-1,4-ylenedimethanol and ethane-1,2-diol, in the form of a film	0
0594	ex3920 69 00 60	Film of a copolymer of ethylene terephthalate and ethylene isophthalate, of a thickness not exceeding 2 µm	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0595	ex3920 91 00 91	Polyvinyl butyral film having a graduated coloured band	6
0596	ex3920 91 00 92	Plasticized film of polyvinyl butyral, containing by weight: <ul style="list-style-type: none"> - either 14,5 % or more but not more than 17,5 % of dihexyl adipate, - or 14,5 % or more but not more than 28,5 % of dibutyl sebacate 	0
0597	ex3920 91 00 93	Film of polyethylene terephthalate, metallised on one or both sides, or laminated film of polyethylene terephthalate films, metallised on the external sides only, and having the following characteristics: <ul style="list-style-type: none"> - a visible light transmission of 50 % or more, - coated on both sides with a layer of polyvinyl butyral but not coated with an adhesive or any other material except polyvinyl butyral, - a total thickness not exceeding 0,2 mm without taking the presence of polyvinyl butyral into account, <p style="text-align: center;">for use in the manufacture of heat-reflecting laminated glass (a)</p>	0
0598	ex3920 99 28 10	Reflecting sheet of metallised polyurethane, containing glass beads, coated with a hot-melt adhesive layer, covered on one or both sides with a release sheet, in rolls of a width of 1 020 mm (\pm 20 mm), for slitting into safety clothing reflecting strip (a)	0
0599	ex3920 99 28 20	Reflecting film, consisting of a layer of polyurethane with security imprints and embedded glass beads on one side and an adhesive layer on the other side, the first side covered with a release layer	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0607	3920 99 53 ex3920 99 59 55	Ion-exchange membranes of fluorinated plastic material	0
0600	ex3920 99 59 20	Film entirely of polyvinyl alcohol, of a thickness not exceeding 1 mm and containing by weight: <ul style="list-style-type: none"> - 2 % or less of unhydrolysed acetate groups evaluated as vinyl acetate and - 5 % or more but not more than 25 % of glycerol as plasticizer, <p>for the manufacture of roof-windows (a)</p>	0
0601	ex3920 99 59 25	Poly(1-chlorotrifluoroethylene) film	0
0602	ex3920 99 59 30	Film and sheet of a copolymer of ethylene with chlorotrifluoroethylene, of a thickness of 12 µm or more but not exceeding 400 µm	0
0603	ex3920 99 59 35	Film entirely of polyvinyl alcohol, of a thickness not exceeding 1 mm and of a width of 2,20 m or more, with an extension at break, in the transverse direction, of 350 % or more	0
0604	ex3920 99 59 40	Biaxially-oriented film of polyvinyl alcohol, coated on both sides, of a total thickness of less than 1 mm	0
0605	ex3920 99 59 45	Iridescent film of polyester, polyethylene and an ethylene-vinyl acetate copolymer	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0606	ex3920 99 59 50	Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not exceeding 0,14 mm, impermeable to water vapour	0
0608	ex3921 19 00 91	Microporous polypropylene film of a thickness not exceeding 100 µm	0
0609	ex3921 19 00 92	Microporous film consisting of mixtures of cellulose acetate and cellulose nitrate, of a thickness not exceeding 200 µm	0
0610	ex3921 90 19 35	Composite plate of polycarbonate and polybutylene terephthalate, reinforced with glass fibres	0
0611	ex3921 90 19 45	Composite plate of polyethylene terephthalate or of polybutylene terephthalate, reinforced with glass fibres	0
0612	ex3921 90 60 91 ex5407 71 00 20 ex5903 90 99 10	Woven polytetrafluoroethylene fabric, coated or covered with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulfonic acid groups, whether or not in the potassium or sodium salt form	0
0613	ex3926 90 91 20	Reflecting sheeting or tape, consisting of a facing-strip of polyvinyl chloride embossed in a regular pyramidal pattern, heat-sealed in parallel lines or in a grid-pattern to a backing-strip of plastic material, or of knitted or woven fabric covered on one side with plastic material	0
0617	ex3926 90 99 10	Microspheres of polymer of divinylbenzene, of a diameter of 4,5 µm or more but not exceeding 80 µm	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0618	ex3926 90 99 20	Tape pad, for use in the manufacture of goods of heading No 8523 (a)	0
0619	ex3926 90 99 30	Guide pin and pole, for use in the manufacture of goods of subheadings 8523 11 00, 8523 12 00 and 8523 13 00 (a)	0
0620	ex4007 00 00 10	Siliconated vulcanised rubber thread and cord	0
0621	ex4008 11 00 10	Blocks or sheets of cellular vulcanised rubber of modified ethylene-propylene-diene (EPDM) blended with chloroprene, which satisfy the Underwriters Laboratories Flammability Standard UL94HF-1	0
0622	ex4016 99 88 10	Soft rubber sealing stoppers for the manufacture of electrolytic capacitors (a)	0
0623	4105 11 91 4105 11 99 4105 12 10 4105 12 90 4105 19 10 4105 19 90	Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4108 or 4109	0
0624	4106 11 90 4106 12 00 4106 19 00	Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading No 4108 or 4109	0
0625	4107 10 10 4107 29 10 4107 90 10	Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading No 4108 or 4109	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0626	ex4802 51 90 10 ex4802 52 20 10 ex4802 52 80 10	Overlay paper, of a width of more than 110 cm and containing by weight more than 5 % of corundum	0
0627	ex4805 60 90 20	Paper, in cross-wise rewinded spiral rolls, of a weight of less than 150 g/m ² and of a thickness not exceeding 0,05 mm, for the manufacture of electrolytic capacitors (a)	0
0628	ex4810 99 10 10	Bleached paper coated with kaolin, for use in the manufacture of tampons applicators (a)	0
0629	ex4811 21 00 10	Impregnated paper coated or covered with a pressure-sensitive self-adhesive layer, the whole: <ul style="list-style-type: none"> – of a tensile of 2 700 N/m or more but not exceeding 3 700 N/m in the machine direction (as determined by the EN ISO 1924-2 and ISO 3781 methods), – of a stretch factor of 1,5 % or more but not exceeding 3,0 % in the machine direction (as determined by the EN ISO 1924-2 and ISO 3781 methods) 	0
0630	ex4811 31 00 10	Paper coated with acrylic polymer, with a gloss of 75 or more but not exceeding 90 (as determined by the Hunter method), of a weight of 160 g/m ² or more but not exceeding 180 g/m ² , for use as casting paper in the manufacture of films of plastics (a)	0
0631	ex4811 39 00 10	Kraft paper impregnated with an acrylic polymer, of a nominal weight of 85 g/m ²	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0632	ex4823 90 50 10	Paper coated with dye retention and dye releasing agents used to produce a positive image, for the manufacture of goods of subheading 3701 20 00 (a)	0
0633	ex4823 90 50 20	Honeycomb filter, of paper impregnated with carbon, of a thickness greater than 10 mm but not exceeding 30 mm	0
0634	ex4823 90 90 12	Strips of paper glued to one another to form a honeycomb of a height not exceeding 13 cm, for agricultural purposes (a)	0
0635	ex4911 99 00 10	Polyester film, partially coated with a magnetic metal layer showing a regular repeating logo or motif, for the manufacture of security threads (a)	0
0636	5002 00 00	Raw silk (not thrown)	0
0637	ex5004 00 10 10 ex5004 00 90 10	Yarn spun entirely from silk, not put up for retail sale	2.5
0638	ex5005 00 10 10 ex5005 00 90 10	Yarn spun entirely from silk waste (noil), not put up for retail sale	0
0638bi	5208 11 10	Fabrics for the manufacture of bandages, dressings and medical gauzes	5.4

CN code & TARIC	Description	Rate of autonomous duty (%)
0639 ex5402 41 00 10	<p>Polyamide yarn, not textured, untwisted or with a twist not exceeding 22 turns per metre, of crimpable bicomponent filaments consisting of poly(hexamethylene adipamide) with a copolyamide, for the manufacture of:</p> <ul style="list-style-type: none"> - knee-length stockings of subheadings 6115 20 11 and 6115 93 30, - women's stockings of subheadings 6115 20 19 and 6115 93 91 or - panty hose (tights) of subheading 6115 11 00 <p>(a)</p>	0
0640 ex5402 41 00 20	Yarn of synthetic textile fibres solely of aromatic polyamides obtained by the polycondensation of <i>m</i> -phenylenediamine and isophthalic acid	0
0641 ex5402 43 00 20	Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex, consisting of 110 filaments each having a core of polyethylene terephthalate and a skin of polyamide-6, containing by weight 75 % or more but not exceeding 77 % of polyethylene terephthalate, for use in the manufacture of roofings (a)	0
0642 ex5402 49 99 10 ex5402 69 90 20	Multifilaments yarn of polytetrafluoroethylene	0
0643 ex5402 49 99 30	Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures (a)	0
0644 ex5402 49 99 50 ex5402 59 90 20 ex5402 69 90 40	Non-textured filament yarn of polyvinyl alcohol	0
0645 ex5402 49 99 60 ex5402 69 90 10	Yarn wholly of polyglycollic acid	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0646	ex5402 49 99 70	Synthetic filament yarn, single, containing by weight 85 % or more of acrylonitrile, in the form of a wick containing 1 000 continuous filaments or more but not more than 25 000 continuous filaments, of a weight per metre of 0,12 g or more but not exceeding 3,75 g and of a length of 100 m or more, for the manufacture of carbon-fibre yarn (a)	0
0647	ex5402 49 99 80	Polyethylene filament yarn, untwisted, of either 55, 110, 165 or 1 760 decitex, for the manufacture of goods of heading No 5607 (a)	0
0648	ex5402 49 99 85	Synthetic filament yarn, single, untwisted, wholly of poly(thio-1,4-phenylene)	0
0649	ex5404 10 90 10	Monofilament of polytetrafluoroethylene	0
0650	ex5404 10 90 20	Monofilament of poly(1,4-dioxanone)	0
0651	ex5404 10 90 30	Monofilament of a copolymer of 1,3-dioxan-2-one with 1,4-dioxan-2,5-dione, for the manufacture of surgical sutures (a)	0
0652	ex5407 71 00 10	Woven fabrics of polyvinyl alcohol fibres, for machine embroidery	0
0653	ex5501 90 90 10	Polyvinyl alcohol tow	0
0654	ex5503 20 00 10	Polyester staple fibres, loaded with zeolite impregnated with a mixture of salts of copper and silver or of salts of zinc and silver	4

CN code & TARIC		Description	Rate of autonomous duty (%)
0655	ex5503 90 10 10 ex5503 90 90 30	Acetalized, multicomponent spun fibres with a matrix fibril structure, consisting of emulsion-polymerized polyvinyl alcohol and polyvinyl chloride	0
0656	ex5503 90 90 10	Textile fibres of polytetrafluoroethylene	4
0657	ex5503 90 90 20 ex5506 90 90 10 ex5601 30 00 10	Polyvinyl alcohol fibres, whether or not acetalized	0
0658	ex5503 90 90 40	Fibres wholly of poly(thio-1,4-phenylene)	0
0659	ex5601 30 00 20	Polyester fibres, measuring 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm	0
0660	ex5601 30 00 30	Acrylic fibres, measuring 0,11 and 0,56 decitex, of a length of 3 mm or more but not exceeding 5 mm	0
0661	ex5603 11 10 10 ex5603 11 90 10 ex5603 12 10 10 ex5603 12 90 10 ex5603 91 10 10 ex5603 91 90 10 ex5603 92 10 10 ex5603 92 90 10	<p>Polyvinyl alcohol non-wovens, in the piece or cut into rectangles:</p> <ul style="list-style-type: none"> - of a thickness of 200 µm or more but not exceeding 280 µm and - of a weight of 20 g/m² or more but not exceeding 50 g/m² 	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0662	ex5603 11 10 20 ex5603 11 90 20 ex5603 12 10 20 ex5603 12 90 50	Non-wovens, containing spunbonded fibres of polypropylene or of polypropylene and polyethylene, for the manufacture of napkins and napkin liners for babies and similar sanitary articles (a)	0
0664	ex5603 12 90 30 ex5603 13 90 30 ex5603 14 90 10	Non-wovens of aromatic polyamide fibres obtained by polycondensation of <i>m</i> -phenylenediamine and isophthalic acid, in the piece or cut into rectangles	0
0663	ex5603 12 90 60 ex5603 13 90 60	Non-woven of spunbonded polyethylene, of a weight of more than 60 g/m ² but not exceeding 80 g/m ² and an air permeance (Gurley) of 8 s or more but not exceeding 36 s (as determined by the ISO 5636/5 method)	0
0665	ex5603 13 90 40 ex5603 14 90 20	Non-wovens consisting of a central layer of polycarbonate fibres, laminated on each side with spunbonded filaments of polyester, of a weight of more than 130 g/m ² but not exceeding 200 g/m ²	0
0666	ex5603 92 90 20 ex5603 93 90 20	Non-wovens consisting of a melt-blown central layer of a thermoplastic elastomer laminated on each side with spunbonded fibres of polypropylene	0
0667	ex5603 92 90 40 ex5603 93 90 10	Non-wovens of polypropylene consisting of a melt-blown central layer, laminated on each side with spun-bonded fibres, of a thickness not exceeding 550 µm and of a weight not exceeding 80 g/m ² , in the piece or simply cut into rectangular shape, not impregnated	0
0668	ex5603 92 90 50	Non-wovens of staple fibres, in rolls, of a width of 78 mm or more but not exceeding 252 mm, for the manufacture of floppy discs (a)	0
0669	ex5603 94 90 20	Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0670	ex5607 50 90 10	Twine, unsterilised, wholly of polyglycollic acid, plaited or braided, with an inner core, for the manufacture of surgical sutures (a)	0
0671	ex5903 10 90 10 ex5903 20 90 10 ex5903 90 99 20	Knitted or woven fabrics, coated or covered on one side with artificial plastic material in which are embedded microspheres	0
0672	ex5903 20 90 20	Tape of polyester fabric laminated with a metallised polyurethane film containing glass beads, for use in the manufacture of marine life-saving equipment (a)	0
0673	ex5907 00 90 10	Textile fabrics, coated with adhesive in which are embedded spheres of a diameter not exceeding 75 µm	0
0674	ex5911 10 00 10	Needle-punched synthetic-fibre felts, not containing polyester, whether or not containing catalytic particles entrapped within the synthetic fibres, coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (a)	0
0675	ex5911 90 90 10	Yarn and strip of impregnated polytetrafluoroethylene, whether or not oiled or graphited	0
0676	ex5911 90 90 30 ex8421 99 00 92	Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness not exceeding 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more	0
0677	6305 10 10	Sacks and bags, of a kind used for the packing of goods, used, of jute or of other textile bast fibres of heading No 5303	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0678	ex6305 90 00 10 ex6305 90 00 91	Sacks and bags, of a kind used for the packing of goods, used, of flax or of sisal	0
0679	ex6903 20 90 10	Yarn of continuous ceramic filaments, each filament containing by weight: <ul style="list-style-type: none"> - 12 % or more of diboron trioxide, - 26 % or less of silicon dioxide and - 60 % or more of dialuminium trioxide 	0
0680	ex6903 90 80 10 ex6909 19 00 40	Beryllium oxide, of a purity by weight of more than 99 %, in the form of blanks, bars, blocks or plates	0
0681	ex6909 12 00 20	Plate, of dialuminium trioxide and titanium carbide, of dimensions not exceeding 48 × 48 mm, or of a diameter not exceeding 125 mm, for the manufacture of magnetic heads (a)	0
0682	ex6909 19 00 30	Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume not exceeding 65 l, having, per cm ² of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end	0
0683	ex6909 19 00 50 ex8102 99 00 10	Disc (target) with deposition material, consisting of molybdenum silicide: <ul style="list-style-type: none"> - containing 1 mg/kg or less of sodium and - mounted on a metal support 	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0684	ex7006 00 90 10	Glass plate, coated on one side with chromium and/or with a mixture of diindium trioxide and tin dioxide, of dimensions of 260 × 320 mm or more but not exceeding 400 × 400 mm, of a thickness not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a)	0
0685	ex7006 00 90 20	Colour filter, consisting of a glass plate with red, blue and green pixels, having a total thickness of 1,1 mm (± 0,1 mm) and exterior dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, for the manufacture of liquid crystal displays (a)	0
0686	ex7006 00 90 30	Glass plate, uncoated, of dimensions of 320 × 352 mm or more but not exceeding 320 × 400 mm, of a thickness of 0,6 mm or more but not exceeding 1,2 mm, for the manufacture of liquid crystal displays (a)	0
0687	ex7006 00 90 40	Disk of aluminosilicate glass, with a hole in the centre, with the edges having been ground and bevelled, of a total thickness not exceeding 1,2 mm	0
0688	ex7011 10 00 10	Glass lenses with a stippled front refractor or with a front refractor composed of prismatic elements, with an external diameter of more than 121 mm but not exceeding 125 mm	0
0689	ex7011 10 00 20	Parabolic glass reflectors, with an external diameter of more than 121 mm but not exceeding 125 mm	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0690	ex7011 20 00 40	0
	<p>Glass face-plate:</p> <ul style="list-style-type: none"> - with a diagonal measurement of 366,4 mm ($\pm 1,5$ mm) and of dimensions of 246,4 × 315,4 mm ($\pm 1,5$ mm), - with a diagonal measurement of 391 mm ($\pm 1,5$ mm) and of dimensions of 261,4 × 326,8 mm ($\pm 1,5$ mm), - with a diagonal measurement of 442 mm ($\pm 1,5$ mm) and of dimensions of 293,4 × 369,2 mm ($\pm 1,5$ mm), - with a diagonal measurement of 544,5 mm ($\pm 1,6$ mm) and of dimensions of 358 × 454 mm ($\pm 1,6$ mm), having a cylindrical curvature, - with a diagonal measurement of 570,5 mm ($\pm 1,6$ mm) and of dimensions of 360 × 486 mm ($\pm 1,6$ mm), - with a diagonal measurement of 629,8 mm (± 3 mm) and of dimensions of 406,5 × 519 mm (± 2 mm), having a cylindrical curvature, or - with a diagonal measurement of 753 mm ($\pm 1,6$ mm) and of dimensions of 471 × 640 mm ($\pm 1,6$ mm), <p>and with a raised edge, for the manufacture of colour cathode-ray tubes (a)</p>	
0691	ex7011 20 00 75	0
	<p>Glass face-plate:</p> <ul style="list-style-type: none"> - with a diagonal measurement of 604,5 mm (± 3 mm) and of dimensions of 340 × 541 mm (± 2 mm), - with a diagonal measurement of 639,3 mm (± 3 mm) and of dimensions of 413,6 × 527 mm (± 2 mm), - with a diagonal measurement of 708 mm (± 3 mm) and of dimensions of 404 × 633 mm (± 2 mm), - with a diagonal measurement of 723 mm (± 3 mm) and of dimensions of 477 × 602 mm (± 2 mm), or - with a diagonal measurement of 812,8 mm (± 3 mm) and of dimensions of 463,8 × 725,5 mm (± 2 mm), <p>having a cylindrical curvature, for the manufacture of colour cathode-ray tubes (a)</p>	
0692	ex7014 00 00 10	0
	<p>Optical elements of glass (other than those of heading No 7015), not optically worked, other than signalling glassware</p>	

CN code & TARIC		Description	Rate of autonomous duty (%)
0693	ex7019 12 00 10	Rovings, measuring 2 600 tex or more but not more than 3 300 tex and of a loss on ignition of 4 % or more but not exceeding 8 % by weight (as determined by the ASTM D 2584-94 method)	0
0694	ex7019 19 10 10	Yarn of 33 tex or a multiple thereof, $\pm 7,5$ %, obtained from continuous spun-glass filaments of a nominal diameter of 3,5 μm or of 4,5 μm , in which filaments of a diameter of 3 μm or more but not exceeding 5,2 μm predominate, other than those treated so as to improve their adhesion to elastomers	0
0695	ex7019 19 10 30	Yarn of 22 tex $\pm 7,5$ %, obtained from continuous spun-glass filaments of a nominal diameter of 5 μm , in which filaments of a diameter of 4,2 μm or more but not exceeding 5,8 μm predominate	0
0696	ex7019 19 10 40	Yarn of 33, 34 or 51 tex or a multiple thereof, $\pm 7,5$ %, obtained from continuous spun-glass filaments of a nominal diameter of 6 μm , in which filaments of a diameter of 5,1 μm or more but not exceeding 6,9 μm predominate	0
0697	ex7019 32 00 10 ex7019 39 10 10 ex7019 39 90 10	Non-woven product of non-textile glass fibre, for the manufacture of air-filters or of air-filtration products (a)	0
0698	ex7019 90 10 10	Non-textile glass fibres in which fibres of a diameter of less than 3,5 μm predominate	0
0699	ex7019 90 10 20	Non-textile E-glass fibres, of a length not exceeding 3 mm and a diameter of 5 μm , for the manufacture of catalysts for the purification of smokes (a)	0
0700	ex7116 20 90 10	Disc of silicon on sapphire	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0701	7202 50 00	Ferro-silico-chromium	0
0702	ex7212 50 91 10	Perforated steel strip, plated or coated with nickel, of a width of 140 mm or more but not exceeding 400 mm and a thickness of 60 µm or more but not exceeding 90 µm	0
0703	ex7212 50 99 10	<p>Cold-rolled steel, coated on both sides with a nickel-zinc layer, in the form of strip of a width of 40,15 (± 0,08) mm and a thickness of 0,3 (± 0,01) mm, containing by weight:</p> <ul style="list-style-type: none"> - not more than 0,1 % of carbon, - not more than 0,04 % of phosphorus, - not more than 0,05 % of sulfur and - 0,2 % or more but not more than 0,5 % of manganese 	0
0704	ex7306 30 29 91	Non-alloy steel precision tube, welded and cold finished, of an external diameter exceeding 160 mm and a wall thickness exceeding 2 mm	0
0705	ex7409 19 00 10	Sheet or plate of polytetrafluoroethylene, with aluminium oxide or titanium dioxide as a filler or reinforced with glass-fibre fabric, laminated on both sides with copper foil	0
0706	ex7410 21 00 10	Sheet or plate of polytetrafluoroethylene, with aluminium oxide or titanium dioxide as a filler or reinforced with glass-fibre fabric, laminated on both sides with copper foil, or sheet of polyimide, laminated on one side or on both sides with copper foil	0
0706bi	ex7606 11 91 20 ex7606 11 93 20	Strip with depth-etching, of anodic oxidation treated aluminium of a purity by weight of 99,9 % and a thickness of less than 3 mm, for incorporation in bodies for motor vehicles (a)	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0707 ex7616 99 90 40	Discs of aluminium alloy, coated or covered on both sides with a nickel-phosphorus layer, having a total thickness not exceeding 3,02 mm	0
0708 ex7616 99 90 50	Discs of aluminium alloy, of a thickness not exceeding 0,84 mm, for the manufacture of goods of subheadings 8523 20 11 and 8523 20 19 (a)	0
0709 ex7905 00 00 10	<p data-bbox="564 734 1219 835">Plate of an alloy of zinc, ground and polished on one surface and coated with an epoxide resin on the other surface, of rectangular or square shape, of a length of 300 mm or more but not exceeding 2 000 mm and of a width of 300 mm or more but not exceeding 1 000 mm, and containing:</p> <ul data-bbox="564 913 1182 1111" style="list-style-type: none"> <li data-bbox="564 913 922 936">– 10 mg/kg or less of iron, <li data-bbox="564 947 922 969">– 10 mg/kg or less of lead, <li data-bbox="564 981 1182 1048">– 700 mg/kg or more but not more than 900 mg/kg of aluminium and <li data-bbox="564 1059 1182 1111">– 500 mg/kg or more but not more than 900 mg/kg of magnesium, <p data-bbox="564 1155 1010 1182">for the manufacture of sensitised printing plates (a)</p>	0
0710 ex8101 99 00 10	<p data-bbox="564 1330 1219 1379">Disc (target) with deposition material, of tungsten or an alloy containing by weight 90 % of tungsten and 10 % of titanium:</p> <ul data-bbox="564 1458 1118 1541" style="list-style-type: none"> <li data-bbox="564 1458 1094 1503">– containing 100 µg/kg or less of sodium and <li data-bbox="564 1514 1118 1541">– mounted on a copper or aluminium support 	0
0711 ex8103 90 90 10	Welded tube solely of tantalum, or solely of an alloy of tantalum with tungsten containing by weight 3,5 % or less of tungsten	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0712	ex8104 11 00 30	Unwrought magnesium, of a purity by weight of 99,95 % or more, in the form of ingots, for the manufacture of zirconium sponge or elements used in the nuclear industry (a)	0
0713	ex8104 90 00 10	Ground and polished magnesium sheets, of dimensions not exceeding 1 500 × 2 000 mm, coated on one side with an epoxy resin insensitive to light	0
0714	ex8108 10 10 10	Titanium sponge	0
0715	8108 10 90	Waste and scrap of titanium	0
0716	ex8108 90 70 20	Welded titanium tubes, of an external diameter of 19,0 (± 0,1) mm, having an external structure of 36 fins per 2,54 cm, for use in the manufacture of refrigerant condensers (a)	0
0717	ex8108 90 90 92	Disc (target) with deposition material, of titanium: <ul style="list-style-type: none"> – containing 50 µg/kg or less of sodium and – mounted on a copper or aluminium support 	0
0718	ex8109 10 10 10	Non-alloy zirconium, in the form of ingots, containing by weight more than 0,01 % of hafnium, for use in the manufacture of tubes for the chemical industry (a)	0
0719	ex8110 00 11 10	Antimony in the form of ingots	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0720	ex8112 19 00 10	Beryllium, of a purity by weight of 94 % or more, in the form of bars, plates and sheets	0
0721	ex8112 99 30 10	Alloy of niobium (columbium) and titanium, in the form of bars and rods	0
CN code & TARIC		Description	Rate of autonomous duty (%)
0001	ex8414 90 90 10	Aluminium pistons, partially covered with polytetrafluoroethylene, for incorporation into compressors of air conditioning machines of motor vehicles (a)	0
0002	ex8414 90 90 20	Pressure-regulating system, for incorporation into compressors of air conditioning machines of motor vehicles (a)	0
0003	ex8418 99 90 91	Welded cooling micro-elements, of an alloy of aluminium, for the manufacture of condensers (a)	0
0004	ex8419 19 00 10	Heat accumulator for motor vehicles, of a coolant capacity of 4 l or more but not exceeding 10 l	0
0005	ex8419 89 98 10	Immersion-tube (coils) bundles, consisting of an assembly of plastic tubes terminating at each end in a honeycomb-structure (end-fitting) surrounded by a pipe-connector	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0006	ex8419 89 98 20 ex8543 89 95 58	Sputtering machines and apparatus, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a)	0
0007	ex8421 99 00 91	Parts of equipment, for the purification of water by reverse osmosis, consisting of a bundle of hollow fibres of artificial plastic material with permeable walls, embedded in a block of artificial plastic material at one end and passing through a block of artificial plastic material at the other end, whether or not housed in a cylinder	0
0008	ex8421 99 00 93	Components of separators for the separation or purification of gases from gas mixtures, consisting of a bundle of permeable hollow fibres enclosed within a container, whether or not perforated, of an overall length of 300 mm or more but not exceeding 3 700 mm and a diameter not exceeding 500 mm	0
0009	ex8421 99 00 95	Parts of equipment for the filtration of magnetic dispersions, consisting essentially of nylon-6 fibres, enclosed in a plastic casing of a diameter of 70 mm (± 2 mm) and a length of 520 mm (± 5 mm)	0
0010	ex8424 89 95 10 ex8460 21 90 10 ex8460 40 10 10 ex8460 90 90 10 ex8464 20 19 10 ex8479 89 98 10	Machines and apparatus providing automated lapping, polishing, grinding, cleaning or surface lubrication of disks, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a)	0
0011	ex8424 89 95 20 ex8479 89 98 30	Machines and apparatus providing automated cleaning or cleaning and drying of disks, by means of de-ionised water, ultra sonic waves, chemical solutions, heat or a combination of these processes, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a)	0
0013	ex8439 99 10 10 ex8439 99 90 10	Suction-roll shells, not drilled, in the form of alloy-steel tubes, of a length of 5 207 mm or more and an external diameter of 754 mm or more, for use in machinery for making paper or paperboard (a)	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0014	ex8455 90 00 10	Helical turn device for cold-rolling mill	0
0015	ex8456 10 90 10	Machine-tool operating by laser beam, for the cutting of slots on the surface of a cylindrical tube for use in the manufacture of endo-vascular prosthesis (so-called "stents") (a)	0
0016	ex8460 90 90 20 ex8463 90 00 10 ex8479 89 98 20	Machine-tool providing automated creation of a texture (a head landing zone) on the surface of disks by means of abrasion or exposure to laser beams, comprising disk handling equipment, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a)	0
0017	ex8473 40 19 20	Thermal printer head	0
0018	ex8479 89 98 40 ex8501 10 99 78	Motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8525 20 91 or 8527 90 92 (a)	0
0020	ex8481 80 59 10	Air control valve, consisting of a stepping motor and a valve pintle, for the regulation of idle air flow in fuel injection engines	0
0021	ex8483 10 80 10	Integrally forged and roughly shaped generator and turbine shafts of a weight exceeding 215 tonnes	0
0022	ex8501 10 99 54	DC motor, brushless, with an external diameter not exceeding 25,4 mm, a rated speed of 2 260 (± 15 %) or 5 420 (± 15 %) rpm, a supply voltage of 1,5 or 3 V	0

CN code & TARIC	Description	Rate of autonomous duty (%)	
0023	ex8501 10 99 59	DC stepping motor, with an angle of step of 1,8° (±0,09°), a holding torque of 0,156 Nm or more, a coupling flange the exterior dimensions of which do not exceed 43 × 43 mm, a chuck of a diameter of 4 mm (±0,1 mm), a two-phase winding and an output not exceeding 5 W	0
0024	ex8501 10 99 73	DC motor, whether or not mounted on a baseplate, for use in the manufacture of products falling within subheading 8471 70 53 (a)	0
0025	ex8501 10 99 77	DC motor, with brushes, with a typical running torque of 0,004 Nm (±0,001 Nm), with a coupling flange of a diameter of 32 mm (±0,5 mm) and a chuck of a diameter of 2 mm (±0,004 mm), with an internal rotor, a three-phase winding, a rated speed of 2 800 (±10 %) rpm and a supply voltage of 12 V (±15 %)	0
0026	ex8502 40 90 10	Rotary converter, with a ferrite core, having coils with 2 or 6 windings and a diameter of 0,1 mm, connected to a flexible printed circuit	0
0027	ex8503 00 91 31 ex8503 00 99 32	Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring	0
0028	ex8503 00 99 31	Stamped collector of an electric motor, having an external diameter not exceeding 16 mm	0
0030	ex8504 40 99 20	Direct current to direct current converter	0
0029	ex8504 40 99 30	Static converter comprising a power switch with insulated-gate bipolar transistors (IGBTs), contained in a housing, for use in the manufacture of microwave ovens of subheading 8516 50 00 (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0031	ex8504 50 80 30	Inductor with an inductance not exceeding 62 mH	0
0032	ex8504 50 80 40	Multilayer monolithic inductors, contained in a housing of the SMD (surface mounted device) type the exterior dimensions of which do not exceed 1,8 × 3,4 mm, for use in the manufacture of products falling within subheading 8517 11 00, 8525 20 91 or 8527 90 92 (a)	0
0033	8504 90 11	Ferrite cores	0
0034	ex8504 90 18 32	Part of a rotary transformer, comprising a ferrite core provided with circular grooves with copper wire windings	0
0035	ex8505 11 00 31	Ferrite magnet having a remanence of 455 mT (±15 mT)	0
0036	ex8505 19 90 31	Neodymium-ferro ring with an external diameter not exceeding 13 mm, an internal diameter not exceeding 9 mm	0
0037	ex8505 90 10 91	Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading No 8517 (a)	0
0038	ex8505 90 10 92	Electro-mechanical throttle plate actuator for automotive engines	0
0041	ex8506 50 90 10	Lithium iodine single cell battery the dimensions of which do not exceed 9 × 23 × 45 mm and a voltage not exceeding 2,8 V	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0042	ex8506 50 90 20	Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit	0
0040	ex8506 50 90 30	Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions not exceeding 27,5 x 41 x 15 mm and a capacity of not less than 1,05 Ah	0
0043	ex8507 30 91 20 ex8507 80 91 10 ex8507 80 99 10	Rectangular accumulator, with a length not exceeding 69 mm, a width not exceeding 36 mm and a thickness not exceeding 12 mm, for use in the manufacture of rechargeable batteries (a)	0
0044	ex8507 30 91 30	Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm ($\pm 1,5$ mm) and a diameter of 14,5 mm (± 1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0046	ex8507 80 91 20	Cylindrical nickel-hydrate accumulator, with a length of 44 mm ($\pm 0,5$ mm) and a diameter of 10 mm ($\pm 0,5$ mm), having a nominal capacity of 450 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0047	ex8507 80 91 30	Cylindrical nickel-hydrate accumulator, with a length of 42,5 mm ($\pm 0,5$ mm) and a diameter of 14 mm ($\pm 0,5$ mm), having a nominal capacity of 855 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0048	ex8507 80 91 40	Cylindrical nickel-hydrate accumulator, with a length of 49,5 mm ($\pm 0,5$ mm) and a diameter of 10 mm ($\pm 0,5$ mm), having a nominal capacity of 540 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0045	ex8507 80 91 50	Cylindrical nickel-hydrate accumulator with a length of 66,5 mm (± 1 mm) and a diameter of 10 mm ($\pm 0,5$ mm), having a nominal capacity of 900 mAh or more, for use in the manufacture of rechargeable batteries (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0049	ex8507 80 99 20	Cylindrical lithium-ion accumulator, with a length of 64,6 mm or more and a diameter of 18,1 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (a)	0
0050	ex8516 90 00 31	Dual diode, consisting of a power rectifying diode connected with a transformer protector diode through a wire, with a peak reverse power rate of 2 J or more, for use in the manufacture of products falling within subheading 8516 50 00 (a)	0
0064	ex8518 29 80 20	Loudspeaker having a power of 5 W and an impedance of 4 ohms, with a diameter not exceeding 50 mm, for use in the manufacture of portable phones (a)	0
0065	ex8518 30 80 20	Headphone and earphone for hearing aids, contained in a housing the exterior dimensions of which, excluding connecting points, do not exceed 5 × 6 × 8 mm	0
0066	ex8518 90 00 91	Integrally cold-upsetted steel coreplate, in the form of a disk on one side provided with a cylinder, for use in the manufacture of loudspeakers (a)	0
0067	ex8520 90 90 20	Drive-unit capable of magneto-optical signal recording and optical signal reproducing, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs having an external diameter not exceeding 70 mm, not comprising circuits with amplification functions or power supply drive functions	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0068	ex8522 90 59 93	0
	<p>Optical unit consisting of a laser diode with one photodiode, emitting light of a nominal wavelength of 780 nm, contained in a housing with a diameter of not more than 10 mm and a height of not more than 9 mm, with not more than 10 connections and bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): LDGU LT 022 or - other identification markings relating to devices complying with the abovementioned description 	
0069	ex8522 90 59 94	0
	<p>Electronic assembly for a laser read-head of a compact disc player, comprising:</p> <ul style="list-style-type: none"> - a printed circuit, - a photo-detector, in the form of a monolithic integrated circuit, contained in a housing, - not more than 3 connectors, - not more than 1 transistor, - not more than 3 variable and 4 fixed resistors, - not more than 5 capacitors, <p>the whole mounted on a support</p>	
0070	ex8522 90 98 31	0
	<p>Thin-film recording and reproducing device, having at least 9 parallel channels for digital signals and at least 2 channels for analogue signals, to which a non-magnetic ceramic substrate is fixed, the whole rounded at one side, for use in the manufacture of magnetic heads for digital sound recording and digital/analogue sound reproducing apparatus of the cassette-type (a)</p>	
0071	ex8522 90 98 32	0
	<p>Sound reproducing assembly, consisting of a compact disc mechanism, comprising an optical reading system and 3 DC motors, for use in the manufacture of products falling within subheading 8527 21 20 or 8527 21 70 (a)</p>	
0072	ex8522 90 98 34	0
	<p>Cassette-deck sub-assembly for sound recording and reproducing apparatus, for use in the manufacture of telephone answering machines (a)</p>	

CN code & TARIC		Description	Rate of autonomous duty (%)
0073	ex8522 90 98 35	Sound reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8519 (a)	0
0074	ex8522 90 98 36	Roll for magnetic tape guiding and winding, for use in the manufacture of products falling within heading No 8521 or 8522 (a)	0
0075	ex8522 90 98 37	Magnetic head for erasing video tapes, for use in the manufacture of products falling within heading No 8521 or 8522 (a)	0
0076	ex8522 90 98 38	Read-head assembly, comprising a laser read-head, 2 motors, a flexible printed circuit, the whole mounted on a plastic support, for use in the manufacture of products falling within subheading 8519 99 12 or 8519 99 18 (a)	0
0077	ex8522 90 98 39	Assembly consisting of a driver circuit, a tachometer sensor and a brushless DC motor	0
0078	ex8522 90 98 40	Compact disc changing and selection mechanism, comprising electronic components, not comprising circuits with amplification functions or power supply drive functions, for use in the manufacture of products falling within subheading 8527 31 91 (a)	0
0079	ex8522 90 98 41	Assembly consisting of a drive-unit, comprising at least an optical unit, DC motors and a printed circuit on which are mounted integrated circuits providing drive and signal processing functions for reading optical discs, not capable of recording, for use in the manufacture of products falling within heading No 8521 (a)	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0080	ex8522 90 98 42 Sound reproducing assembly, consisting of a compact disc changing and selection mechanism, comprising an optical reading system, DC motors and an electronic assembly not comprising circuits with amplification functions or power drive functions, for use in the manufacture of products falling within heading No 8527 (a)	0
0081	ex8522 90 98 43 Analogue sound recording and reproducing assembly, comprising a record/playback head and a twin tape deck mechanism of the cassette type, not comprising circuits with amplification functions or power supply drive functions, for use in the manufacture of products falling within subheadings 8527 31 91 and 8527 31 98 (a)	0
0084	ex8528 22 00 10 Video monitor comprising: <ul style="list-style-type: none"> <li data-bbox="564 994 1198 1084">– a flat screen monochrome cathode-ray tube with a diagonal measurement of the screen not exceeding 110 mm and equipped with a deflector yoke, and <li data-bbox="564 1099 1118 1167">– a printed circuit on which are mounted a deflection unit, a video-amplifier and a transformer, the whole mounted on a chassis, for the manufacture of video entry-phones, video telephones or surveillance apparatus (a)	0
0087	ex8529 10 70 10 Ceramic filter package comprising 2 ceramic filters and 1 ceramic resonator for a frequency of 10,7 MHz (± 30 kHz), contained in a housing	0
0088	ex8529 10 70 15 Ceramic filter for a centre frequency of 10,7 MHz, with a bandwidth not exceeding 330 kHz at 3 dB and not exceeding 950 kHz at 20 dB, contained in a housing	0
0089	ex8529 10 70 20 Ceramic filters for frequencies of 4,5 MHz or more but not exceeding 6,6 MHz contained in a housing	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0090	ex8529 10 70 25 Ceramic filter for a centre frequency of 450 kHz or more but not exceeding 470 kHz, with a bandwidth not exceeding 13 kHz at 3 dB, contained in a housing	0
0091	ex8529 10 70 30 Ceramic filter for a frequency of 450 kHz, with a bandwidth not exceeding 18 kHz at 10 dB, contained in a housing	0
0092	ex8529 10 70 35 Ceramic filter for a centre frequency of 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 25 kHz at 6 dB and not exceeding 60 kHz at 40 dB, contained in a housing	0
0094	ex8529 10 70 45 Ceramic filter for a centre frequency of 450 kHz ($\pm 1,5$ kHz) or 455 kHz ($\pm 1,5$ kHz), with a bandwidth not exceeding 30 kHz at 6 dB and not exceeding 70 kHz at 40 dB, contained in a housing	0
0085	ex8529 10 70 50 Radio frequency (RF) signal isolator for frequencies of 890 MHz or more but not exceeding 1 990 MHz, having an insertion loss not exceeding 0,7 dB, contained in a housing	0
0086	ex8529 10 70 55 Filters, excluding surface acoustic wave filters, for a center frequency of 485 MHz or more but not exceeding 1 990 MHz with an insertion loss not exceeding 3,5 dB, contained in a housing	0
0096	ex8529 10 70 80 Ceramic filter package, excluding surface acoustic wave filters, consisting of: – a transmit filter with a centre frequency of 1 747,5 MHz and an insertion loss not exceeding 2,3 dB at a bandwidth of 75 MHz and – a receive filter with a centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,3 dB at a bandwidth of 75 MHz, the whole contained in a housing	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0097	ex8529 10 70 85	0
<p>Ceramic filter package, excluding surface acoustic wave filters, comprising 2 filters with one of the following combinations of characteristics:</p> <ul style="list-style-type: none"> - a transmit centre frequency of 902,5 MHz, a receive centre frequency of 947,5 MHz and an insertion loss not exceeding 3,2 dB at a bandwidth of 25 MHz <p>or</p> <ul style="list-style-type: none"> - a transmit centre frequency of 1 747,5 MHz, a receive centre frequency of 1 842,5 MHz and an insertion loss not exceeding 3,5 dB at a bandwidth of 75 MHz, <p>the whole contained in a housing</p>		
0098	ex8529 10 90 20	0
<p>Antenna switch, comprising:- a transmit filter with a center frequency of 942,5 MHz or more but not exceeding 1990 MHz and- a receive filter with a center frequency of 847,5 MHz or more but not exceeding 1990 MHz, the whole contained in a housing</p>		
0101	ex8529 90 40 40	0
<p>Ceramic intermediate frequency (IF) filter, excluding surface acoustic wave filters, for a centre frequency of 13 MHz and an insertion loss not exceeding 6 dB, contained in a housing</p>		
0102	ex8529 90 81 31	0
<p>Demagnetisation coil, with at least one of following characteristics:</p> <ul style="list-style-type: none"> - an internal diameter of less than 375 mm, - an internal linear dimension measured on the surface profile of less than 1 178 mm, <p>with cables and connectors</p>		
0103	ex8529 90 81 32	0
<p>Optical unit for video projection, comprising a colour separation system, a positioning mechanism and lenses, for use in the manufacture of products falling within heading No 8528 (a)</p>		
0104	ex8529 90 81 34	0
<p>Assembly consisting of a lens unit, having an adjustable focal length of 4 mm or more but not exceeding 69 mm and comprising a zoom encoder, a stepping motor unit, a zoom motor unit, an iris motor unit and a photo interrupter</p>		

CN code & TARIC		Description	Rate of autonomous duty (%)
0105	ex8529 90 81 35	Video recording and reproducing assembly, comprising a tape deck mechanism of the cassette type, comprising a DC motor, for use in the manufacture of products falling within heading No 8525 (a)	0
0106	ex8529 90 81 36	Assembly consisting of a monochrome cathode-ray tube with a diagonal measurement of the screen of 165 mm or more but not exceeding 230 mm and a concave focus lens mounted on a liquid-filled cooling armature, for use in the manufacture of television projection equipment (a)	0
0100	ex8529 90 81 37 ex8529 90 88 33	Filter, consisting of 2 piezo-electric crystals each with a frequency of 21 MHz or more but not exceeding 30 MHz and separately mounted on a bracket, with not more than 7 connections	0
0118	ex8531 80 80 01	Indicator lamp, consisting of 4 light-emitting diodes made from silicon-carbide (SiC) semiconductor material, operating at a nominal wavelength of 481, 560 or 630 nm, contained in a housing	0
0119	ex8531 80 80 15	Indicator lamp, consisting of 2 light-emitting diodes made from aluminium-gallium-arsenic (AlGaAs) or gallium-phosphor (GaP) semiconductor material, having a rectangular base, contained in a housing of the SMD (surface mounted device) type and having a lens	0
0120	ex8531 80 80 25	Electro-acoustic transducer	0
0121	ex8531 80 80 30	An electromagnetic display, consisting of 7 electromagnetic coils which by means of the residual magnetism in the stators provide that the last indication remains available (set state), and 7 pivoting light-reflecting segments each of which is attached to a bar magnet; assembly comprising such displays	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0144	ex8536 30 30 11 ex8536 30 90 31 ex8536 50 80 96	Thermo-electric switch with a cut-off current of 50 A or more, comprising a snap action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0
0145	ex8536 41 10 91 ex8536 41 90 91 ex8536 49 00 91	Thermal relays contained in a hermetically sealed glass cartridge not exceeding 35 mm in length excluding wires, with a maximum leakage rate of 10^{-6} cm ³ He/sec at one bar in the temperature range 0 to 160 °C, to be incorporated into compressors for refrigerating equipment (a)	0
0146	ex8536 50 11 31	Switch of the printed circuit mount type, operating at a force of 4,9 N ($\pm 0,9$ N), contained in a housing	0
0147	ex8536 50 19 91	Hall effect switch, comprising 1 magnet, 1 Hall effect sensor and 2 capacitors, contained in a housing with 3 connections and bearing: <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 2AV28E 2AV31E 2AV56 or - other identification markings relating to devices complying with the abovementioned description 	0
0148	ex8536 50 19 92	Hydraulic pressure switch, incorporating a pressure sensitive snap action disc, operating at a supply voltage of 6 V or more but not exceeding 18 V	0
0149	ex8536 50 80 93	Switch unit for coaxial cable, comprising 3 electromagnetic switches, with a switching time not exceeding 50 ms and an actuating current not exceeding 500 mA at a voltage of 12 V	0
0150	ex8536 50 80 95	Reed switch having a switching power of 20 W or more within the range of 17-43 A.turn, in the form of a glass capsule, not containing mercury, the dimensions of which do not exceed 3×21 mm, for use in the manufacture of automotive airbag shock-sensors (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0152	ex8536 90 85 92	Metallic stamped frame with connections	0
0153	ex8536 90 85 93	Contact element with a hold-force of more than 3 N, in the form of 2 rectangular plastic frames interconnected by electric conductors	0
0154	ex8536 90 85 94 ex8544 49 80 10	Elastomeric connector, consisting of one or more conductor elements and of a rubber or silicon substrate	0
0155	ex8537 10 99 92	Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors	0
0156	ex8538 90 99 92	Part of an electrothermal fuse, consisting of a tin coated copper wire attached to a cylindrical casing, the exterior dimensions of which do not exceed 5 × 48 mm	0
0157	ex8540 11 11 91	Colour cathode-ray tube with a slit or slot mask, equipped with electron guns placed side by side (in-line technology) and with a diagonal measurement of the screen of 12 cm or more but not exceeding 26 cm	0
0158	ex8540 11 11 93	Colour cathode-ray tube, equipped with 1 gun with 3 rays and with a diagonal measurement of the screen of 22 cm or more but not exceeding 26 cm	0
0159	ex8540 11 13 91	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,42 mm and a diagonal measurement of the screen of 49 cm, for use in the manufacture of professional video monitors including security and medical monitor applications (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0160	ex8540 11 19 91	Colour cathode-ray tube equipped with electron guns placed side by side (in-line technology), with a diagonal measurement of the screen of 85 cm or more	0
0161	ex8540 11 70 31	Colour cathode-ray tube with a screen width/height ratio of 16/9 and a diagonal measurement of the screen of 39,8 cm ($\pm 0,3$ cm)	0
0162	ex8540 11 70 32	Colour cathode-ray tube with a diagonal measurement of the screen of 85,5 cm or more	0
0163	ex8540 12 00 82	Monochrome cathode-ray tube with a diagonal measurement of the screen of 250 mm or more but not exceeding 320 mm and an anode voltage of 18 kV or more but not exceeding 22 kV	0
0164	ex8540 12 00 83	Monochrome cathode-ray tube, with a diagonal measurement of the screen of 150 mm or more but not exceeding 182 mm, a neck diameter of less than 30 mm and an anode voltage of 25 kV or more but not exceeding 32 kV	0
0165	ex8540 12 00 84	Flat screen monochrome cathode-ray tube, with a diagonal measurement of the screen not exceeding 102 mm	0
0166	ex8540 20 80 91	Photomultiplier consisting of a photocathode tube with 9 dynodes, for light of a wavelength of 160 nm or more but not exceeding 930 nm, of a diameter not exceeding 14 mm and a height not exceeding 94 mm	0
0167	ex8540 40 00 31 ex8540 60 00 31	Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (in-line technology) or 1 gun with 3 rays, with a diagonal measurement of the screen of more than 72 cm and a distance of less than 0,5 mm between dots of the same colour	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0168	ex8540 40 00 32 ex8540 60 00 32	Colour cathode-ray tube with a dot mask, equipped with 3 electron guns placed side by side (in-line technology) or 1 gun with 3 rays, having a diagonal measurement of the screen not exceeding 72 cm	0
0169	ex8540 40 00 33	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 53 cm	0
0170	ex8540 40 00 34	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,39 mm and a diagonal measurement of the screen of 33 cm or more but not exceeding 38 cm	0
0171	ex8540 40 00 35	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,35 mm and a diagonal measurement of the screen not exceeding 72 cm, for use in the manufacture of monitors (a)	0
0172	ex8540 40 00 36	Colour cathode-ray tube with a slit or slot mask, having a distance between stripes of the same colour of less than 0,30 mm and a diagonal measurement of the screen not exceeding 58 cm	0
0173	ex8540 50 00 31 ex8540 60 00 33	Flat screen monochrome cathode-ray tube, with a diagonal measurement of the screen of 142 mm or more but not exceeding 190 mm, a luminescence of 300 lumen or more but not exceeding 2 000 lumen, a resolution of 0,06 mm or more but not exceeding 0,1 mm, phosphor types P1 or P22 or P53 or P55 or P56, an anode voltage of more than 34 kV, a focus voltage of more than 7 kV and a cathode current of 3 mA or more	0
0174	ex8540 50 00 32 ex8540 60 00 34	Monochrome cathode-ray tube with a diagonal measurement of the screen of 176 mm or more but not exceeding 520 mm and a neck diameter not exceeding 21 mm	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0175	ex8540 89 00 91	Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 300 × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0
0176	ex8540 89 00 92	Vacuum fluorescent display tube	0
0178	ex8540 91 00 31	Electron gun, for use in the manufacture of colour cathode-ray tubes of subheading 8540 40 00 with a diagonal measurement of the screen of 34 cm or more but not exceeding 39 cm (a)	0
0177	ex8540 91 00 32	Electron gun of colour cathode-ray tubes with an anode voltage of 27,5 kV or more but not exceeding 33 kV	0
0179	ex8540 91 00 91	Deflector yoke for cathode-ray tubes with an operating frequency of 31 250 Hz or more but not exceeding 64 000 Hz, incorporating a quadripolar magnet	0
0180	ex8540 91 00 92	Slit or slot mask, excluding masks with continuously vertical slits, with a diagonal measurement of 39 cm or less	0
0181	ex8540 91 00 93	Electron gun for the production of monochrome cathode-ray tubes with a diagonal measurement of the screen of 7,6 cm or more but not exceeding 30,5 cm (a)	0
0182	ex8540 91 00 94	Deflector yoke for colour cathode-ray tubes, with an operating frequency of 15 625 or 31 250 Hz, comprising 2 two-pole ring magnets, 2 four-pole ring magnets and 2 six-pole ring magnets	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0183	ex8540 91 00 96 Assembly for cathode-ray tubes with 2 or more but not more than 6 coils, a plastic support and a metal fixing ring, for the adjustment of display sharpness and/or convergence	0
0184	ex8540 91 00 97 Slit mask, consisting of continuously vertical slits measuring more than 275 mm in the length	0
0185	ex8540 91 00 98 Frame of molybdenum chrome steel, for use in the manufacture of cathode-ray tubes (a)	0
0186	ex8540 99 00 91 Anode, cathode or output part, or an assembly comprising these components (magnetron core tube), for the manufacture of magnetrons of subheading 8540 71 00 (a)	0
0187	ex8543 19 00 10 Electron beam accelerator systems, with an operating voltage or more not exceeding 1,5 MV and a beam current not exceeding 70 mA, providing electron beam radiation to cross link various polymer based products	0
0188	ex8543 89 95 46 Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing bearing: - an identification marking consisting of or including (one of) the following combination(s): FA 01314 MHW 2707 MHW 9002 PF 0144 PHW 902 FA 01317 MHW 607 MHW 910 PF 0146 PHW 925 FA 01321 MHW 704 MHW 914 PF 0148 SHW 5115 FMC 1717 MHW 707 MHW 915 PF 0412 XHW 105 FMC 1819 MHW 720 MHW 916 PHW 2905 XHW 2803 ISO 122 MHW 803 MHW 926 PHW 2907 XHW 2902 MHW 105 MHW 820-1 MHW 927 PHW 5113 XHW 5115 MHW 1815 MHW 820-2 MHW 953 PHW 9012 XHW 903 MHW 2701 or - other identification markings relating to devices complying with the abovementioned description	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0189	ex8543 89 95 48	0
	Radio frequency (RF) modulator, operating with a frequency range of 43 MHz or more but not exceeding 870 MHz, capable of switching VHF and UHF signals, consisting of active and passive elements mounted on a printed circuit, contained in a housing	
0190	ex8543 89 95 49	0
	Rectifier assembly of power barrier diodes, consisting of 2 diodes with an average forward current not exceeding 600 A and a repetitive reverse peak voltage not exceeding 40 V, each contained in a housing and connected by a common cathode	
0191	ex8543 89 95 50	0
	<p>Piezo-electric crystal clock oscillator with a fixed frequency, within a frequency range of 1,8 MHz to 67 MHz, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): R4000.8 R4000.9 or - other identification markings relating to devices complying with the abovementioned description 	
0192	ex8543 89 95 51	0
	<p>Mechanical vibratory gyroscope driven by a 25 or 26 kHz oscillator, comprising a differential amplifier and a detector circuit, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): ENC05D or - other identification markings relating to devices complying with the abovementioned description 	

CN code & TARIC	Description	Rate of autonomous duty (%)
0193	ex8543 89 95 52	0
<p>Opto-electronic circuit comprising one or more light-emitting diodes (LEDs) and one photodiode with amplifier circuit and an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, contained in a plastic housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): HC PL 2400 HC PL 2730 or - other identification markings relating to devices complying with the abovementioned description 		
0194	ex8543 89 95 53	0
<p>Oscillator, with a centre frequency of 20 GHz or more but not exceeding 42 GHz, consisting of active and passive elements not mounted on a substrate, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): 372-02 372-03 or - other identification markings relating to devices complying with the abovementioned description 		
0195	ex8543 89 95 55	0
<p>Audio recording and reproducing circuit, capable of stereo audio data storage and simultaneous record and playback, comprising 2 or 3 monolithic integrated circuits mounted on a printed circuit or a lead frame, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): RWA010 RWA100 RWA200 RWA300 or - other identification markings relating to devices complying with the abovementioned description 		
0196	ex8543 89 95 56	0
<p>Overvoltage suppression assembly, comprising 8 diodes, having a reverse stand-off voltage not exceeding 4,5 V, a reverse leakage current not exceeding 10 µA, a peak pulse current not exceeding 30 A and a nominal capacitance of 50 pF, contained in a housing</p>		

CN code & TARIC	Description	Rate of autonomous duty (%)
0197 ex8543 89 95 57	Frequency converter, not comprising a dipole aerial, for the conversion of frequencies of 10,7 GHz or more but not exceeding 12,75 GHz to frequencies of 950 MHz or more but not exceeding 3 GHz and operating at a supply voltage of 11 V or more but not exceeding 20 V	0
0198 ex8543 89 95 59	Charged coupled device (CCD) scanner assembly, for a real-time film scanning system, having optical functions, illumination functions and signal processing functions	0
0199 ex8543 90 80 40	Stainless steel cathode in the form of a plate with a hanger bar and plastic side strips	0
0200 ex8543 90 80 50	Assembly of products falling within heading No 8541 or 8542 mounted on a printed circuit, contained in a housing	0
0201 ex8545 90 90 01	Cell and battery carbon, in the form of rods, with a length of 34 mm or more but not exceeding 160 mm and a diameter not exceeding 12 mm	0
0063 ex8548 90 90 38	Parts, for use in the manufacture or the repair of products falling within subheading 8517 21 00 (a)	0
0203 ex8548 90 90 39	Optical unit, consisting of a laserdiode and a photodiode, operating at a typical wavelength of 635 or 670 nm	0

CN code & TARIC	Description	Rate of autonomous duty (%)
0204 ex8548 90 90 40	<p>Infrared signal receiver unit, consisting of a photodiode and at least an amplifier in the form of a monolithic integrated circuit, contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): GPIU58XB SBX 1610 or - other identification markings relating to devices complying with the abovementioned description 	0
0205 ex8548 90 90 41	<p>Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not exceeding 40 MHz and a capacitor, contained in a housing</p>	0
0206 ex8548 90 90 42 ex9110 90 00 94	<p>Clock/calendar circuit, consisting of a printed circuit on which are mounted at least a quartz oscillator and a monolithic integrated circuit, the whole contained in a housing bearing:</p> <ul style="list-style-type: none"> - an identification marking consisting of or including (one of) the following combination(s): DS 1287 DS 1387 MK 48T08 MK 48T18 RTC 65271 DS 12887A MK 48T02 MK 48T12 RTC 63421 RTC 72423 or - other identification markings relating to devices complying with the abovementioned description 	0
0207 ex8548 90 90 43	Contact image sensor	0
0208 ex9001 10 90 10	Image reverser made up from an assembly of optical fibres	0
0209 ex9001 20 00 10	Material consisting of a polarising film, supported on one or both sides by transparent material	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0210	ex9001 90 90 20	Rear projection screen, comprising a Fresnel lens of plastic and a polarising sheet of plastic, for use in the manufacture of products falling within heading No 8528 (a)	0
0211	ex9001 90 90 30	Lens of plastic, unmounted, having a focal length of 3,86 mm ($\pm 0,1$ mm) and with a diameter not exceeding 8 mm, for use in the manufacture of compact disc players (a)	0
0212	ex9001 90 90 40	Optical fibre plate, for use in the manufacture of screens and photocathodes for image intensifiers (a)	0
0213	ex9001 90 90 50	Rear projection screen, comprising a lenticular plastic plate	0
0214	ex9001 90 90 60	Prism for the splitting of light, unmounted, for use in the manufacture of charged-coupled image (CCD) cameras (a)	0
0215	ex9001 90 90 70	Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends	0
0216	ex9001 90 90 80	Lens of plastic, unmounted, for use in the manufacture of products falling within subheading 9006 40 00 (a)	0
0217	ex9002 11 00 10	Adjustable lens unit, having a focal length of 90 mm or more but not exceeding 180 mm and comprising a combination of between 4 and 8 glass or methacrylic lenses with a diameter of 120 mm or more but not exceeding 180 mm, each lens coated on at least one side with a magnesium fluoride layer, for use in the manufacture of video projectors (a)	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0218	ex9002 11 00 50	Lens unit, having a focal length of 75 mm or more but not exceeding 94 mm, consisting of glass or plastic lenses, with a diameter of 60 mm or more but not exceeding 180 mm	0
0219	ex9002 11 00 60	Optical element, comprising one or more mounted lenses of plastic, for use in the manufacture of products falling within subheading 9006 40 00 (a)	0
0220	ex9002 19 00 10	Lens unit, having a focal length of 24,96 mm ($\pm 0,1$ mm), a diameter of 16 mm and a length of 16 mm, for use in the manufacture of products falling within subheading 8517 21 00 (a)	0
0221	ex9002 20 00 10	Filter, consisting of a plastic polarising membrane, a glass plate and a transparent protective film, mounted on a metal frame, for use in the manufacture of products falling within heading 8528 (a)	0
0222	ex9002 90 90 10	Optical element comprising an octagonal Fresnel lens, for use in the manufacture of overhead projectors (a)	0
0223	ex9002 90 90 20	Lens, mounted, having a fixed focal length of 3,8 mm ($\pm 0,19$ mm) or 8 mm ($\pm 0,4$ mm), with a relative aperture of F2.0 and a diameter not exceeding 33 mm, for use in the manufacture of charged-coupled (CCD) cameras (a)	0
0224	ex9002 90 90 30	Optical unit, comprising 1 or 2 rows of optical glass fibres in the form of lenses and with a diameter of 0,85 mm or more but not exceeding 1,15 mm, embedded between 2 plastic plates	0
0225	ex9002 90 90 50	Lens and image gate assembly, for a real-time film scanning system, comprising a lens consisting of 9 or 11 elements and having an illumination function	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0226	ex9006 91 90 10	Parts, for use in the manufacture of products falling within subheading 9006 40 00 (a)	0
0229	ex9013 80 90 10	Polarisation insensitive fibre-optic isolator, operating at a wavelength of 1 200 nm or more, contained in a cylindrical housing	0
0230	ex9017 90 90 20	Thermal printer head, comprising at least 7 168 heater elements mounted on 2 or more ceramic supports, the whole contained in a housing the exterior dimensions of which exceed 21 × 39 × 639 mm	0
0231	ex9022 30 00 10	X-ray tube with a target voltage of 4 kV or more but not exceeding 30 kV, a power not exceeding 9 W and a target current not exceeding 2 mA	0
0232	ex9026 20 30 10	Pressure measurement device for automotive applications, comprising active and passive elements mounted on a printed circuit and a sensor, the whole contained in a housing	0
0234	ex9031 80 34 10 ex9031 80 39 30 ex9031 80 99 10	Machines and apparatus providing automated quality inspection of rigid magnetic disks, for use in the manufacture of products falling within subheading 8523 20 11 or 8523 20 19 (a)	0
0235	ex9031 80 39 10	Acceleration measurement device for automotive applications, comprising one or more active and/or passive elements and a sensor, the whole contained in a housing	0
0236	ex9031 90 80 20	Read and write test head for checking the quality of rigid magnetic disks, mounted on a carrier arm	0

	CN code & TARIC	Description	Rate of autonomous duty (%)
0237	ex9031 90 80 30	Assembly for a laser align sensor, in the form of a printed circuit comprising optical filters and a charge-coupled image (CCD) sensor, the whole contained in a housing	0
0238	ex9031 90 80 40	Test head for checking the mechanical quality of rigid magnetic disks, mounted on a carrier arm	0
0239	ex9031 90 80 50	Burnishing head, for removing asperities on and polishing of the surface of rigid magnetic disks, mounted on a carrier arm	0
0240	ex9032 10 91 10	Thermostat, comprising a snap-action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0
0241	ex9032 89 90 10	Automotive airbag shock-sensor, comprising a contact capable of switching a current of 12 A at a voltage of 30 V, having a typical contact resistance of 80 mohm	0
0242	ex9110 12 00 91	Assembly consisting of a printed circuit on which are mounted one quartz oscillator, at least one watch circuit and, whether or not integrated, at least one capacitor, of a thickness not exceeding 5 mm	0
0243	ex9110 90 00 92 ex9114 90 00 91	Assembly consisting of a printed circuit on which is mounted a watch circuit or a watch circuit and a quartz oscillator, of a thickness not exceeding 5 mm	0
0244	ex9110 90 00 93	Assembly consisting of a printed circuit on which is mounted at least one watch circuit, a quartz oscillator and a piezo-electric sound element, with a thickness exceeding 5 mm	0

CN code & TARIC		Description	Rate of autonomous duty (%)
0245	ex9608 91 00 10	Non-fibrous plastic pen-tips with an internal channel	0
0246	ex9608 91 00 20	Felt tips and other porous-tips for markers, without internal canal	0
0247	ex9612 10 10 10	Ribbons of plastic with segments of different colours, providing the penetration of dyes by heat into a support (so called dye-sublimation)	0
0248	ex9613 90 00 20	Piezo-electric ignition mechanism	0

(a)	Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.
(b)	However, the suspension is not allowed where processing is carried out by retail or catering undertakings.

”

FINANCIAL STATEMENT

1. TITLE OF OPERATION

Proposal for a Council Regulation amending Regulation (EC) No 1255/96 temporarily suspending the autonomous common customs tariff duties on certain industrial and agricultural products.

2. BUDGET HEADING(S) INVOLVED

Chapter 12 Article 120.

3. LEGAL BASIS

Article 26 of the EC Treaty.

4. DESCRIPTION OF OPERATION

Suspension of the common customs tariff duties for the above products.

7. FINANCIAL IMPACT

In order to reduce the economic problems arising from the period of validity of previous Regulations, Council Regulation (EC) No 1255/96, now in force, does not have an expiry date.

This proposal contains only the amendments which must be made to the Annex to the existing Regulation in order to take account of the following:

1. new requests for suspension which have been presented and accepted;
2. technical product developments, economic trends on the market and the GATT agreement, resulting in the lifting of certain existing suspensions;
3. amendments to Nomenclature codes.

This time the amendments take the form of a consolidated annex.

Obviously only the amendments described in 1 and 2 have a financial impact.

Addition

This Annex, in addition to the amendments resulting from changes to CN codes, contains 50 new products. The uncollected duties corresponding to these suspensions, calculated on the basis of expected imports into the requesting Member State for 2000, total EUR 9.9 million.

On the basis of the existing statistics for the preceding years, it would appear, however, that this amount must be increased by an average factor, estimated at 1.8, to take account of imports into other Member States using the same suspensions. This means **a loss of revenue of some EUR 17.9 million.**

Withdrawal:

67 products have been withdrawn from this annex reflecting the reintroduction of customs duties. This represents **an increase of EUR 50.1 million in resources**, as calculated from requests for suspension or available statistics (1998).

Estimated cost of this operation

Taking available statistics (1998) as a basis, the impact on the loss of revenue resulting from this Regulation may therefore be estimated at **17.9 - 50.1 = EUR -32.2 million**, then a decrease of loss of revenue, with a **total loss estimated for 2000 of 629.3 - 32.2 = EUR 597.1 million**.

The shortfall in traditional own resources will have to be made up by the Member States by topping up the GNP component.

8. FRAUD PREVENTION MEASURES

Checks on the end-use of some of the products covered by this Council Regulation will be carried out in accordance with Articles 291 to 304 of Commission Regulation (EEC) No 2454/93 laying down provisions for the implementation of the Community Customs Code.