COMMISSION OF THE EUROPEAN COMMUNITIES

COM(82) 219 final

Brussels, 21 April 1982

Proposal for a COUNCIL REGULATION (EEC)

temporarily suspending the autonomous Common Customs
Tariff duties on certain industrial products

(submitted to the Council by the Commission)

COM(82) 219 final

EXPLANATORY MEMORANDUM

- 1. The subject of the following draft regulation is the temporary suspension of duties in the Common Customs Tariff for a number of industrial items, as requested by the Member States.

 It is partly a prolongation and partly a new measure.
- 2. It seems appropriate to the Commission that a duty suspension is justified for the goods listed in the annex to this regulation. The Commission proposes a total suspension for those products for which Community production does not exist or is minimal. A partial suspension is proposed in cases where the Community production covers only a part of the requirements. The rate of the partially suspended duty depends on the extent of the possible Community supply to the Community users. The Commission is also always looking for the right balance between the interests of the suppliers, users and the consumers in the Community.

It also takes into account the need to protect employment.

- 3. The proposed measures are confined to six or twelve months because of the difficulties of estimating the evolution of the basic factors.
- 4. For a number of items for which the Member States also requested duty suspensions the Commission does not propose a taniff measure because the necessary conditions are not fulfilled. This concerns the following items:

CCT Description heading No 17-alpha, 27 Dihydroxy-16-alpha-methylpregna-1,4,9(11)-triene3, 20 dione ex 29.13 D I b) ex 29.13 E 2,4-Dihydroxybenzophenone (4-Benzoylresorcinol) ex 29.14 AIIc)4 16-alpha, 17-alpha, 21-Trihydroxypregna-1, 4,9(11)-triene-3,20-dione 21-acetate. ex 29.22 D VII N-(1-Ethylpropyl)-2,6 dinitro-3,4-xylidine ex 29.25 B III b 3,5-Dichloro-N-(1,1-dimethylprop-2-ynyl)benzamide ex 29.26 B II c) 1,1,3,3-Tetramethylguanidine ex 29.31 B Probucol (INN) ex 29.35 Q Methotrexate (INN) ex 30.03 B II b) Cisplatin (INN) Catalysts consisting of a mixture of oxides on an silicon dioxide support and containing by ex 38.19 G weight: (a) Not less than 25 % and not more than 40 % of antimony (a) Not less than 25 % and not more than 40 % of antimony
(b) Not less than 5 % and not more than 10 % of iron
(c) Not less than 0 · 2 % and not more than 1 · 5 % of molybdenum (d) Not less than 0.8 % and not more than 4.0 % of tellurium ex 38.19 X 2-(Perfluoroalkyl)ethanethiols ex 39.01 C III Film, in rolls, of polyethylene terephthalate, for a) the manufacture of frames or covers for the

protection of microfiches

130,000

Poly(dimethylsiloxane) with a molecular weight of not less than 90,000 and not more than

ex 39.01 C VI

CCT Heading No

Description

ex 39.01 C VII

Poly(thio-1,4-phenylene) income of the forms mentioned in Note 3(b) to Chapter 39

ex 39.01 C VII

Poly(amide-imide) resin, compounded with one or more of the following materials: glass fibres, carbon fibres, graphite, titanium dioxide or polytetrafluoro-ethylene, in one of the forms mentioned in Note 3 (b) to Chapter 39

ex 39.02 C X .

Film of a plasticised copolymer of vinyl chloride and vinyl acetate, compounded with carbon black, with a thickness of no more than 1 mm, backed with paper or paperboard, whether or not in rolls, for the manufacture of duplicator stencils

ex 39.02 CX

Copolymer of vinyl chloride and vinyl acétate containing not less than 85 % and not more than 86.5 % by weight of vinyl chloride and not less than 13.5 % and not more than 15 % by weight of vinyl acetate and with a residual content of vinyl chloride monomer of not more than 0.01 ppm and of which 50 grammes mixed with 150 grammes of distilled water and stirred for 2 hours at room temperature gives, after filtration, a solution of which the surface tension is not more than 71.5 dynes/cm when measured at 23°C

ex 39.02 CXIV a

Copolymer of vinyl chloride and vinyl acetate modified by maleic acid, containing not less than 85 % and not more than 88 % by weight of vinyl chloride, not less than 10.8 % and not more than 14.2% by weight of vinyl acetate and not less than 0.8 % and not more than 1.2 % by weight of maleic acid and with a residual content of vinyl chloride monomer of not more than 0.01 ppm and of which 50 grammes mixed with 150 q of distilled water and stirred for 2 hours at room temperature, gives, after filtration, a solution of which the surface tension is not more than 71.5 dynes/cm when measured at 23°C

ex 39.02 C XIV a)

Terpolymer of ethylene, methyl acrylate and a monomer containing a non-terminal carboxy group as a substituent, compounded with silica

CCT
heading
No

ex 39.02 C XIV a)

Chlorinated polyvinyl chloride in one of the forms mentioned in note 3 (b) to Chapter 39, containing by weight not less than 55 % chlorine and not less than 0.3 % tin

ex 56.01 A

Synthetic textile fibres containing not less than 85% by weight of fibres of aromatic polyamides obtained by the polycondensation of m-phenylene-diamine and isophthalic acid and not more than 15% by weight of fibres of poly(p-phenylenetere-phthalamide)

ex 70. 3 8

Spun roving of not less than 7 000 tex with a core of not less than 600 tex and not more than 1500 tex, made from continuous glass fibre, coated with epoxy resin

ex 70.20 B

Yarns of not less than 340 tex and not more than 680 tex obtained from continuous spun glass filaments having a diameter of not less than 12.5 micrometres and not more than 13.5 micrometres treated with resorcinol-formaldehyde

ex 84.18 C II b)

Apparatus, for the separation of gas from gas mixtures, of a total length of not less than 375 cm and not more than 690 cm consisting essentially of a metal cylinder, whose diameter is not less than 10.5 cm and not more than 22.5 cm, containing bundles of hollow permeable fibres

ex 84.45 C VIII b)2

Machines for cutting conical, spheroidal hypocycloid gears

ex 84.55 C

Liquid crystal display devices formed by a layer of liquid crystal between two plates of transparent material and containing 2560 display elements ranged in 16 rows and 160 columns whose dimensions do not exceed 160 x 37 x 14 mm, and bearing:

- an identification marking either consisting of the following combination of figures and letters or including this combination: H 2543
- other identification markings relating to liquid crystal displays complying with the abovementioned description

ex 84.55 C

Keyboard consisting of not less than 63 and not more than 105 switches incorporating a steel leaf spring whose dimensions are not less than 120 mm and not more than 190 mm in width+, and not less than 385 and not more than 510 mm in length

ex 85.21 D II

Electronic programmable read only memories (EPROMS) UV erasable, with a storage capacity of 32 K bits in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 17×39 mm, with a quartz window on the upper surface, and bearing:

 an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:

or

other identification markings relating to EPROMS complying with the abovementioned description

ex 85.21 D II

Random access memories (RAMS) with a storage capacity of 64 K bits, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 9 x 24 mm with 18 connecting pins, and bearing:

- an identification marking either consisting of one of the following combinations of figures or figures and letters/including one of those combinations:

or

 other identification markings relating to RAMS complying with the abovementioned description

ex 85.21 D II

C-MOS random access memories (RAMS of complementary MOS technology), with a storage capacity of 16 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17×34 mm, with 24 connecting pins, and bearing:

- an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:

5128

5516

HM 6116

6516

8416

8417

8418

or

other identification markings relating to C-MOS
 RAMS complying with the abovementioned description

CCT
heading
No

ex 85.21 D II

Cathode ray tube (CRT) controllers in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 16 x 54 mm with not more than 40 connecting pins, and bearing:

- an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:

```
2672
  3301
HD 46505
  5027
  5037
  5047
  5057
  6545
  68045
  68 A 45
  68 B 45
  8052
  8275
  8350
  9927
```

- other identification markings relating to CRT controllers complying with the abovementioned description

ex 85.21 D II

Random access memories of emitter coupled logic technology (ECL RAMS) with a storage capacity of 1 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x39 mm with not more than 24 connecting pins and bearing :

- an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those

100415

- other identification markings relating to ECL RAMS complying with the abovementioned description

combinations:

11

Description

ex 85.21 D II

Programmable non-erasable logic circuit array (Field Programmable Logic Array) of TTL Schottky technology with 48 AND functions and 8 OR functions and 16 inputs in the form of a monolithic integrated circuit 'contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with 28 connecting pins and bearing:

- an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:

or

 other identification markings relating to programmable logic arrays, complying with the abovementioned description

ex 85.21 D II

Programmable, non-erasable, logic circuit (Field Programmable Gate Array) of bipolar technology in the form of a monolithic integrated circuit with AND/NAND functions containing 16 inputs and 9 outputs contained in a housing whose dimensions do not exceed 17 x 39 mm with 28 connecting pins and bearing:

: 1

- an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:

82 S 102 82 S 103

or

 other identification markings relating to circuits complying with the abovementioned description

ex 85.21 D.II

Arithmetic logic unit (ALU) which can execute logic operations and binary arithmetic as well as decimal arithmetic operations. In addition, it can memorize the partial result and create the memory address of the system with which it holds a dialoque. It executes parity controls on data of varied length. It uses H-MOS technology in the form of a monolithic chip inserted in a 64-pin package of maximum dimensions 82.1 x 22.9 mm; this package is stamped with:

- a marking consisting of, or containing, the following letters: ALU.
- or another marking concerning an electronic chip having the abovementioned characteristics

ex 85.21 D II

3

Electronic memory control circuit which has the function of generating and memorizing the address, of managing the address jumps and the relevant priorities for carrying out diagnostic operations. It uses H-MOS technology in the form of a monolithic chip inserted in a 64-pin package of maximum dimensions 82.1 x 22.9 mm; this package is stamped with:

- a marking consisting of, or containing, the following letters: CSS
- or another marking concerning an electronic chip having the abovementioned characteristics

CCT
heading
No

ex 85.21 D II

Interface control unit between two interconnection channels and also between logic units of the system. It contains two timers for the synchronization of the dialog between the units it intercorrects. It executes diagnostic operations It uses HMOS technology in the form of a monolithic chip inserted in a 64-pin package of maximum dimensions 82.1 x 22.9 mm; this package is stamped with:

- a marking consisting of, or containing, the following letters: MIC
- or another marking concerning an electronic chip having the abovementioned characteristics

ex 90.10 A

Monolithic-block keyboard for photocopiers of maximum dimensions 238 x 56.5 x 12.5 mm with 10 keys for setting out the number of copies, 6 keys for services and a 5-digit fluorescent digital display unit, complete with wiring

ex 98.10 B

Flint wheels for use in the manufacture of non refillable gas fuelled pocket lighters

111

5. Attention is drawn to the fact that the Council Resolution of 27.6.1974 simplifying the task of the customs administrations (OJ C 79/74) requires the publication of the attached Regulation at least six weeks before its entry into force.

...

I

(Acts whose publication is obligatory)

Proposal for a

COUNCIL REGULATION (EEC)

temporarily suspending the autonomous Common Customs Tariff duties on certain industrial products

THE COUNCIL OF THE EUROPEAN COMMUNITIES,

Having regard to the Treaty establishing the European Economic Community, and in particular Article 28 thereof,

Having regard to the draft Regulation submitted by the Commission,

Whereas production of the products referred to in this Regulation is at present inadequate or nonexistent within the Community and producers are thus unable to meet the needs of user industries in the Community;

Whereas it is in the Community's interest to suspend the autonomous Common Customs Tariff duties only partially in certain cases, due particularly to the existence of Community production, and to suspend them completely in other cases;

Whereas, taking account of the difficulties involved in accurately assessing the development of the economic situation in the sectors concerned in the near future, these suspension measures should be taken only temporarily with their term of validity fixed to coincide with the interests of Community production,

HAS ADOPTED THIS REGULATION:

Article 1

The autonomous Common Customs Tariff duties for the products listed in the tables annexed to this Regulation shall be suspended at the level indicated in respect of each of them.

These suspensions shall be valid:

- from 1 July to 31 December 1982 for the products listed in Table I,
- from 1 July 198 2to 30 June 1983 for the products listed in Table II.

Article 2

This Regulation shall enter into force on 1 July 1982.

This Regulation shall be binding in its entirety and directly applicable in all Member

Done at Brussels, White the

For the Council
The President

CCT heading No	Description	Rate of auto- nomous duty (%)
ex 13.03 A V	Extract of dewaxed pyrethrum	0
ex 28.04 C III	Tellurium	0
ex 28.55 A	Phosphides of iron (ferro-phosphorus) containing by weight: — not less than 68 % and not more than 72 % of iron, — not less than 22 % and not more than 26 % of phosphorus, — not more than 3.5 % of silicon, of which not less than 99 % by weight is of a particle size of less than 20 micrometres; for the manufacture of varnishes or paints (2)	0
ex 29.01 D VII	1,3-Diisopropylbenzene with a purity of not less than 94% by weight	0
ex 29.06 A IV	2-Isopropyiphenol	0
ex 29.16 A II	L-Malic acid and its salts	0
ex 29.16 D	Methyl 5-(2,4-dichlorophenoxy)-2-nitrobenzoate	0
ex 29.21 B II	0,0-Dioctadecyl pentaerythritol bis(phosphite)	0
ex 29.21 B II	1,1'-Dimethyl-2,2'-oxydiethylene tetraphenyl bis(phosphite)	o o
ex 29.22 D I	3,5-Dichloroaniline with a purity of not less than 99 % by weight	0
ex 29.35 Q	L-Tryptophan	5
ex 29.35Q	2-Chloro-5-trifluoromethylpyridine	0
ex 29.39 D II	Methylprednisolone (INN)	8
ex 30.03 A II b)	Cisplatin (INN)	0
ex 37.02 B	Colour negative film of a width not less than 75 mm and not more than 105 mm and of a length of 100 m or more, for use in the manufacture of instant picture film packs (a)	0
ex 38.03 B	Acid activated montmorillonite which, when examined by X-ray powder diffraction, shows four principal lines corresponding to crystal interplane spacing (d values) of 0.44, 0.40, 0.33 and 0.25 nm the line corresponding to 0.40 nm being the most intense, for the manufacture of self-copy paper (*)	0

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provision.

CCT heading No	Description au no	te of to- mous ty (%)
ex 38.08 C	Rosin hydrogenated, polymerized, dimerized or oxidized	5 .
ex 38.19 G	Catalysts in the form of rodlets having a diameter of not less than 1.5 mm and not more than 9.5 mm, containing not less than 60 % by weight of diron trioxide, not less than 8% by weight of dipotassium oxide and not less than 0.5% by weight of dichromium trioxide	0
ex 38.19 G	Catalysts, in the form of granules or rings having a diameter of not less than 3 mm and more than 10 mm, consisting of silver supported on aluminium oxide, the silver content being not less than 10 % and not more than 20 % by weight	0
·ex 38.19 Х	Grains consisting of a mixture of dialuminium trioxide and zirconium dioxide containing by weight not less than 70 % and not more than 78 % dialuminium trioxide and not less than 19 % and not more than 26 % zirconium dioxide	6-7
ex 38.19 χ	Grains consisting of a mixture of dialuminium trioxide and zirconium dioxide containing by weight not less than 54 % and not more than 62 % dialuminium trioxide and not less than 36 % and not more than 44 % zirconium dioxide	6-7
ex 38.19 X	Cholic acid and 3-alpha, 12-alpha-dihydroxy-5-beta-cholan-24-oic acid (deoxycholic acid), crude	0
ex 38.19 X	Crude bile acids	0
ex 38.19 X	Reaction products containing not less than 65 % by weight of benoxaprofen (INN)	6.5
ex 39.01 C III a)	Reflecting polyester sheeting in which glass microspheres are embedded whether or not ir rolls	0
ex 39.01 C III a)	Reflecting self-adhesive sheeting made up of more than one layer of polyester, metallized, whether or not in rolls	0
ex 39.01 C V	Reflecting polyurethane sheeting whether or not in rolls	0
ex 39.02 C VI a)	Copolymer of maleic anhydride and styrene, whether or not containing a styrene-butadiene block copolymer in one of the forms mentioned in Note 3 (b) to Chapter 39	0

CCT heading No	Rate Description auto- nomou duty	s
ex 39.02 VI b)	Plates made of a copolymer consisting of maleic anhydride and styrene, also containing styrene-block copolymer, covered on both sides with a sheet of the abovementioned copolymer, modified with butadiene or pigmented	.0
ex 39.02 C VII b)	Reflecting polyvinyl chloride sheeting wholly embossed on one side in a regular pyramidal pattern, whether or not in rolls	0
ex 39.02 C XIV a ,	Copolymer of tetrafluorethylene and hexafluors propylene compounded with materials which are opaque to X-rays and containing not less than 15% and not more than 30% by weight of such materials	0 ;
ex 39.07 B V d)	Reflecting tape of a width not exceeding 105 mm consisting of a facing strip of polyvinyl chloride embossed in a regular pyramidal pattern, heat sealed, in parallel lines or a grid pattern to a backing strip of plastic material, or of knitted or woven fabric covered on one side with plastic material, whether or not on rolls	0
ex 51.01 A	Yarn of poly(p-phenyleneterephthalamide), for uses other than the manufacture of tyres or of products used in the manufacture of tyres (a)	2

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ex 56.01 A and cx 59.01 B I	Fibres of poly(p-phenyleneterephthalamide)	2
ex 56.01 A	Textile fibres exclusively of aromatic polyamides obtained by the polycondensation of m-phenylene=diamine and isophthalic acid, for uses other than the manufacture of articles falling within Chapters 60, 61, 64 and 65 or of materials used in the manufacture of such articles (a)	0
ex 56.01 A	Synthetic textile fibres containing not less than 85% by weight of fibres of aromatic polyamides obtained by the polycondensation of m-phenylenediamine and isophthalic acid and not more than 15% by weight of fibres of poly(p-phenyleneterephthalamide) for uses other than the manufacture of articles falling under Chapters 60, 61, 64 and 65 or of materials used in the manufacture of such articles	ti o
ex 56.01 A	Synthetic textile fibres containing not less than 85% by weight of fibres of aromatic polyamides obtained by the polycondensation of m-phenylenediamine and isophthalic acid and not more than 15% by weight of fibres of poly(p-phenyleneterephthalamide) for uses other than the manufacture of articles falling under Chapters 60, 61, 64 and 65 or of materials used in the manufacture of such articles	7
ex 58.01 B	Carpets, carpeting and rugs, of silk or of waste silk other than noil, of which the pile contains not less than 85 % by weight of silk or waste silk other than noil (b)	18,2 maximum o 3,8UCE/m2
ex 59.03	Bonded-fibre fabrics and similar bonded yarn fabrics of aromatic polyamide manmade fibres obtained by polycondensation of m-phenylenediamine and isophthalic acid	0
ex 59.03	Bonded-fibre fabrics, with a thickness of not more than 300 micrometres, of spun- bonded polyethylene fibres, with a weight not exceeding 115 g/m ² , whether or not in rolls	0
•		
ex 59.08	Knitted or woven fabric coated or covered on one side with artificial plastic material in which are embedded glass microspheres	0
ex 70.20 A	Mats of npn-textile glass fibres of a weight per square metre of a not more than 100 g and a fibre diameter of not more than seven micrometres	0
ex 81.04 G I	Electrolytic manganese of a purity of at least 99.7 % by weight for the production of non-ferrous alloys	a

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.(b) The Additional Note to Chapter 58 shall apply here

CCT heading No	Description	Rate of auto nomous duty (%
ex 84.51 A	Typewriters with Braille characters	. 0
ex 84.51 A	Electronic pocket communicators for handicapped persons which, by means of push buttons and printing thermic head, print and issue text on tape	0
ex 84.51 A	Portable machine for reading and writing Braille with tactile read-out and magnetic tape cassette recording systems, microphone and speaker, equipped with a standard electromechanical Braille typewriter keyboard and an electro-mechanical Braille read-out unit with 20 characters, all contained in a case measuring 24 × 36 × 11 cm	
ex 84.55 C	Parts and accessories of electronic pocket communicators for handicapped persons which, by means of push buttons and printing thermic head, print and issue text on tape	0
ex 84.55 C	Opto-electric encoder for electronic typewriters consisting of electronic circuits, a light-emitting diode (LED), a rotating disc with radial openings, a fixed mask and a single chip photovoltaic cell, contained in two plastic shells forming a housing of a size not exceeding 60 × 48 × 16 mm	0
ex 85.03	Dry (zinc/carbon batteries of a voltage of not less than 5.5 and not more than 6.5 and of a size not exceeding 110 x 90 x 5 mm, for incorporation in film cassettes for instant pictures (a)	0 '
ex 85.21 A V	Digital displays in the form of a tube consisting of a glass housing mounted on a board whose dimensions do not exceed 350 × 300 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metalised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0
ex 85.21 A V	Colour cathode-ray tubes, using shadow mask, in-line technology in which images are displayed on a screen with a useable surface not exceeding 165 x 165 mm for use in electronic flight instrument, warning and systems displays (*)	0
•		

⁽a) Control of the used for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No

Description

Rate of autonomous duty(%)

ex 85.21 D I

Wafers not yet cut into chips containing exclusively test chips and other monalithic integrated circuits, the latter consisting of an arithmetical unit with a capacity of 4 bits plus a read only memory (ROM) with a capacity not not less than 18K bits and not more than 65 K bits and a radom access memory (RAM) with a capacity of not less than 512 bits and not more than 4 K bits for the manufacture of single-chip micro-computers contained in a housing whose exterior dimensions do not exceed 16 x 54 mm with not more than 40 connecting pins and bearing:

 an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:

CD 3200 to 3299
TMC 0270 to 0279
TMC 0500 to 0599
TMC 0980 to 0989
TMC 1500 to 1599
TMC 1980 to 1999
TMC 0310 to 0329
TP 0450 to 0459
TP 0480 to 0489
TP 0500 to 0599

or

 other identification markings relating to the microcomputers concerned manufactured from monolithic integrated circuits complying with the abovementioned description (a)

ex 85.21 D II

Digital displays, not incorporating a decoder, of a size not exceeding 25 x 35 mm, consisting of a printed circuit board on which are mounted, under a transparent plastic cover, up to 22 light-emitting diodes manufactured from gallium-based semi-conductor compounds. Each display consists of a single character with or without a plus or minus sign and/or one or two dots

0

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of auto-
NO		nomous duty (%)
ex 85.21 D II	Digital displays, consisting of a printed circuit board of a size not exceeding 35 × 90 mm with a single line of characters not less than two in number comprising light-emitting diodes made from gallium-based semi-conductor compounds mounted thereon. Each character is composed of up to eight segments and the line of characters has a protective cover of transparent plastic	0
ex 85.21 D II	Digital displays consisting of a printed circuit board of a size not exceeding 35 × 90 mm with a single line of digits, not less than three in number comprising light-emitting diode manufactured from gallium-based semi-conductor compounds mounted thereon. Each digit is composed of seven segments plus a decimal point and the line of digits has a protective cover of transparent plastic	1
ex 85.21 D II	Programmable non-erasable read only memories (PROMS) of Schottky TTL technology with a storage capacity of 1 K bit, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 9 x23 mm, with 16 connecting pin and bearing:	4 1 ,
·	- an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:	
	14 S 10 24 S 10 24 SA 10	
	247 A 10 27 S 20 27 S 21	
	29760 29761	
	38510 5300 5301	
	53 S 140 53 S 141 54 S 287 54 S 387	
	54700 5603 5623	
	6300 6301 63 S 140	
	63 S 141 7052 7057	
	74 S 287 74 S 387 7610	
	7611 82 S 126 82 S 129	
	8520 8521 93417 93427	
	or	1
	<pre></pre>	1

CCT heading No	Description	Rate of auto- nomous duty (%)
ex 85.21 D II	Programmable non-erasable read only memories (PROMS), of Schottky TTL technology, with a storage capacity of 2 K bits, in the form of a momolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x39 mm, with not more than 24 connecting pins and bearing:	
	 an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: 	
	27 S 12 27 S 13 28 L 22 28 LA 22 29613 29770 29771 38510 5305 5306 5308 5309 53 S 240 53 S 241 54 S 570 54 S 571 5604 5624 6305 6306 6308 6309 63 S 240 63 S 241 6335 6336 7053 7058 74 S 570 74 S 571 76 LS 03 7620 7621 82 S 114 82 S 130 82 S 131 93 436 93446	
	orother identification markings relating to	
	PROMS complying with the above- mentioned description	11.5

CCT heading No	1 .	Descr	ription	Rate of auto- nomous duty (%)
	Programmable, non- 4 K bits in the form exterior dimensions pins, and bearing: — an identification	of a monolist do not excee marking eithe	I only memories (PROMS) with a storage capacity of thic integrated circuit contained in a housing whose of 17 × 39 mm, with not more than 24 connecting er consisting of one of the following combinations of rincluding one of those combinations: 74 \$ 472 74 \$ 473 74 \$ 474 74 \$ 475 74 \$ 477 74 \$ 572 74 \$ 573 7640 7641 7642 7643 7644 7645 7647 7648 7649 82 HS 137 82 HS 147 82 \$ 115 82 \$ 136 82 \$ 137 82 \$ 140 82 \$ 141	nomous
	28 SA 46 29620 29621 29622 29623 29624 29625 29626 29627 3604 3624 3625 or - other ider	6349 6350 6351 6352 6353 6641 7054 7059 7121 7122 7123 7125 7126	82 S 146 82 S 147 93 438 93 448 93 452 93 453 on markings relating to PROMS abovementioned description	8.5

Common Customs Tariff heading No	(Description		Rate of autonomou duty (%)	
ex 85.21 D II	8 K bits in the for exterior dimension pins, and bearing: — an identificatio	m of a monolith is do not exceed in marking either	ic integrated circuit 17 × 39mm, with	OMS) with a storage of contained in a house not more than 24 of the following combines combinations:	connecting	
	24 S 81 24 S 86 24 S 86 27 S 180 27 S 181 28 L 85 28 L 86 28 P 85 28 R 85 28 S 2708 28 S 85 28 S 86 29 630 29631 29634 29635 29636 29637 or — other identifica	29650 29651 29652 29653 3628 5380 5381 54 LS 478 54 S 2708 54 S 454 54 S 455 54 S 479 6380 6381 7050 7127 7128 7129 7130 7131 7132	74 LS 478 74 S 2708 74 S 454 74 S 455 74 S 478 74 S 479 7608 7680 7681 7684 7685 7686 7687 7688 7689 77 S 180 77 S 181 77 S 184 77 S 185 77 S 186 77 S 187	TBPS 81 M 82707 82708 82 LS 180 82 LS 181 82 S 180 82 S 181 82 S 182 82 S 183 82 S 184 82 S 185 82 S 2708 87 S 180 87 S 181 87 S 184 87 S 184 87 S 185 87 S 186 87 S 187 93450 93451 93460 93461 93465 93 L 450 93 L 451 9460 Inplying with the above	mentioned	
ex 85.21 D II	Programmable nor 16 K bits, in the fexterior dimension pins and bearing: - an idention of the fo	n-erasable read of orm of a monoling so not exceed fication managed fication managed fication managed fication managed fication f	only memories (PRO thic integrated circuit i 17 × 39 mm, with marking eithe mbinations of or includin M Si N Si N Si D	MS) with a storage of the contained in a house in not more than 24 der consisting of figures or ng one of tho M 7616-5 M 77 S 190 M 77 S 191 IM 82 S 190 S 82 S 190 M 82 S 191 M 87 S 190 M 87 S 191 M 87 S 190 M 87 S 191 M 87 S 190 M 87 S 191 M 87 M 8	capacity of sing whose connecting	•
	7138 HM 76 16 HM 76 16 HM 76 16 HM 76 16	0 - 5 1 - 2				

HM 76 16-2

CCT	Description	Rate
heading No		of autonomous duty (%)
ex 85.21 D II	or - other identification marking relating to PROMS complying with the abovementioned description Electronic programmable read only memories (EPROMS) UV erasable, with a storage capacity of 64 K bits in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 17 × 39 mm, with a quartz window on the upper surface, and bearing: - an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:	4
	2764 68764 68766 2564 68 A 764 or 68L 64 68 L 764 — other identification markings relating to EPROMS complying with the abovementioned description	0
ex 85.21 D II	N-MOS static random access memories (Static RAMS of N-MOS technology), with a storage capacity of 8Kbits in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with not more than 26 connecting pins and bearing:	
	 an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: 	
	4008 4118 PD 421 4801 4808 8104 8108 8112 8114 8185	
	or - other identification markings relating to N-MOS Static RAMS complying with the above- mentioned description	0
ex 85.21 D II	Static random access memories of N-MOS technology (N-MOS Static RAMS) with a storage capacity of 2 K x 8 bits in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with 24 connecting pins and bearing:	
	an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:	

	Description	. Rate
heading No	<i>5</i>	of auto- nomous duty (%)
	TMM 2016	
	2128	
	3528	
	TMS 4016	
	4802	
	58725 . 8128	
	or	
	w Other identification mankings no lating to	
	 other identification markings relating to N-MOS Static RAMS complying with the 	
	abovementioned description	8.5
		0.5
		4
k 85.21 D Ⅱ	Static random access memories, of N-MOS technology (N-MOS Static RAMS), with a	•
	storage capacity of 16 K × 1 bit, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 × 39 mm with 20 or 24 connecting pins and bearing:	
	- an identification marking either consisting	
	of one of the following combinations of	
	figures or figures and letters or including	
	one of those cominations :	. :
	2167	
	IMS 1400	
	58757	,
	8167	
	other identification markings relating to N-MOS Static RAMS complying with the above description	0
x 85.21 D II	Random access memories of emitter coupled logic technology (ECL RAMS) with a storage capacity of 16 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 11 × 31 mm, with 20 connecting pins and bearing:	
	- an identification marking either consisting of one of the following combinations of figures or	
	figures and letters or including one of those combinations:	
	F 10480 100480	
	or	•
	- another identification markings relating to	
	ECL RAMS complying with the abovementioned description	0
85.21 D II	Single-chip microcomputer, in the form of a monolithic integrated circuit, consisting of an arithmetical unit with a capacity of 4 bits plus a read only memory (ROM) with a capacity of not less than 18 K bits and not more than 65 K bits and a random access memory (RAM) with a capacity of not less than 512 bits and not more than 4 K bits, contained in a housing whose exterior dimensions do not exceed 16 × 54 mm with not more than 40 connecting	
	pins .	1

CCT neading **No**

Description

Rate of autonomous duty(%)

ex 85.21 D II (cont'd)

- an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:

CD 3200 to 3299
TMC 0270 to 0279
TMC 0500 to 0599
TMC 0980 to 0989
TMC 1500 to 1599
TMC 1980 to 1999
TP 0310 to 0329
TP 0450 to 0459
TP 0480 to 0489
TP 0500 to 0599

or

 other identification markings relating to microcomputers complying with the abovementioned description

0

ex 85.21 D II

Single chip microcomputer in the form of a monolithic integrated circuit consisting of an arithmetical unit with a capacity of 8 K bits, a 12 bit timer, an internal clock, a read only memory (ROM) with a capacity of 32 K bits and a random access memory (RAM) with a capacity of 1 K bits, with 48 input/output gates and contained in a housing whose exterior dimensions do not exceed 16.5 × 42 mm, with 64 connecting pins

The package bears:

the following combination of figures and letters or including this combination:

PD 7801

or

 other identification markings relating to microcomputers complying with the abovementioned description

CCT heading No	Description	Rate of auto- nomous duty (%)
·		
ex 85.21 D II	P-MOS 12/24-hour clock circuit incorporating an elapsed time facility, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 53 x 14 mm, with 40 connecting pins, for the manufacture of instrument panel clocks and clocks of a similar type for vehicles (a).	
	The package bears :	
	- an identification marking either consisting of the following combination of figures and letters or including this combination :	
	MM 53124 .	
	or ·	
	- other identification markings relating to clock circuits complying with the abovementioned description integrated	0.
ex 85.21 D II	i — — — — — — — — — — — — — — — — — — —	†

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of auto- nemous duty (%)
	 The package bears: an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: 	
	 V 35 C 05 or other identification markings relating to amplifiers complying with the abovementioned 	
ex 85.21 D II	N-MOS static random access memories (Static RAMS of N-MOS technology), with a storage capacity of 1 K bits in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with not more than 24 connecting pins and bearing:	0
	 an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: 	
	M 120 2101 21 H 01 2102 21 L 02 2111 21 H 11 21 H 12 2115 21 L 15 2125 21 L 25 2148 TMM 313 6508 6810 68 A 10 68 B 10 7714 8101 8111 9101 91 L 01 9102 91 L 02 9111 91 L 11 9112 91 L 12	

CCT heading No	Description	Rate of auto- nomous duty (%)
95 24 D TT	or - other identification markings relating to N-MOS Static RAMS complying with the above- mentioned descriptions Static random access memory of TTL technology	0
ex 85.21 D II	(TTL SRAM) with a storage capacity of 1 K bits, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 30 x 16 mm with not more than 22 pins and bearing:	
	—an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:	
	2205 2510 2511 74 L'S 214	
	74 LS 215 74 LS 314 74 S 207 74 S 208 74 S 214 74 S 314	
	93 412 93 L 412 93415 93 L 415	
•	93422 93 L 422 93425 93 F 425 93 L 425	
	or)
	 other identification markings relating to TTL Static RAMS complying with the above- mentioned description 	,

CCT heading No	Description	Rate of auto- nomous duty (%)
ex 85.21 D II	Monolithic integrated circuit consisting of eight independent elements capable of controlling the 8 segments and or characters of fluorescent or gas discharge displays contained in a housing whose exterior dimensions do not exceed 7 x 23 mm with 18 connecting pins and bearing:	
	- an identification marking either consisting of one of the following combinations of figures or including one of those combinations:	
	513 514 534 594 6118 6128 6138	,
11 + 4 − \$1	or - other identification markings relating to circuits complying with the abovementioned description	0
ex 90.19 A III	Vascular prostheses with an internal diameter of less than 6 mm	O [']
ex 90.19 B I	Head-phones for hearing aids, contained in a housing whose external dimensions do not exceed 6.5 x 4.5 x 3.2 mm	0
ex 90.19 B II	Reading appliances for the blind, in which a miniature camera using photo- transistors transmits letters onto a scanning board with piezo-electric pencils, and its parts and accessories	0
ex 90.20	Apparatus for the irradation of biological samples incorporating permanently shielded caesium 137 radioactive sources, an exposure chamber whose volume does not exceed 930 cubic centimetres, an electrically driven turntable and a digital timer	0

CCT heading No	Description	Rate of auto- nomous duty (%)
ex 27.13 B II	Synthetic paraffin wax having a molecular weight of not less than 460 and not more than 1 560	0
`ex 28.04 B	Helium	0
ex 28.13 IJ	Tellurium dioxide	. О
·	Chromium dioxide	
ex 28.21		· .
ex 28.31 C	Lithium hypochlorite	. 0
ex 28.38 C	Potassium hydrogenperoxomonosulphate	0
ex 28.39 A	Potassium nitrite for the manufacture of cooling and cutting fluids used in the working of metal or metal carbides (a)	0
ex 28.40 B II	pentaCalcium hydroxide tris(orthophosphate) for use in non-ferrous metallurgy (a)	0
ex 28.42 A VI	Lithium carbonates not corresponding to the following specifications:	
	— In the form of white powder	
	— Containing 98.5 % or more of Li ₂ CO ₃ and:	· · ·
	— Less than 2 ppm of arsenic	,
	— Less than 200 ppm of calcium	
, ,	— Less than 200 ppm of chlorides	
	— Less than 20 ppm of iron	
	— Less than 150 ppm of magnesium	' '
	— Less than 20 ppm of heavy metals	,
	Less than 300 ppm of potassium Less than 300 ppm of sodium	}
	- Less than 200 ppm of sulphates	0
28.46 A I b)	Sodium borates, anhydrous	0
28.40 A 1 b)	Socium boraces, annydrous	
ex 28.47 C.	Potassium permanganate	0
ex 28.47 F	Calcium wolframate, for the manufacture of ferro-alloys or deca-ammonium 41-oxododecawolframate (ammonium paratungstate) (a)	0
ex 28.48 B III	Hydrotalcite (INN)	0
ex 28.48 B III	tetraaluminium nonamagnesium dicarbonatehexacosa= hydroxide	0

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT Description heading No	Rate of auto- nomous duty (%)
Deuterium, deuterium oxide (heavy water) and other compounds of deuterium; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products (Euratom)	0
ex 28.57 A Silane (silicon hydride)	0
ex 28.57 B Manganese nitride containing not more than 8 % of nitrogen by weight	0
ex 29.01 C I beta-Pinene	0
ex 29.01 D VII Vinyltoluenes	0
ex 29.01 D V II Tricyclo 8.2.2.2 ^{4,7} hexadeca-1(12),4,6,10,13,15-hexaene	0
ex 29.02 A I Carbon tetrafluoride (tetrafluoromethane)	0
ex 29.02 A II b) 1,2,3-Trichloropropenes	0
ex 29.02 A III Vinyl bromide	0
ex 29.02 A III 1,2-Dibromoethane	4
ex 29.02 A V Bromochloromethane	0 .
ex 29.02 B 1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo [12.2.1.1.6,9.0 ^{2,13} .0 ^{5,10}] octadeca-7,15-diene, for use in the manufacture of polyamide (a)	0 .
ex 29.02 C Dichlorotricyclo/8.2.2.2 ^{4,7} /hexadeca-1(12),4,6,10, 13,15-hexaene, mixed isomers	0
ex 29.02 C Tetrachlorotricyclo 8.2.2.2 4,7 hexadeca-1(12),4, 6,10,13,15-hexaene, mixed isomers	0
ex 29.03 A Methanesulphonic acid	0
ex 29.03 B II Nitromethane	0 .
ex 29.03 B II 1-Nitropropane,	0
ex 29.03 B II 2-Nitropropane	. 0
ex 29.03 B II Nitroethane	0
ex 29.03 C I Methanesulphonyl chloride	0
ex 29.04 A III 2-Methylpropan-2-ol(tert-butyl alcohol) with a purity of not less than 90 % but not more than 96 % by weight	0
ex 29.04 C I Butane-1,3-diol ex 29.04 C I 2,4,7,9 -Tetramethyldec-5-yne-4,7-diol	0
ex 29.04 C V 2,2-Bis(bromomethyl)propanediol	0

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of auto- nomous duty (%)
ex 29.05 A II	(<u>+</u>)-Menthol	0
, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
ex 29.06 B V	4,4'-(2,3-Dimethyltetramethylene)dipyrocatechol, not less than 98 % pure	0
ex 29.06 B V	6,6',6"-Tri-tert-butyl-4,4',4"-(1-methylpropan-1-yl-3-ylidene); ri-m-cresol, whether or not containing toluene of crystallization	0
ex 29.06 B V	2,5-Di(tert-pentyl)hydroquinone	0
ex 29.07 C III	2,4-Dinitro-6-octylphenol	0
ex 29.08 A III c)	Bis(phenoxyphenoxy)benzene, mixed isomers	0
ex 29.08 A III c)	Sodium 4-(2-methylallyloxy)benzenesulphonate	0
ex 29.08 A III c)	2-Bromo-6-methoxynaphthalene	0
ex 29.09 B	1,2-Epoxybutane	7
ех 29.13 А І	5-Methylhexan-2-one	0
ex 29.13 A I	3,3-Dimethylbutanone	. 0
ex 29.13 B I b)	Refined natural bornan-2-one(camphor)	, 0
ex 29.13 D I b)	3-beta-Hydroxy-16-alpha-methylpregn-5-en-20-one	6
ex 29.13 D I b)	11-alpha,17,21-Trihydroxy-16-beta-methylpregna-1,4-diene-3,20-dione	0 .
ex 29.13 E	4-Methoxy-4-methylpentan-2-one	0
ex 29.13 F	1,4-Naphthoquinone	0
ex 29.13 G II	1-Chloro-3,3-dimethylbutanone	0
ex 29.14 A II c) 4	16-alpha,17-alpha-Epoxy-20-oxopregn-5-en-3-beta-yl acetate	6
ex 29.14 A II c) 4	11-alpha,17-alpha,21-Trihydroxy-16-alpha-methyl-5-alpha-pregnane-3,20-dione 21-acetate 11-(toluene-4-sulphonate)	9
ex 29.14 A II c) 4	20-Oxopregna-5,16-dien-3-beta-yl acetate	0
ex 29.14 A XI	2,2'-Ethylenedioxydiethyl bis(2-ethylbutyrate)	0
ex 29.14 B IV b)	Lutyl perchlorocrotonate	0
29.15 A IV a)	Azelaic acid and sebacic acid	0.

CCT heading No	Description	Rate of auto- nomous duty (%)
ex 29.15 B	1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn- 5-ene-2,3-dicarboxylic anhydride (chlorendic anhydride)	0 ·
ex 29.15 C III	Benzene-1,2,4-tricarboxylic acid	. 0
ex 29.15 C III	Benzene-1,2,4,tricarboxylic acid 1,2-anhydride	0
ex 29.15 C III	Tetrachlorophthalic anhydride	0
ex 29.15 C III	Benzyl 3-isobutyryloxy-1-isopropyl-2,2-dimethylpropyl phthalate	о о
ex 29.15 C III	Tetrabromophthalic anhydride	0
ex 29.16 A VIII a)	2,2-Bis(hydroxymethyl)propionic acid	0
ex 29.16 B VI	Octadecyl-3-(3,5-di-tert-butyl-4-hydroxphenyl)propionate	٥
ex 29.16 B VI	Pentaerythritol tetrakis[3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate]	o
ex 29.16 D	Dinoprostone (INN)	0
ex 29.16 D	Alprostadil (INN)	0
ex 29.19 C	2,2-Bis(chloromethyl)trimethylene tetrakis(2-chloroethyl) bis(phosphate)	5
ex 29.19 C and ex 38.19 X	Tetrakis(2-chloroethyl) ethylene bis(phosphate)	5
ex 29.22 A III	tert-Butylamine	0
ex 29.22 A III	1,1,3,3-Tetramethylbutylamine	O
ex 29.22 B II	N, N, N', N'-Tetrabutylhexamethylenediamine	0
ex 29.22 E II	1,8-Naphthylenediamine	. 0
ex 29.22 E II	m-Phenylenebis(methylamine)	0
ex 29.23 A II	Dinoprost(INN), Trometamol salt (INN)	0
ex 29.23 A II	(+)-4-Dimethylamino-3-methyl-1,2-diphenylbutan-2-ol	0
ex 29.23 A II	1-Deoxy-1-(octylamino)- <u>D</u> -glucitol	0
ex 29.23 B II	Dobutamine (INN) and its salts	0
ex 29.23 C	Ketamine hydrochloride (INNM)	0
ex 29.23 D V	Tranexamic acid (INN)	0
ex 29.23 D V	beta-Alanine	0
ex 29.23 E	4-(2-Hydroxy-3-isopropylaminopropoxy)-2,3,6-trimethylphenyl acetate	. 0
ex 29.23 É	Methyldopa (INN)	0

CCT heading No	Description	Rate of auto- nomous duty (%)
ex 29.23 E	Diethyl 1,3-benzodioxol-5-ylaminomethylenemalonate	0
ex 29.23 E	6-Acetyl-1,3-benzodioxol-5-ylammonium chloride	Ο.
ex 29.23 E	Levodopa (INN)	0
ex 29.23 E	Nadolol (INN)	0
ex 29.25 A II	N-Acetyl- <i>DL</i> -valine	0
ex 29.25 A II	(3-Methacrylamidopropyl)trimethylammonium chloride	· 0
ex 29.25 A II	2-Acrylamido-2-methylpropanesulphonic acid	0
29.25 B II a)	Phenobarbital (INN) and its salts	11
ex 29.25 B II c)	Barbituric acid	C
ex 29.25 B III b)	Z-Benzoyl-4'-chloro-N-(2-hydroxypropyl)glycinanilide	0
ex 29.25 B III b)	Bendiocarb (ISO)	0
ex 29.27	(—)-N-(alpha-Cyano-4-hydroxy-3-methoxy-alpha-methylphenethyl)acetamide	0
ex 29.27	2-(3-Phenoxyphenyl)propiononitrile	0
ex 29.27	Octocrilene (INN)	0
ex 29.29	20-Hydroxyiminopregna-5,16-dien-3-yl acetate	0
ex 29.29	Carbidopa (INN)	0
ex 29.29	Robenidine hydrochloride (INNM)	0
ex 29.29	N, N-Diethylhydroxylamine	0
ex 29.29	3,3'-Bis(3,5-di-tert-butyl-4-hydroxyphenyl)-N,N'-bipropionamide	0
ex 29.30	0,0-Bis(4-tert-butylphenyl) N-cyclohexylphosphoramidothioate	0
ex 29.30	Methyl isocyanate	9
ex 29.30	Methylenedicyclohexyl di-isocyanate, mixed isomers	o
ex 29.31 B	2-Methyl-2-(methylthio)propionaldehyde oxime	0
ex 29.31 B	Thiophenol	0
ex 29.31 B	Tolnaftate (INN)	0
ex 29.31 B	2,2'-Thiodiethyl bis[3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate]	, 0
·		

CCT heading No	Description	Rate of auto- nomous duty (%)
ex 29.31 B and ex 38.19 X	Biosynthetic peptide having the structure of the 'A' chain of human insulin, in the form of a salt of the S-sulphonate derivative	0
ex 29.31 B	4,4'-Sulphonyldiphenol with a purity of not less than 99.5 % by weight	0
ex 29.34 C	Crystalline dimethyltin dichloride in the form of powder, for the production of goods falling within Chapter 70 (a)	0
ex 29.34 C	2-Chloroethylphosphonic acid	7,-6
ex 29.34 C	2-Diphenylphosphinobenzoic acid	0
•		
ex 29.35 Q	2-Benzotriazol-2-yl-4-(1,1,3,3-tetramethylbutyl)phenol	0
ev 29.35 Q	2-Benzotriazol-2-yl-p-cresol	0
es 29,35 Q	2,6-Di-tert-butyl-4-[4,6-bis(octylthio)-1,3,5-triazin-2-yl-amino]phenol	0
ex 29.35 Q and ex 30 03 A II b)	Butorphenol (INN) and its salts	0
ex 29,35 Q	()-1-tert-Butylamino-3-(4-morpholino-1,2,5-thiadiazol-3-yloxy)propan-2-ol	0
es 29.35 Q	Clotiazepam (INN)	0 -
ex 29.35 Q	1,4-Diazabicyclo[2.2.2]octane (triethylenediamine)	0,
ex 29.35 Q	2,4-Di-tert-butyl-6-(5-chlorobenzotriazol-2-yl)phenol	0,
ex 29.35 Q	Carpipramine dihydrochloride (INNM)	0
ex 29.35 Q	2,3-Dihydro-2,2-dimethylbenzofuran-7-ol	0
ex 29.35 Q	1-Ethyl-1,4-dihydro-4-oxo[1,3]dioxolo[4,5-g]cinnoline-3-carbonitrile	. 0
ex 29.35 Q	Diphemanil metilsulphate (INN)	0
ex 29.35 Q	Orazamide (INN)	0
ex 29.35 Q	(25R)-Spirost-5-en-3-beta-ol(diosgenin) and its esters	0 -
		1
ex 29.35 Q	4-Nitrobenzyl 7-amino-3-chloro-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylate and its salts	0
ex 29.35 Q	Azatadine dimaleate (INNM)	٥
ex 29.35 Q	Amprolium hydrochloride (INNM)	0
ex 29.35 Q	2-(4-Pyridyl)ethanesulphonic acid	0 -
ex 29.35 Q	Prifinium bromide (INN)	, 0
ex 29.35 Q	Glucurolactone (INN)	0

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.35 Q	2-Chlorodibenz[b,f][1,4]oxazepin-11(10H)-one	0
ex 29.35 Q	2,3,5,6-Tetrachloropyridine	0
ex 29.35 Q	Diltiazem hydrochloride (INNM)	ó
ex 29.35 Q	(6R,7R)-3-Acetoxymethyl-7-[(R)-2-formyloxy-2-phenylacetamido]-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid and its salts and esters	0
ex 29.35 Q and ex 30.03 A II b)	Buspirone hydrochloride (INNM)	0,
29.35 Q and ex 30.03 A II b)	Encainide hydrochloride (INNM)	0
ex 29.35 Q-and	5-Bromopyrimidine	0
ex 38_19 X ex 29.35 Q	Minoxidil (INN)	0
ex 29.35 Q	Triazolam (INN)	0
ex 29.35 Q ex 29.35 Q	Biosynthetic peptide having the structure of the 'B' chain of human insulin, in the form of a salt of the S-sulphonate derivative Diazoxide (INN)	0
ex 29.35 Q	(6R,7R)-7-Amino-3-(5-methyl-1,3,4-thiadiazol-2-ylthiomethyl)-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid and its salts	0
ex 29.35 Q	Tolmetin sodium (INNM)	0
ex 29.35 Q	Captopril (INN).	0
ex 29.35 Q	 Flunixin meglumine (INNM)	ľ 1 0
ex 29.36	Quinethazone (INN)	0
ex 29.36	Sulfaguanidine (INN)	0
ex 29.36	Sulfathiazole (INN)	0
ex 29.36	4-Chloro-5-sulphamoylanthranil-o-toluidide	. 0
ex 29.38 A	Nicotinic acid (INN)	.0

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.38 B II	Panthenol (INN)	0
ex 29.38 B III	Folic acid (INN)	0
ex 29.38 B V	Nicotinamide (INN)	0
ex 29.39 C I	Serum gonadotrophin (INN)	. 0
ty 29.39 D II	Betamethasone 17,21-dipropionate (INNM)	0
ex 29.39 D II	Triamcinolone hexacetonide (INN)	6.6
ex 29.39 D II	Diflorasone di(acetate) (INNM)	0
ex 29.39 E	Calcitonin (INN), salmon-type and its salts	0
ex 29.39 E	Prasterone (INN)	0
ex 29.39 E	Calcitonin (INN), porcine	0
ex 29.41 D	Purified mixture of glycosides from the fermentation of Streptomyces avermitilis	0
ex 29.42 C VII	Pilocarpine hydrochloride	0
ex 29.42 C VII	Pilocarpine nitrate	·o
ex 29.42 C VII	(22R,25R)-Tomat-5-enin-3-beta-ol (Solasodine)	0
ex 29.42 C _. VII	Vindesine sulphate (INNM)	0
ex 29.43 B	Ribose	0
ex 29.43 B	Sucralfate (INN)	0
ex 29.44 A	Epicillin (INN)	0
ex 29.44 A and ex 30.03 A Ii a M	Piperacillin sodium (INNM)	0
ex 29.44 C and ex 30.03 A II b)	Amikacin (INN) and its salts	0
ex 29.44 C	Amphotericin B (INN)	0.
ex 29.44 C	Minocycline mono-hydrochloride dihydrate (INNM)	0
ex 29.44 C	Clindamycin (INN) and its salts and esters	
ex 29.44 C	Spectinomycin dihydrochloride pentahydrate (INNM)	0
ex 29.44 C	Gentamicin (INN) and its salts	. 0
ex 29.44 C	Nystatin (INN)	0
ex 29.44 C and ex 30.03 A II b)	Bleomycin sulphate (INNM)	. 0

CCT heading No	Description /	Rate of autonomous duty (%)
ex 29.44 C	Sisomicin sulphate (INNM)	0
ex 29.44 C	Spectinomycin sulphate (INNM)	0
ex 29.44 C	Tobramycin (INN) and its salts	0
ex -29.44 C	Lincomycin (INN) and its salts and esters, for the manufacture of products falling within heading No 30.03 (a)	. 0
ex 29.44 C	Monensin (INN) and its salts	o
ex 29.44 C	Cefaclor (INN) and its hydrates, salts and esters	0
ex 29.44 C	Fumagillin dicyclohexylammonium (INNM)	0
ex 29.44 C	Netilmicin sulphate (INNM)	0
ex 29.44 C	Dibekacin sulphate (INNM)	0
ex 29.44 C	Cefoxitin sodium (INNM)	0
ex 29.44 C	Cefradine (INN)	0
ex 29.44 C	Cefamandole (INN) and its salts and esters	Ö
ex 29.44 C	Cefazolin (INN) and its salts	. 0
ex 29.44 C	(6R,7R)-7-[2-Carboxy-2-(4-hydroxyphenyl)acetamido]-7-methoxy-3-(1-methyl-1H-tetrazol-5-ylthiomethyl)-8-oxo-5-oxa-1-azabicyclo[4.2,0]oct-2-ene-2-carboxylic acid and its salts and esters	0
ex 29.44 C	Josamycin (INN)	0
ex 29.44 C	Josamycin propionate (INNM)	0
ex 29.45	Potassium <u>tert-</u> butoxide	0
ex 30.01 A	Bovine livers for organotherapeutic purposes, dried	0
ex 30.01 B II	Extracts of liver of bovine animals	0
ex 30.01 B II	Extracts of suprarenal glands	0
ex 30.01 B II and ex 90.19 A III	Bioprosthetic heart valves	O
ex 30.02 A	Tetanus immunoglobulin	. 0
ex 30.02 A	Anti-tetanus immunoplasma	0
ex 30.02 A	German measles immunoplasma	0
ex 30.02 A	Mumps immunoplasma	0
ex 30.02 A	Whooping-cough immunoplasma	,0
ex 30.02 A	Rabies immunoplasma	0

CCT heading No	· Description	Rate of autonomous duty
ex 30.03 A II b) B II b)	Human albumin, whether or not in solution	0
ex 30.03 A II b) B II b)	Human fibrinogen	0
ex 30.03 A II b) B II b)	Preserved serum prepared on a basis of human blood	0
ex 30.03 A II b) B II b)	Anti-haemophilic globulin and anti-P(D)-globulin derived from human blood	0
ex 30.03 A II b)	Mixture of oestrogens, of equine origin in powder form	0
ex 30.03 A II b	Mitomycin (INN)	. 0
ex 30.03 B II b)	Gamma-globulin, in solution, derived from human blood	0
ex 30.03 B II b)	Lyophilized gamma-globulin derived from human blood	0
32.01 A I	Tanning extracts of wattle (mimosa)	0
ex 32.01 A IV	Tanning extracts derived from gambier and myrobolan fruits	0
ex 32.01 A IV	Tanning extracts of eucalyptus	3.2
ex 32.07 B	Inorganic colouring matter preparations mentioned in Note 3 to Chapter 32, in hollow polyurethane spheres having a diamater of less than 200 micrometres	0
ex 32.08 D	Glass in the form of flakes of a length not less than 0.1 mm and not more than 3.5 mm of a thickness not less than two and not more than five micrometres	0
ex 32.09 A II and ex 39.01 C V	Polyurethane of 2,2'-(tert-butylimino)diethanol and 4,4'-methylenedi(cyclohexylisocyanate, dissolved in N,N-diamethylaceramide, with a copolymer content of not less than 48 % by weight	0
ex 32.09 A II and ex 39.02 C XIV a)	Copolymer of p-cresol and divinylbenzene, dissolved in N, N-dimethylacetamide, with a copolymer content of not less than 48 % by weight	0
ex 35.07	Bromelains (INN)	0.
ex 35.07	Mixture of streptokinase (INN) and streptodornase (INN)	0
ex 35.07	Peroxidase	0
38.07 A	Gum spirits of turpentine	3
38.07 B	Spirits of sulphate turpentine; crude dipentene	3
38.07 C	Spirits of wood turpentine; terpenic solvents produced by the distillation or other treatment of coniferous woods; sulphite turpentine; pine oil (excluding 'pine oils' not rich in terpineol)	3

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provision.

	Common Customs Tariff heading No	Description	Rate of autonomous duty (%)
ex	38.08 C	Hydroabietyl alcohol	0
ex	38.19 G	Catalysts consisting essentially of diphosphorus pentaoxide on an inert support	0
ex	38.19 G	Catalysts in the form of spherical grains with a diameter of not less than 1.4 mm and not more than 1.8 mm consisting of boron trifluoride on an aluminium oxide support	0
ex .	38.19 G	Catalysts in the form of rodlets having a length of not more than 5.0 mm and in diameter of not more than 3.6 mm consisting of copper oxide and dichromium trioxide	0
ex	38.19 G	Catalysts consisting of copper chloride supported on aluminium oxide for the preparation of dichloroethane from ethylene, hydrochloric acid and oxygen, with a surface area of less than 90 m ² /g (^a)	0
,	ex 38.19 G	Catalysts consisting of chromium trioxide fixed on a silicon dioxide support with a pore volume, as determined by the nitrogen absorption method, of not less than 2 cm3/g	0
ex .	38.19 G	Catalysts in the form of rodlets having a length of not less than 3 mm and not more than 6 mm, and a diameter of not more than 3.8 mm, consisting of not less than 18 % and not more than 21 % by weight of dichromium trioxide and not less than 78 % and not more than 81 % by weight of aluminium oxide	
ex	38.19 G	Catalysts in the form of granules consisting of a mixture of oxides on a carrier of aluminium oxide and containing.by weight: — not less than 12 % and not more than 20 % of nickel, — not less than 5 % and not more than 10 % of copper, — not less than 0.5 % and not more than 1.5 % of manganese The pore volume is not less than 0.25 cm ³ /g and not more than 0.95 cm ³ /g and the	:
ex	38.19 G	apparent specific gravity is not less than 0.5 and not more than 1.25 Catalysts in the form of grains, of which not less than 90 % by weight have a particle size of less than 10 micrometres, consisting of a mixture of oxides on a carrier of magnesium silicate and containing by weight: — not less than 20 % and not more than 35 % of copper, — not less than 2 % and not more than 3 % of bismuth The catalyst has an apparent specific gravity of not less than 0.2 and not more than 1.0	0
	ex 38.19 G	Catalysts in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing not less than 20% and not more than 25% by weight of titanium and not less than 60% and not more than 72% by weight of chlorine, for manufacture of polypropylene or propylene copolymers (a)	0
сx	38.19 K	Sintered magnesite mixed with small quantities of mineral oils	o
	38.19 V	Crude calcium tartrate	3.5
ex	38.19 X	Lyophilized extract of the blood cells of the crab Limulus polyphemus (Lyophilized Limulus amebocyte lysate)	0
ex	38.19 X	Calcined bauxite (refactory grade)	0

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ех 38.19 Х	Diosgenin crude	0
ex 38.19 X	4-(6-Fluoro-2-methylinden-3-ylmethyl)phenyl methyl sulphide dissolved in toluene	0
ex 38.19 χ	Mixtures of x-butyl-4,4'-isopropylidenediphenol and x,x'-dibutyl-4,4'-isopropylidenediphenol	0
ex 38.19 [*] χ	Mixture of nitromethane and 1,2-epoxybutane	4
ex 38.19 ΄ χ	Reaction products containing not less than 55% by weight of 2-(2-p-chloro-phenylbenzoxazol-5-yl) propiononitrile	0
ex 38.19 X -	Residues of manufacture containing not less than 40 % by weight of 11-beta, 17,20,21-tetrahydroxy-6-methylpregna-1,4-dien-3-one 21-acetate	0
ex 38.19 X	Intermediate products from the manufacture of monensin salts	o ·
ex 38.19 .X	N-(2-Methyl-2-nitropropyl)-4-nitrosoaniline containing not less than 65 % by weight of an inert filler	0
ex 38.19 X	Tetramethylammonium hydroxide dissolved in methanol	0
ex 38.19 x	Intermediate products of the antibiotics manufacturing process obtained from the fermentation of Streptomyces tenebrarius, whether or not dried	0
ex 38.19 X	Dibutylmagnesium dissolved in organic solvents to a concentration of less than 28 % by weight	0
ex 38.19 X	Flame retardant reaction products of acetaldehyde, ethylene oxide and phosphorus trichloride containing by weight: — not less than 14 % and not more than 16 % of phosphorus, — not less than 27 % and not more than 33 % of chlorine	0
ex 38.19 X	Butylethylmagnesium dissolved in organic solvents to a concentration of not less than 19 % and not more than 22 % by weight	0
ex 39.01 A	Colestipol hydrochloride (INNM)	0
ex 39.01 C II a)	Polycondensation products of formaldehyde and a mixture of toluene-2-sul- phonamide and toluene-4-sulphonamide	0
ex 39.01 C III a)	Film base, in rolls, of polyethylene terephthalate, for cinematography or photography (including radiography)	8
ex 39.01 C III a)	Reflecting polyester sheeting wholly embossed on one side in a regular pyramidal pattern, whether or not in rolls	0
ex 39.01 C III b) and ex 39.03 B II b) 2, B III b) 4 aa) and B IV b) 4 aa)	Waste and scrap of photographic (including cinematographic) and X-ray film	0
ex 39.01 C III b)	Waste and scrap of polyester sheets coated with tungsten compounds	0
ex 39.01 C III b)	Polyester of a mixture of isophthalic acid and terephthalic acid with 4,4'-isopropylidenediphenol	0

CCT heading No	Description	Rate of autonomous duty (%)
ex 39.01 C V	Polyurethane polymers in one of the forms mentioned in Note 3 (a) to Chapter 39, based on a mixture of 2-methyl and 4-methyl-m-phenylene di-isocyanates and branched chain triols with an average molecular weight of not less than 6 000, and containing terminal epoxy groups	10
ex 39.01 C VII	Polyimide sheet and strip, whether or not in rolls	0
ex 39.01 C VII	Polyethylene oxide having a molecular weight of not less than 4 000 000	8
ex 39.01 C VII	Poly[oxy(2,6-dibromo-1,4-phenylene)] for use in the manufacture of polyamide (a)	o
ex 39.01 C VII	Poly(oxy-1,4-phenylenesulphonyl-1,4-phenyleneoxy-1,4-phenyleneisopropylidene- 1,4-phenylene), in one of the forms mentioned in Note 3 (b) to Chapter 39	0
ex 39.01 C VII	alpha-4-Hydroxybutyl-omega-hydroxypoly(oxytetramethylene)	0
ex 39.01 C VII	Liquid poly(oxypropylene) with 3-(3-[2-[2-(2-mercaptoethoxy)ethoxy]ethylthio]propoxy-carbonylamino)-p-tolylcarbamoyloxy as the end group	0
ex 39.02 A	Membranes consisting of a woven textile fabric coated on both sides with a copolymer of poly(tetrafluoroethylene) and poly[oxy(perfluoropropylene)] with carboxylic acid end groups, whether or not in rolls	0
ex 39.02 A	Membranes consisting of a woven fabric of which one side is coated with a copolymer of poly(tetrafluoroethylene) and poly[oxy(perfluoropropylene)] with carboxylic acid end groups, and the other side is coated with the same copolymer but with sulphonic acid end groups. whether or not in rolls	0
ex 39.02 C I b)	Transparent polyethylene film which will split longitudinally when stretched at right angles to its length, and having a density of not less than 0.925 gm/cc and yielding not less than 7 g/m² and not more than 19 g/m², for the manufacture of typewriter ribbon or similar ribbons (a)	0
ex 39.02 C II	Microporous polytetrafluoroethylene film, not less than 30 cm in width and weighing not more than 22.4 g/m² whether or not in rolls	0
ex 39.02 C II	Microporous polytetrafluoroethylene film coated on one side with a polymer permeable to water vapour, not less than 30 cm in width and weighing not more than 50 g/m², whether or not in rolls	0 '
ex 39.02 C III	Polysulphohaloethylenes in one of the forms mentioned in Note 3 (a) and (b) to Chapter 39	4
ex 39.02 C VI a)	An A-B-A block copolymer of polystyrene ethylene-butylene copolymer and polystyrene containing not more than 35 % by weight of styrene, in one of the forms mentioned in Note 3 (b) to Chapter 39	0
ex 39.02 C VI a) b)	Copolymers solely of allyl alcohol with styrene, which have an acetyl value of not less than 175	0
ex 39.02 C VI b)	Reflecting foil of a terpolymer of vinyl chloride with styrene and an acrylic ester embossed on one side with a regular pattern on which there is a thin layer of aluminium whether or not in rolls	0
ex 39.02 C VII b)	Polyvinyl chloride sheeting, whether or not in rolls, of a thickness less than 1 mm and coated with an adhesive in which are embedded hollow glass balls having a diameter of not more than 100 micrometres	0
ex 39.02 C VIII	Copolymers of vinylidene chloride with vinyl chloride, containing not less than 79.5 % by weight of vinylidene chloride, in one of the forms mentioned in Note 3 (a) and (b) to Chapter 39, for the manufacture of fibres, monofil or strip (a)	0

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

(h) The Additional Note to Chapter 58 shall aplly here

CCT heading No	Description	Rate of autonomous duty (%)
ex 39.02 C XI	Poly(vinyl formal), in one of the forms mentioned in Note 3 (b) to Chapter 39, having a molecular weight not less than 10 000 and not more than 40 000 and containing by weight:	
	- Not less than 9.5 % and not more than 13 % of the acetyl groups, expressed as vinyl acetate	
	— Not less than 5 % and not more than 6.5 % of the hydroxy groups, expressed as vinyl alcohol	0
ex 39.02 C XII	Poly(2-diethylaminoethyl methacrylate) dissolved in N,N-dimethylacetamide, with a polymer content of not less than 55 % by weight	. 0
ex 39.02 C XII	Copolymer of 2-di-isopropylaminoethyl methacrylate and decyl methacrylate dissolved in N,N-dimethylacetamide, with a copolymer content of not less than	
	55 % by weight	. 0
ex 39.02 C XII	Reflecting polyacrylic sheeting, whether or not in rolls	0
ex 39.02 C XII	Copolymerization products of acrylic and methacrylic esters in the form of film of a thickness not less than 50 and not more than 150 micrometres, whether or not in rolls	. 0
ex 39.02 C XII	Copolymer of acrylic acid and 2-ethylhexyl acrylate containing not less than 10% and not more than	
	11% by weight of 2-ethylhexyl acrylate	0
ex 39.02 C XIV a)	Copolymers of vinylidene chloride and acrylonitrile in the form of expandable beads of a diameter not less than four and not more than 20 micrometres	0
ex 39.02 C XIV a)	Copolymers of vinyl chloride with vinyl acetate and vinyl alcohol containing by weight not less than 89 % and not more than 92 % of vinyl chloride, not less than 2 % and not more than 6 % of vinyl acetate and not less than 4 % and not more than 8 % of vinyl alcohol, in one of the forms mentioned in Note 3 (a) and (b) to Chapter 39	.0
ex 39.02 C X(V a)	Fluorinated ethylene propylene copolymers, for the manufacture of flat (ribbon) cable, containing not less than 60 cores (a)	0
ex 39.02 C XIV a)	Poly(1-ethylethylene) (Polybutene-1) in one of the forms mentioned in Note 3 (b) to Chapter 39	0
ex 39.02 C XIV a)	Alternating copolymer of ethylene and maleic anhydride for use as a thickener in textile pigment printing pastes (a)	0
ex 39.02 C XIV a)	Polymerization products of acrylic acid with small quantities of polyunsaturated monomer for use as a thickener in textile pigment printing pastes (a)	0
ex 39.02 C XIV b)	Polyvinyl fluoride sheet, whether or not in rolls	0
ex 39.02 C XIV b)	Reflecting sheeting of an acrylic polymer modified by melamine-formaldehyde, whether or not in rolls	o
ex 39.02 C XIV b)	Polyvinylidene fluoride film, whether or not in rolls	. 0
39.03 B V a) 1	Ethylcellulose, not plasticized	4
ex 39.03 B V a) 2	Ethylhydroxyethylcellulose, insoluble in water	4
ex 39.03 B V a) 2	Hydroxypropylcellulose	o

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.
(b) The Additional Note to Chapter 58 shall apply here.

CCT heading No	· Description	Rate of autonomous duty (%)
ex 39.06 B	O-(2-hydroxyethyl)amylopectin hydrolysate	0
ex 39.07 B V d)	Perforated polyethylene film of a width of not less than 4.5 cm and not more than 5.5 cm and having a molecular weight of not less than 4 000 000 in rolls for use as conveyor belts in machines for manufacturing cigars (a)	0
ex 40.05 C	Strip, whether or not in rolls, consisting of polybutadiene-acrylonitrile containing, in the mass, glass microspheres, laminated on the upper surface with a polyvinyl chloride sheet also containing glass microspheres	0
41.02 B	Bovine cattle leather (including buffalo leather) not further prepared than chrome-tanned in the wet-blue state	0
ex 41.02 C	Leather of East India kip, whole, whether or not the heads and legs have been removed, each weighing more than 4.5 kg net and not more than 8 kg, not further prepared than vegetable tanned, whether or not having undergone further preservative treatment with oil, but obviously unsuitable for immediate use in the manufacture of leather articles	0
41.03 B I	Sheep and lambskin leather, except leather falling within heading No 41.06 or 41.08, other, not further prepared than tanned	0
41.04 B I	Goat and kid skin leather, except leather falling within heading No 41.06 or 41.08, other, not further prepared than tanned	o
41.05 B I	Other kinds of leather, except leather falling within heading No 41.06 or 41.08, other, not further prepared than tanned	O
ex 44.22 B	Used casks and barrels of oak, whether assembled or not; their staves and heads	0
ex 44.28 C	Match splints manufactured from aspen (Populus tremuloides) for the manufacture of matches not requiring a specific striking surface (so called 'strike-anywhere' matches) (*)	. 0
ex 44.28 D II	Shingles for roofs and walls of coniferous wood	0
45.01	Natural cork, unworked, crushed, granulated or ground; waste cork	, 0
45.02	Natural cork in blocks, plates, sheets or strips (including cubes or square slabs, cut to size for corks or stoppers)	4
ex 48.07 D	Kraft paper with latex addition to the stock, coated on one side with polybutadiene-styrene weighing not less than 104 g and not more than 130 g/m², for the manufacture of all-in-one disposable nappies (a)	. 6
ex 49.11 B	Microcopies on an opaque base for data banks and libraries (a)	0
ex 49.11 B	Artists' screen prints (commonly described as serigraphs), signed by the artist and numbered from 1 to 200	. 0
x 51.01 A	Yarn of polytetrafluorethylene	0
ex 51.01 A	Yarn of polyvinyl alcohol, soluble in water at a temperature of 50 °C for use in the manufacture of weftless 'felts' for papermaking machines (a)	0

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	. Description	Rate of autonomous duty (%)
ex 51.01 A	Yarn, multiple, of polyamide, coated, impregnated or covered with a phenolic resin	0
ex 51.01 A	Yarn of synthetic textile fibres of aromatic polyamides obtained by polycondensation of m-phenylenediamine and isophthalic acid	0
ex 51.01 A	Yarn of a copolymer of glycollic acid and lactic acid for the manufacture of surgical sutures (a)	0
ex 51.01 A	Yarn wholly of polyglycollic acid	0
ex 51.01 A	Yarn of poly(1,4-dioxanone)	o
ex 51.01 A	Polyamide yarn, not textured, untwisted or with not more than 22 turns per metre, of crimpable bicomponent filaments consisting of poly(hexamethylene adipamide) and a copolyamide for the manufacture of women's stockings falling within subheading 60.03 B II a) or panty hose (tights) falling within subheading 60.04 B IIIa) 1 (a)	0
ex 51.02 A I	Monofil of polytetrafluoroethylene	jo
ex 51.02 A I	Monofil of poly(1,4-dioxanone)	0
ex 51.02 A II	Polyimide strip, whether or not in rolls	0
ex 51.02 A II	Strip of polytetrafluoroethylene, whether or not in rolls with an extension at break not exceeding 25 %	0
ex 51:04 A IV	Woven fabrics of polyvinyl alcohol fibres for machine embroidery	0
ex 54.03 B I a)	Unbleached linen yarn (excluding yarn of flax tow), measuring per kg 30 000 m or less, for the manufacture of multiple or cabled yarns fot the footwear industry or for whipping cables (a)	
ex 56.01 A	Textile fibres of polytetrafluoroethylene	0
ex 56.01 A	Polyvinyl alcohol fibres	0
ex 58.07 A and ex 59.04	Braid wholly of polyglycollic acid yarn	0
ex 58.07 A and ex 59.04	Braid of yarn of a copolymer of glycollic acid and lactic acid, whether or not coated, for the manufacture of surgical sutures (4)	0
ex 59.04	Coir yarn, for the manufacture of carpets, carpeting and rugs, mats and the like (a)	0
ex 59.12	Cotton fabric coated with adhesive in which are embedded glass balls the diameters of which range from 45 to 75 micrometres, weighing not less than 300 g/m ² and not more than 550 g/m ²	· o
x 59.17 A	Needle punched synthetic fibre felts on a woven synthetic fibre base coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (a)	0
x 59.17 D	Yard of poly(p-phenyleneterephthalamide), impregnated, oiled	0
		1

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomous duty (%)
ex 59.17 D	Yarn and strip of impregnated polytetrafluoroethylene, whether or not oiled or graphited	0
62.03 A I	Sacks and bags, of a kind used for the packing of goods, used, of jute or of other textile bast fibres of heading No 57.03	0
62.03 B I a)	Sacks and bags of the kind used for the packing of goods, used, of flax or of sisal	0
ex 68.02 B	Artificially coloured granules and chippings	0
ex 69.09 B	Catalyst supports, consisting of porous cordierite ceramic pieces of roughly circular or oval cross-section with parallel sides, having an overall volume of not less than 240 ml and not more than 11 100 ml, and having a minimum dimension of not less than 70 mm and a maximum dimension of not more than 480 mm, having not less than 28 continuous channels per 100 mm² running parallel to the main axis of symmetry, the total channel cross-section area being not less than 50 % and not more than 80 % of the whole cross-section area	
o 70 10 A TV L		
ex 70.19 A IV b)	Glass beads of a diameter of less than 0.1 mm and with a refractive index of 2.26	0
ex 70.20 B	Glass-fibre yarns, with a filament diameter of not more than four micrometres, for the manufacture of carpets (a)	0
ex 70.20 B	Yarns of 33 tex or a multiple thereof obtained from continuous spun glass filaments having a diameter of not less than 2.5 and not more than 5.1 micrometres other than those treated so as to improve their adhesion to elastomers	0
ex 74.05 B	Non-rigid sheets and plates of polytetrafluoroethylene, with aluminium oxide as a filler or reinforced with glass-fibre fabric, laminated on both sides with copper foil	0
ex 75.04 A	Tubes of nickel, not alloyed, of a purity not less than 99 %, not deviating from straightness lengthwise by more than 1 mm per 150 cm of length, and with an outside diameter either:	.:
	- not less than 213 36 mm and not more than 214 mm	or
	- Not less than 209.95 mm and not more than 210.59 mm, or - Not less than 168.28 mm and not more than 168.78 mm	. 0 .
76.01 B I b)	Waste of aluminium, other (including factory rejects)	0
ex 76.03	Aluminium alloy strip in coils, containing not less than 18 % by weight and not more than 23 % by weight of tin and not less than 0.7 % by weight and not more than 1.5 % by weight of copper as the major alloying elements and having a width of not less than 75 and not more than 230 mm and a thickness of not less than 3 and not more than 6.5 mm	
ex 81.03 B	Wire of unalloyed tantalum, of a diameter not less than 0.2 mm and not more than 0.5 mm, for the manufacture of capacitors (a)	0
ex 81.04 D I b)	Chromium, in the form of cathode chips, pellets or briquettes, which contains not more than 0·10 % by weight of total oxygen, not more than 0·15 % by weight of total aluminium and not more than 0·001 % by weight of aluminium compounds insoluble in boiling 5N hydrochloric acid and in boiling fuming perchloric acid, and evaluated as aluminium, for the production of alloy for the manufacture of the following parts of gas turbines and jet engines (a)	
	- Blades, fixed or movable, including their rings	
	- Vanes - Nozzles	0
ex 81.04 G I	Electrolytic manganese of a purity of at least 99.7 %, for the chemical industry (a)	0
ex 81.04 K I	Waste and scrap titanium	0
ex 81.04 K I	Titanium sponge	. 0

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

CCT heading No	Description	Rate of autonomo duty
1/10		(%)
x 84.18 C IIb	Components of separators for the isolation of	
	gases in gas mixtures, consisting of a bundle	
	of permeable hollow fibres embedded at one end in a block of plastic material and passing through a	
	block of plastic material at the other end	0
-		
c 84.31 A	Suction roll shells, not drilled, being alloy steel tubes with a length of not less	
	than 5 207 mm and an outside diameter of not less than 754 mm for use in machinery for making paper or paperboard (a)	0
		1
- 04 50 D		1 .
x 84.59 B	Integrally forged, rough-turned components with unit weights of more than 150 tonnes, for reactor pressure vessels	0
-		
c 84.63 D	Forged and roughly shaped generator and turbine shafts of a weight exceeding 180 tonnes	0
c 90.01 B	Material consisting of a polarizing film, supported on one or both sides by transparent material	
	transparent material	. 0
	·	. :
	•	
	1	
		•
	1	
	·	
	1	

⁽a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.