

COMMISSION OF THE EUROPEAN COMMUNITIES

COM(81) 629 final

Brussels, 27 October 1981

Draft of a
COUNCIL REGULATION (EEC)
temporarily suspending the autonomous Common Customs Tariff duties
on certain industrial products

(submitted to the Council by the Commission)

COM(81) 629 final

EXPLANATORY MEMORANDUM

1. The subject of the following draft regulation is the temporary suspension of duties in the Common Customs Tariff for a number of industrial items, as requested by the Member States.
It is partly a prolongation and partly a new measure.
2. It seems appropriate to the Commission that a duty suspension is justified for the goods listed in the annex to this regulation. The Commission proposes a total suspension for those products for which Community production does not exist or is minimal. A partial suspension is proposed in cases where the Community production covers only a part of the requirements. The rate of the partially suspended duty depends on the extent of the possible Community supply to the Community users. The Commission is also always looking for the right balance between the interests of the suppliers, users and the consumers in the Community.
It also takes into account the need to protect employment.
3. The proposed measures are confined to six months because of the difficulties of estimating the evolution of the basic factors.
4. For a number of items for which the Member States also requested duty suspensions the Commission does not propose a tariff measure because the necessary conditions are not fulfilled. This concerns the following items.:

CCT heading No	Description
ex 28.55 A	<p>Phosphides of iron (ferro-phosphorous) containing by weight :</p> <ul style="list-style-type: none"> - not less than 68 % and not more than 72 % of iron; - not less than 22% and not more than 26% of phosphorous; - not more than 3.5% of silicon; <p>of which not less than 99% by weight is of a particle size of less than 30 micrometres; for the manufacture of varnish and paint</p>
ex 29.02 B	<p>1,6,7,8,9,14,15,16,17,18,18-Dodecachloropentacyclo(12.2.1.1^{6.9}.0^{2.13}.0^{5.10})octadeca-7,15-diene, for use in the manufacture of polypropylene</p>
ex 29.02 B	Hexabromocyclododecanes
ex 29.04 A III a)	2-Methylpropan-2-ol (tert-butyl alcohol) with a purity of not less than 90 % but not more than 98% by weight
ex 29.07 A	2,2', 6,6'-Tetrabromo-4,4'-isopropylidenediphenol
ex 29.07 C III	2,4-Dinitro-6-octylphenol
ex 29.11 C II	A mixture of 3- <i>o</i> -cumenyl-2-methylpropionaldehyde and 3- <i>p</i> -cumenyl-2-methylpropionaldehyde (cyclamen aldehyde)
ex 29.13 D I b)	17- <u>alpha</u> -21-Dihydroxy-16- <u>alpha</u> -methylpregna-1,4,9(11)-triene-3, 20-dione
ex 29.13 E	2,2',4,4'-Tetrahydroxybenzophenone
ex 29.13 E	2,4-Dihydroxybenzophenone (4-Benzoylerorcinol)

CCT heading No	Description
ex 29.14 C	Ethyl chrysanthemate
ex 29.14 D IV	Methyl 5-(2,4-Dichlorophenoxy)-2-nitrobenzoate
ex 29.22 A II	1,1,3,3-Tetramethyl butylamine
ex 29.22 D I	3,5-Dichloroaniline
ex 29.22 E II	<u>N</u> -Phenyl-1,4-phenylenediamine
ex 29.23 A II	1-Deoxy-1-(octylamino)- <i>D</i> -glucitol
ex 29.27	4-Bromophenylacetonitrile
ex 29.27	Octocriene (INN)
ex 29.38 BV	<u>RRR</u> -alpha-Tocopheryl acetate with a potency of not less than 1,100 IU/g
ex 29.39 D II	16-alpha-, 17-alpha-, 21-Trihydroxypregna-1,4,9(11)-triene-3,20-dione-21-acetate
ex 36.08 A	<p>Pyrophoric alloy, in the form of billets the dimensions of which are not less than 60 mm in length with a diameter of not less than 20 mm, containing by weight not less than :</p> <ul style="list-style-type: none"> - rare earth metals 77 % - iron 18 %
ex 38.19 G	<p>Catalysts consisting of a mixture of oxides on an silicon dioxide support and containing by weight:</p> <ul style="list-style-type: none"> (a) Not less than 25 % and not more than 40 % of antimony (b) Not less than 5 % and not more than 10 % of iron (c) Not less than 0.2 % and not more than 1.5 % of molybdenum (d) Not less than 0.8 % and not more than 4.0 % of tellurium
ex 38.19 G	Catalysts consisting of chromium trioxide fixed on a silicon dioxide support with a pore volume, as determined by the nitrogen absorption method, equal to or more than 2 cm ³ per gramme
ex 38.19 G	Catalysts in the form of rodlets having a length of not less than 3 mm and not more than 6 mm, and a diameter of not more than 3.8 mm, consisting of not less than 18% and not more than 21% by weight of dichromium trioxide and not less than 78% and not more than 81% by weight of aluminium oxide

CCT heading No	Description
ex 38.19 G	<p>Catalysts in the form of granules consisting of a mixture of oxides on a carrier of alluminium oxide and containing by weight :</p> <ul style="list-style-type: none">- not less than 12 % and not more than 20% of nickel;- not less than 5% and not more than 10% of copper;- not less than 0.5% and not more than 1.5% of manganese; <p>The pore volume is not less than 0.95 cm³/g and the apparent specific gravity is not less than 0.5 and not more than 1.25.</p>
ex 38.19 G	<p>Catalyst in the form of grains, of which not less than 90% by weight have a particle size of less than 10 micrometers, consisting of a mixture of oxides on a carrier of magnesium silicate and containing by weight:</p> <ul style="list-style-type: none">- not less than 20% and not more than 35% of copper;- not less than 2% and not more than 3% of bismuth. <p>The catalyst has an apparent specific gravity of not less than 0,2 and not more than 1,0.</p>
ex 38.19 U	<p>Reaction products containing not less than 65% by weight of benoxaproten (INN)</p>
ex 39.01 C III a)	<p>Reflecting polyester sheeting, whether or not in rolls</p>
ex 39.01 C V	<p>Polyurethane reflecting sheeting whether or not in rolls</p>
ex 39.01 C VII	<p>Polyoxy(2,6-dimethyl-1,4-phenylene), in one of the forms mentioned in Note 3(b) to Chapter 39.</p>
ex 39.02 C VII b).	<p>Reflecting polyvinyl chloride sheeting wholly embossed on one side in a regular pyramidal pattern, whether or not in rolls</p>

CCT heading No	Description
39.02 C XIV-a	Copolymers of ethylene and propylene containing not less than 90% by weight of propylene, in one of the forms mentioned in Note 3(b) to Chapter 39.
ex 51.01 A	Polyamide yarn, not textured, untwisted or with not more than 50 turns per metre, of crimpable bicomponent filaments consisting of poly(hexamethylene adipamide) and a copolyamide for the manufacture of women's stockings falling within subheading No 60.03 B II a) or panty hose (tights) falling within subheading No 60.04 B III a)
ex 70.20 B	Yarns of 34 tex or a multiple thereof obtained from continuous spun glass filaments having a diameter of not less than 5.2 and not more than 6.2 micrometres, other than those treated so as to improve their adhesion to elastomers
ex 70.20 B	Yarns of 33 tex or a multiple thereof obtained from continuous spun glass filaments having a diameter of not less than 5.8 and not more than 6.4 micrometres, other than those treated so as to improve their adhesion to elastomers
ex 70.20 B	Spun roving with a core of 600 tex, made from continuous glass fibre. The substance is coated with epoxy resin
ex 84.51 A	Portable machine for reading and writing Braille with tactile read-out and cassette recording systems equipped with a standard electromechanical Braille typewriter keyboard and an electromechanical Braille read-out unit with 20 characters, all contained in a case measuring 22 x 34 x 11 cm
ex 85.19 B	Potentiometers, contained in a housing whose diameter does not exceed 4.5 mm, whether or not fitted with an on/off switch, for the manufacture of products falling under tariff subheading 90.19 B I (a)
ex 85.21 D II	Electronic programmable read only memories (EPROMS) UV erasable, with a storage capacity of 32 K bits in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with a quartz window on the upper surface, and bearing: — an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: 2532 25 A 32 25 L 32 2732 or — other identification markings relating to EPROMS complying with the above-mentioned description

CCT heading No	Description																												
ex 85.21 D II	<p>Electronic programmable read only memories (EPROMS) UV erasable, with a storage capacity of 64 K bits in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 17 x 39 mm, with a quartz window on the upper surface, and bearing:</p> <ul style="list-style-type: none"> — an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: <ul style="list-style-type: none"> 2564 68764 68 A 764 or — other identification markings relating to EPROMS complying with the abovementioned description 																												
ex 85.21 D II	<p>Random access memories (RAMS) with a storage capacity of 64 K bits, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 9 x 23 mm with 16 connecting pins, and bearing:</p> <ul style="list-style-type: none"> — an identification marking either consisting of one of the following combinations of figures or including one of those combinations: <ul style="list-style-type: none"> 3764 4164 4864 6664 6665 8164 or — other identification markings relating to RAMS complying with the abovementioned description 																												
ex 85.21 D II	<p>C-MOS random access memories (RAMS of complementary MOS technology), with a storage capacity of 4 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 11 x 31 mm with 18, 20 or 22 connecting pins, and bearing:</p> <ul style="list-style-type: none"> — an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations: <table data-bbox="515 1598 949 1763" style="margin-left: 40px;"> <tbody> <tr> <td>21 SC 14</td> <td>5047</td> <td>6147</td> <td>8404 E</td> </tr> <tr> <td></td> <td>5104</td> <td>6148</td> <td>8414 E</td> </tr> <tr> <td>4315</td> <td>5114 A</td> <td>6504</td> <td></td> </tr> <tr> <td>4334</td> <td>5115</td> <td>6514</td> <td></td> </tr> <tr> <td>4434</td> <td>5504</td> <td>6533</td> <td></td> </tr> <tr> <td>μ PD 444</td> <td>5514</td> <td>6543</td> <td></td> </tr> <tr> <td>μ PD 445 L</td> <td>58981</td> <td></td> <td></td> </tr> </tbody> </table> or — other identification markings relating to C-MOS RAMS complying with the abovementioned description 	21 SC 14	5047	6147	8404 E		5104	6148	8414 E	4315	5114 A	6504		4334	5115	6514		4434	5504	6533		μ PD 444	5514	6543		μ PD 445 L	58981		
21 SC 14	5047	6147	8404 E																										
	5104	6148	8414 E																										
4315	5114 A	6504																											
4334	5115	6514																											
4434	5504	6533																											
μ PD 444	5514	6543																											
μ PD 445 L	58981																												

CCT heading No	Description
-------------------	-------------

ex 85.21 D II Programmable, non-erasable, read only memories (PROMS) with a storage capacity of 4 K bits in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 17 x 34 mm, with not more than 24 connecting pins, and bearing:

— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:

18 S 42	38510	74 S 472
18 S 46		74 S 473
18 SA 42	5340	74 S 474
18 SA 46	5341	74 S 475
	5348	74 S 476
24 S 41	5349	74 S 477
24 SA 41	5350	74 S 572
	5351	74 S 573
27 S 15	5352	
27 S 26	5353	7640
27 S 27		7641
27 S 28	54 S 472	7642
27 S 29	54 S 473	7643
27 S 30	54 S 474	7644
27 S 31	54 S 475	7645
27 S 32	54 S 476	7647
27 S 33	54 S 477	7648
	54 S 572	7649
	54 S 573	
28 L 42		
28 L 45	54 740	82 S 115
28 P 42	54 741	82 S 136
28 P 45		82 S 137
28 R 45	5605	82 S 140
28 S 42	5625	82 S 141
28 S 45		82 S 142
	6340	82 S 146
29620	6341	82 S 147
29621	6348	
29622	6349	93 438
29623	6350	93 448
29624	6351	93 452
29625	6352	93 453
29626	6353	
29627		
	7121	
3604	7122	
3624	7123	
3625	7125	
	7126	

or

— other identification markings relating to PROMS complying with the abovementioned description

ex 85.21 D II Single-chip microcomputer in the form of a monolithic integrated circuit consisting of an 8 bit central processor, and 8 bit timer, an internal clock,

18 input/output gates, a read only memory (ROM) with a capacity of 8 K bits and a random access memory (RAM) with a capacity of 512 bits, contained in a housing, whose exterior dimensions are 53 x 14 mm with 40 connecting pins

The package bears:

— one of the following markings:

D 8041
P 8041

or

— other markings relating to microcomputers complying with the abovementioned description

CCT heading No	Description																																																																																																											
ex 85.21 D II	Programmable, non-erasable, read only memories (PROMS) with a storage capacity of 8 K bits in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 34 mm, with not more than 24 connecting pins, and bearing:																																																																																																											
	— an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:																																																																																																											
	<table border="0"> <tr><td>24 S 81</td><td>29650</td></tr> <tr><td>24 SA 81</td><td>29651</td></tr> <tr><td></td><td>29652</td></tr> <tr><td>2708-65</td><td>29653</td></tr> <tr><td>27 S 180</td><td>3628</td></tr> <tr><td>27 S 181</td><td></td></tr> <tr><td></td><td>5380</td></tr> <tr><td>28 L 85</td><td>5381</td></tr> <tr><td>28 L 86</td><td>54 LS 478</td></tr> <tr><td>28 P 85</td><td>54 S 2708</td></tr> <tr><td>28 R 85</td><td>54 S 454</td></tr> <tr><td>28 S 2708</td><td>54 S 455</td></tr> <tr><td>28 S 85</td><td>54 S 478</td></tr> <tr><td>28 S 86</td><td>54 S 479</td></tr> <tr><td>28 SA 86</td><td></td></tr> <tr><td></td><td>6380</td></tr> <tr><td>29630</td><td>6381</td></tr> <tr><td>29631</td><td></td></tr> <tr><td>29632</td><td>7127</td></tr> <tr><td>29633</td><td>7128</td></tr> <tr><td>29634</td><td>7129</td></tr> <tr><td>29635</td><td>7130</td></tr> <tr><td>29636</td><td>7131</td></tr> <tr><td>29637</td><td>7132</td></tr> </table>	24 S 81	29650	24 SA 81	29651		29652	2708-65	29653	27 S 180	3628	27 S 181			5380	28 L 85	5381	28 L 86	54 LS 478	28 P 85	54 S 2708	28 R 85	54 S 454	28 S 2708	54 S 455	28 S 85	54 S 478	28 S 86	54 S 479	28 SA 86			6380	29630	6381	29631		29632	7127	29633	7128	29634	7129	29635	7130	29636	7131	29637	7132	<table border="0"> <tr><td>74 LS 478</td><td>TBPS 81 M</td></tr> <tr><td>74 S 2708</td><td>82707</td></tr> <tr><td>74 S 454</td><td>82708</td></tr> <tr><td>74 S 455</td><td>82 LS 180</td></tr> <tr><td>74 S 478</td><td>82 LS 181</td></tr> <tr><td>74 S 479</td><td>82 S 180</td></tr> <tr><td></td><td>82 S 181</td></tr> <tr><td></td><td>82 S 182</td></tr> <tr><td></td><td>82 S 183</td></tr> <tr><td></td><td>82 S 184</td></tr> <tr><td></td><td>82 S 185</td></tr> <tr><td></td><td>82 S 2708</td></tr> <tr><td></td><td>87 S 180</td></tr> <tr><td></td><td>87 S 181</td></tr> <tr><td></td><td>87 S 184</td></tr> <tr><td></td><td>87 S 185</td></tr> <tr><td></td><td>87 S 186</td></tr> <tr><td></td><td>87 S 187</td></tr> <tr><td></td><td></td></tr> <tr><td></td><td>93450</td></tr> <tr><td></td><td>93451</td></tr> <tr><td></td><td>93460</td></tr> <tr><td></td><td>93461</td></tr> <tr><td></td><td>93465</td></tr> <tr><td></td><td>93466</td></tr> <tr><td></td><td>93 L 450</td></tr> <tr><td></td><td>93 L 451</td></tr> <tr><td></td><td></td></tr> <tr><td></td><td>9460</td></tr> </table>	74 LS 478	TBPS 81 M	74 S 2708	82707	74 S 454	82708	74 S 455	82 LS 180	74 S 478	82 LS 181	74 S 479	82 S 180		82 S 181		82 S 182		82 S 183		82 S 184		82 S 185		82 S 2708		87 S 180		87 S 181		87 S 184		87 S 185		87 S 186		87 S 187				93450		93451		93460		93461		93465		93466		93 L 450		93 L 451				9460
24 S 81	29650																																																																																																											
24 SA 81	29651																																																																																																											
	29652																																																																																																											
2708-65	29653																																																																																																											
27 S 180	3628																																																																																																											
27 S 181																																																																																																												
	5380																																																																																																											
28 L 85	5381																																																																																																											
28 L 86	54 LS 478																																																																																																											
28 P 85	54 S 2708																																																																																																											
28 R 85	54 S 454																																																																																																											
28 S 2708	54 S 455																																																																																																											
28 S 85	54 S 478																																																																																																											
28 S 86	54 S 479																																																																																																											
28 SA 86																																																																																																												
	6380																																																																																																											
29630	6381																																																																																																											
29631																																																																																																												
29632	7127																																																																																																											
29633	7128																																																																																																											
29634	7129																																																																																																											
29635	7130																																																																																																											
29636	7131																																																																																																											
29637	7132																																																																																																											
74 LS 478	TBPS 81 M																																																																																																											
74 S 2708	82707																																																																																																											
74 S 454	82708																																																																																																											
74 S 455	82 LS 180																																																																																																											
74 S 478	82 LS 181																																																																																																											
74 S 479	82 S 180																																																																																																											
	82 S 181																																																																																																											
	82 S 182																																																																																																											
	82 S 183																																																																																																											
	82 S 184																																																																																																											
	82 S 185																																																																																																											
	82 S 2708																																																																																																											
	87 S 180																																																																																																											
	87 S 181																																																																																																											
	87 S 184																																																																																																											
	87 S 185																																																																																																											
	87 S 186																																																																																																											
	87 S 187																																																																																																											
	93450																																																																																																											
	93451																																																																																																											
	93460																																																																																																											
	93461																																																																																																											
	93465																																																																																																											
	93466																																																																																																											
	93 L 450																																																																																																											
	93 L 451																																																																																																											
	9460																																																																																																											
	or																																																																																																											
	— other identification markings relating to PROMS complying with the abovementioned description																																																																																																											
ex 85.21 D II	CRT controllers in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 16 x 54 mm with not more than 40 connecting pins, and bearing:																																																																																																											
	- an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations:																																																																																																											
	<table border="0"> <tr><td>5027</td></tr> <tr><td>DP 8350</td></tr> <tr><td>HD 46505</td></tr> </table>		5027	DP 8350	HD 46505																																																																																																							
5027																																																																																																												
DP 8350																																																																																																												
HD 46505																																																																																																												
	or																																																																																																											
	- other identification markings relating to CRT controllers complying with the abovementioned description																																																																																																											

CCT heading No	Description
ex 85.21 D II	<p>C-MOS read/write static random access memories (RAMS of complementary MOS technology), with a storage capacity of 16 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 15 x 34 mm, with 24 connecting pins, and bearing:</p> <ul style="list-style-type: none">- an identification marking either consisting of the following combination of figures and letters or including this combination : HM 6116 <p>or</p> <ul style="list-style-type: none">- other identification markings relating to C-MOS RAMS complying with the abovementioned description
ex 85.21 D II	<p>H-MOS read/write random access memories (RAMS of H-MOS technology), with a storage capacity of 4 K-bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 8 x 24 mm, with 18 connecting pins, and bearing :</p> <ul style="list-style-type: none">- an identification marking either consisting of one of the following combinations of figures or figures and letters or including one of those combinations : 2114 TMM 314 <p>or</p> <ul style="list-style-type: none">- other identification markings relating to H-MOS RAMS complying with the abovementioned description
ex 85.21 D II	<p>Programmable non-erasable read only memories (PROMS) of TTL-Schottky technology, with a storage capacity of 1K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 8 x 21 mm, with 16 connecting pins and bearing :</p> <ul style="list-style-type: none">- one of the following identification markings: 82 S 12 9 HM 7611-5 MMI 6301-1 <p>or,</p> <ul style="list-style-type: none">- other identification markings relating to PROMS complying with the abovementioned description

CCT heading No	Description																																				
ex 85.21 D II	<p>Programmable read only memories (PROMS), manufactured by means of the Schottky process, with a storage capacity of 2 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 15 x 35 mm, with 16, 20 or 24 connecting pins and bearing :</p> <p>- one of the following identification markings: TBP 28 L 22 MMI 6306-1</p> <p>or,</p> <p>- other identification markings relating to PROMS complying with the abovementioned description</p>																																				
ex 85.21 D II	<p>Single chip microcomputer in the form of a monolithic integrated circuit consisting of an arithmetical unit with a capacity of 8 bits, a 12 bit timer, a read only memory (ROM) with a capacity of 32 K bits and a random access memory (RAM) with a capacity of 1 K bits, with 48 input/output gates and contained in a housing whose exterior dimensions do not exceed 16.5 x 42 mm, with 64 connecting pins. The package bears the identification markings of PD 7801 or other identification markings relating to microcomputers complying with the abovementioned description</p>																																				
ex 85.21 D II	<p>Programmable read only memories (PROMS) with a storage capacity of 16 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 34 mm, with not more than 24 connecting pins and bearing one of the identification markings :</p> <table data-bbox="707 1469 1161 2048"><tbody><tr><td>TBP 28 R 166</td><td>DM 77S190</td></tr><tr><td>TBP 28 P 166</td><td>MM 82S190</td></tr><tr><td>TBP 28 S 166</td><td>HM 7616-5</td></tr><tr><td>93510 M</td><td>HM76161-5</td></tr><tr><td>SM 82S190</td><td>3636</td></tr><tr><td>SM 82S191</td><td>M 3636</td></tr><tr><td>29681A</td><td>DM 7 7S 191</td></tr><tr><td>29683A</td><td>29681</td></tr><tr><td>93510C</td><td>N 82S191</td></tr><tr><td>93511C</td><td>MN 82S191</td></tr><tr><td>SM 82S190</td><td>29683</td></tr><tr><td>SM 82S191</td><td>HM76160-2</td></tr><tr><td>93511M</td><td>S 82S190</td></tr><tr><td>3636-I</td><td>HM 7616-2</td></tr><tr><td>DM 87S190</td><td>HM 76161-2</td></tr><tr><td>DM 87S191</td><td>S 82S191</td></tr><tr><td>TBP 28L166</td><td></td></tr><tr><td>HM 76160-5</td><td></td></tr></tbody></table> <p>or other identification markings relating to PROMS complying with the abovementioned description</p>	TBP 28 R 166	DM 77S190	TBP 28 P 166	MM 82S190	TBP 28 S 166	HM 7616-5	93510 M	HM76161-5	SM 82S190	3636	SM 82S191	M 3636	29681A	DM 7 7S 191	29683A	29681	93510C	N 82S191	93511C	MN 82S191	SM 82S190	29683	SM 82S191	HM76160-2	93511M	S 82S190	3636-I	HM 7616-2	DM 87S190	HM 76161-2	DM 87S191	S 82S191	TBP 28L166		HM 76160-5	
TBP 28 R 166	DM 77S190																																				
TBP 28 P 166	MM 82S190																																				
TBP 28 S 166	HM 7616-5																																				
93510 M	HM76161-5																																				
SM 82S190	3636																																				
SM 82S191	M 3636																																				
29681A	DM 7 7S 191																																				
29683A	29681																																				
93510C	N 82S191																																				
93511C	MN 82S191																																				
SM 82S190	29683																																				
SM 82S191	HM76160-2																																				
93511M	S 82S190																																				
3636-I	HM 7616-2																																				
DM 87S190	HM 76161-2																																				
DM 87S191	S 82S191																																				
TBP 28L166																																					
HM 76160-5																																					

CCT heading No.	Description
ex 85.21 D II	<p>Random access memories, of <u>N</u>-MOS technology, in which information is stored in bi-stable elements (N-MOS Static RAMS), with a storage capacity of 16 K x 1 bit, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 34 mm with 20 or 24 connecting pins and bearing :</p> <ul style="list-style-type: none">- one of the following identification markings <p style="margin-left: 40px;">2167 IMS 1400 - 70 IMS 1400 - 55 IMS 1400 - 45</p> <p>or,</p> <ul style="list-style-type: none">- other identification markings relating to <u>N</u>-MOS Static RAMS complying with the above description
ex 85.21 D II	<p>Integrated circuit, "semi-custom" built by means of the low absorption TTL (transistor-transistor logic) Schottky process; it contains 512 internal gates with dual NAND input, 60 input and 48 output buffers. The internal delay time is 1.8 nanoseconds. It is encapsulated in a 64-pin plastic quad package (each side 25 mm)</p>
ex 85.21 D II	<p>Static random access memories of <u>N</u>-MOS technology (N-MOS Static RAMS) with a storage capacity of 2 x 8 K bits in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 17 x 34 mm, with 24 connecting pins and bearing the identification marking TMS 4016, or other identification markings relating to static RAMS complying with the above description</p>
ex 85.21 D II	<p>Digital displays of a size not exceeding 12 mm by 20 mm, consisting of a printed circuit board on which are mounted under a transparent plastic cover, up to 22 light emitting diodes manufactured from gallium-based semi-conductor compounds. Each display consists of a single character with or without a plus or minus sign and/or one or two dots.</p>
ex 85.21 D II	<p>Static random access memories of N-MOS technology (N-MOS static RAMS) with a storage capacity of 4 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 9 x 24 mm, with 18 connecting pins and bearing :</p> <ul style="list-style-type: none">- the identification marking : TMS 2147, <p>or</p> <ul style="list-style-type: none">- other identification markings relating to Static RAMS complying with the above description

5. Attention is drawn to the fact that the Council Resolution of 27.6.1974 simplifying the task of the customs administrations (O.J. C 79/80) requires the publication of the attached Regulation at least six weeks before its entry into force.

Draft
COUNCIL REGULATION (EEC)

**temporarily suspending the autonomous Common Customs Tariff duties on
certain industrial products**

THE COUNCIL OF THE EUROPEAN
COMMUNITIES,

Having regard to the Treaty establishing the European
Economic Community, and in particular Article 28
thereof,

Having regard to the draft Regulation submitted by
the Commission,

Whereas production of the products referred to in this
Regulation is at present inadequate or non-existent
within the Community and producers are thus unable
to meet the needs of user industries of the Commu-
nity;

Whereas it is in the Community's interest in certain
cases to suspend the autonomous Common Customs
Tariff duties only partially, particularly because of the
existence of Community production, and in other
cases to suspend them completely;

Whereas, taking account of the difficulties involved in
accurately assessing the development of the economic
situation in the sectors concerned in the near future,
these suspension measures should be taken only
temporarily, by fixing their period of validity by refer-
ence to the interests of Community production,

HAS ADOPTED THIS REGULATION :

Article 1

From 1 January to 30 June 1982 the autonomous
Common Customs Tariff duties for the products listed
in the Annex hereto shall be suspended at the level
indicated in respect of each of them.

Article 2

This Regulation shall enter into force on 1 January
1982.

This Regulation shall be binding in its entirety and directly applicable in all Member
States.

Done at Brussels,

For the Council

The President

CCT heading No	Description	Rate of autonomous duty (%)
ex 28.39 A	Potassium nitrite for the manufacture of cooling and cutting fluids for working metal (a)	0
ex 29.04 A III a)	2-Methylpropan-2-ol (<i>tert</i> -butyl alcohol) with a purity of not less than 90 % but not more than 96 % by weight	0
ex 29.08 A III c)	2-Bromo-6-methoxynaphthalene	0
29.15 B	1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride (1,4,5,6,7,7-hexachlorobicyclo-(2.2.1)hept-5-ene-2,3-dicarboxylic anhydride)	0
ex 29.16 A II	<i>L</i> -Malic acid and its salts and esters	0
ex 29.19 C	2,2-Bis(chloromethyl) trimethylene tetrakis(2-chloroethyl) bis(phosphate)	5
ex 29.19 C and ex 38.19 U	Tetrakis(2-chloroethyl) ethylene bis (phosphate)	5
ex 29.25 A II	2-Acrylamido-2-methylpropanesulphonic acid	0
ex 29.25 B III b)	Bendiocarb (ISO)	0
ex 29.29	3,3-Bis (3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)- <u>N-N'</u> -bipropionamide	0
ex 29.31 B	Biosynthetic peptide having the structure of the 'A' chain of human insulin, in the form of a salt of the <i>S</i> -sulphonate derivative	0
ex 29.31 B	4,4'-Sulphonyldiphenol, not less than 99.5 % pure	0
ex 29.34 C	Trichloronat (ISO)	0
ex 29.35 Q	Biosynthetic peptide having the structure of the 'B' chain of human insulin, in the form of a salt of the <i>S</i> -sulphonate derivative	0
ex 29.35 Q	Diazoxide (INN)	0
ex 29.35 Q	(6 <i>R</i> ,7 <i>R</i>)-7-Amino-3-(5-methyl-1,3,4-thiadiazol-2-ylthiomethyl)-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid and its salts	0
ex 29.35 Q	Tolmetin sodium (INN)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ANNEX

CCT heading No	Description	Rate of autonomous duty (%)
ex 29.35 Q	Captopril (INN)	0
ex 29.39 D II	Betamethasone 17,21-dipropionate (INN)	0
ex 29.39 D II	Methylprednisolone (INN)	8
ex 29.39 D II	Triamcinolone hexacetonide (INN)	6.6
ex 29.39 D II	Diflorasone di (acetate) (INN)	0
ex 29.44 C	Cefoxitin sodium (INN)	0
ex 29.44 C	Cefradine (INN)	0
ex 29.44 C	Cefamandol (INN) and its salts and esters	0
ex 29.44 C	Cefazolin (INN) and its salts	0
ex 29.44 C	(6R, 7R)-7-[2-Carboxy-2-(4-hydroxyphenyl)acetamido]-7-methoxy-3-(1-methyl-1H-tetrazol-5-ylthiomethyl)-8-oxo-5-oxa-1-azabicyclo[4.2.0]-oct-2-ene-2-carboxylic acid and its salts and esters	0
ex 30.03 A II b	Mitomycin (INN)	0
ex 38.03 B	Acid activated montmorillonite which, when examined by X-ray powder diffraction, shows four principal lines corresponding to crystal interplane spacing (d values) of 0.44, 0.40, 0.33 and 0.25 nm the line corresponding to 0.40 nm being the most intense, for the manufacture of self-copy paper (a)	0
38.07 A	Gum spirits of turpentine	3
38.07 B	Spirits of sulphate turpentine; crude dipentene	3
38.07 C	Spirits of wood turpentine; terpenic solvents produced by the distillation or other treatment of coniferous woods; sulphite turpentine; pine oil (excluding 'pine oils' not rich in terpineol)	3
ex 38.08 C	Rosin hydrogenated, polymerized, dimerized or oxidized	5
ex 38.19 G	Catalysts in the form of rodlets having a diameter of not less than 1.5 mm and not more than 9.5 mm, containing not less than 60 % by weight of diiron-trioxide, not less than 8 % by weight of dipotassiumoxide and not less than 0.5 % by weight of dichromiumtrioxide, for use in the production of styrene from ethylbenzene (a)	0
ex 38.19 G	Catalysts in the form of rodlets having a length of not more than 5.0 mm and in diameter of not more than 3.6 mm consisting of copper oxide and dichromium trioxide	0
ex 38.19 G	Catalysts, in the form of granules or rings having a diameter of not less than 3 mm and more than 10 mm, consisting of silver supported on aluminium oxide, the silver content being not less than 10 % and not more than 20 % by weight	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ANNEX

CCT heading No	Description	Rate of autonomous duty (%)
ex 38.19 G	Catalysts consisting of copper chloride supported on aluminium oxide for the preparation of dichloroethane from ethylene, hydrochloric acid and oxygen, with a surface area of less than 90 m ² /g (a)	0
ex 38.19 U	Dibutylmagnesium dissolved in organic solvents to a concentration of less than 28 % by weight	0
ex 38.19 U	Flame retardant reaction products of acetaldehyde, ethylene oxide and phosphorous trichloride containing by weight : - not less than 14% and not more than 16% of phosphorus - not less than 27% and not more than 33% of chlorine	0
ex 38.19 U	Butylethylmagnesium dissolved in organic solvents to a concentration of not less than 19% and not more than 22%	0
ex 39.01 C III a)	Reflecting polyester sheeting in which glass microspheres are dispersed, whether or not in rolls	0
ex 39.01 C V	Reflecting polyurethane sheeting in which glass microspheres are dispersed, whether or not in rolls	0
ex 39.01 C VII	<i>alpha</i> -4-Hydroxybuthyl- <i>omega</i> -hydroxypoly (oxytetramethylene)	0
ex 39.01 C VII	Liquid poly(oxypropylene) with 3-(3-{2- $\bar{2}$ -(2-mercaptoethoxy)ethoxy/ethylthio} propoxycarbonylamino)- <i>p</i> -tolylcarbonoxyloxy as terminal group	0
ex 39.02 C I b)	Transparent polyethylene film which will split longitudinally when stretched at right angles to its length, and having a density of not less than 0.925 gm/cc and yielding not less than 7 g/m ² and not more than 19 g/m ² , for the manufacture of typewriter ribbon (a)	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ANNEX

CCT heading No	Description	Rate of autonomous duty (%)
39.02 C XIV b)	Ion-exchange membranes consisting of a woven fabric of which one side is coated with a copolymer of poly(tetrafluoroethylene) and poly(oxy(perfluoropropylene) with carboxylic acid end groups and the other side is coated with the same copolymer but with sulphonic acid end groups, whether or not in rolls	0
ex 39.02 C VI b)	Reflecting foil of a terpolymer of vinyl chloride with styrene and an acrylic ester embossed on one side with a regular pattern on which there is a thin layer of aluminium whether or not in rolls	0
ex 39.02 C XIV a)	Terpolymer of ethylene, methyl acrylate and a monomer containing a non-terminal carboxy group as a substituent, compounded with silica	12.5
ex 39.02 C XIV a)	Alternating copolymer of ethylene and maleic anhydride for use as a thickener in textile pigment printing pastes (a)	5
ex 39.02 C XIV a)	Polymerization products of acrylic acid with small quantities of a polyunsaturated monomer for use as a thickener in textile pigment printing pastes (a)	5
ex 39.02 C XIV b)	Sheets consisting of a woven textile fabric covered on both sides with a copolymer of poly(tetrafluoroethylene) and poly[oxy(perfluoro-2-methylethylene)] with terminal carboxyl groups, whether or not in rolls	0
ex 44.28 C	Match splints manufactured from aspen (<i>Populus tremuloides</i>) for the manufacture of matches, not requiring a specific striking surface (so called 'strike-anywhere matches) (a)	0
ex 51.01 A	Yarn of a copolymer of glycollic acid lactic acid for the manufacture of surgical sutures (a)	0
ex 51.01 A	Yarn wholly of polyglycollic acid	0
ex 51.01 A	Yarn of poly(<i>p</i> -phenyleneterephthalamide), for uses other than the manufacture of tyres (a)	2
ex 51.01 A	Yarn of poly(1,4-Dioxanone)	0
ex 51.02 A I	Monofil of poly(1,4-Dioxanone)	0
ex 56.01 A and ex 59.01 B I	Fibres of poly(<i>p</i> -phenyleneterephthalamide)	2
ex 56.01 A	Polyvinyl alcohol fibres	0
ex 58.07 A and ex 59.04	Braid wholly of polyglycollic acid yarn	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ANNEX

CCT heading No	Description	Rate of autonomous duty (%)
ex 58.07 A and ex 59.04	Braid of yarn of a copolymer of glycollic acid and lactic acid, whether or not coated, for the manufacture of surgical sutures (a)	0
ex 59.17 A	Needle punched synthetic fibre felts on a woven synthetic fibre base coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (a)	0
ex 59.17 D	Yarn of poly(p-phenyleneterephthalamide), impregnated, oiled	0
ex 84.18 C II b)	Apparatus, for the separation of gas from gas mixtures, of a total length of not less than 375 cm and not more than 690 cm consisting essentially of a metal cylinder, whose diameter is not less than 10.5 cm and not more than 22.5 cm, containing bundles of hollow permeable fibres	0
ex 84.55 C	Opto-electric encoder for electronic typewriters consisting of electronic circuits, a light-emitting diode (LED), a rotating disc with radial openings, a fixed mask and a single chip photovoltaic cell, contained in two plastic shells forming a housing of a size not exceeding 60 x 48 x 16 mm	0
ex 85.21 A V	Digital displays in the form of a tube consisting of a glass housing mounted on a board whose dimensions do not exceed 350 x 300 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallized base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons	0
ex 85.21 D II	Digital displays consisting of a printed circuit board of a size not exceeding 35 x 90 mm with a single line of digits, not less than three in number comprising light-emitting diodes manufactured from gallium-based semi-conductor compounds mounted thereon. Each digit is composed of seven segments plus a decimal point and the line of digits has a protective cover of transparent plastic	0
ex 85.21 D II	Digital displays, consisting of a printed circuit board of a size not exceeding 35 x 90 mm with a single line of characters not less than two in number comprising light-emitting diodes made from gallium-based semi-conductor compounds mounted thereon. Each character is composed of up to eight segments and the line of characters has a protective cover of transparent plastic	0
ex 85.21 D II	<p>P-MOS 12/24-hour clock circuit incorporating an elapsed time facility, in the form of a monolithic integrated circuit contained in a housing whose exterior dimensions do not exceed 53 x 14 mm, with 40 connecting pins, for the manufacture of instrument panel clocks and clocks of a similar type for vehicles (a)</p> <p>The package bears:</p> <ul style="list-style-type: none"> — the following identification marking: <p style="margin-left: 40px;">MM 53124</p> <p style="margin-left: 40px;">or</p> <ul style="list-style-type: none"> — other identification markings relating to clock circuits complying with the abovementioned description 	0

(a) Control of the use for this special purpose shall be carried out pursuant to the relevant Community provisions.

ANNEX

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Single-chip microcomputer, in the form of a monolithic integrated circuit, consisting of an arithmetical unit with a capacity of 4 bits plus a read only memory (ROM) with a capacity of not less than 18 K bits and not more than 65 K bits and a random access memory (RAM) with a capacity of not less than 512 bits and not more than 4 K bits, contained in a housing whose exterior dimensions do not exceed 16 x 54 mm with not more than 40 connecting pins</p> <p>The package bears:</p> <p>— one of the following identification markings:</p> <ul style="list-style-type: none"> CD 3200 to 3299 TMC 0270 to 0279 TMC 0500 to 0599 TMC 0980 to 0989 TMC 1500 to 1599 TMC 1980 to 1999 TP 0310 to 0329 TP 0450 to 0459 TP 0480 to 0489 TP 0500 to 0599 <p>or</p> <p>— other identification markings relating to microcomputers complying with the abovementioned description</p>	0
ex 85.21 D II	<p>Amplifier in the form of a monolithic integrated analog circuit contained in a housing whose dimensions do not exceed 3.56 x 3.56 x 1.65 mm with not more than 10 connecting pins for use in products falling within subheading 90.19 B I (a)</p> <p>The package bears:</p> <p>— one of the following identification markings:</p> <ul style="list-style-type: none"> V 35 C 05 <p>or</p> <p>— other identification markings relating to amplifiers complying with the abovementioned description</p>	0
ex 85.21 D II	<p>N-MOS read/write static random access memories (RAMS of N-MOS technology), with a storage capacity of 8 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 8 x 24 mm, with 18 connecting pins and bearing :</p> <p>- the following identification marking :</p> <p style="text-align: center;">8185</p> <p>or</p> <p>- other identification markings relating to N-MOS Static RAMS complying with the abovementioned description</p>	0

ANNEX

CCT heading No	Description	Rate of autonomous duty (%)
ex 85.21 D II	<p>Random access memories of emitter coupled logic technology (ECL RAMS) with a storage capacity of 16 K bits, in the form of a monolithic integrated circuit, contained in a housing whose exterior dimensions do not exceed 11 x 31 mm, with 20 connecting pins and bearing:</p> <ul style="list-style-type: none">- one of the following identification markings: 10480or 100480- other identification markings relating to ECL RAMS complying with the abovementioned description	0